



Liqui-Gem. Marquise Cut Gel

BASEBOARD STRIPPER SPRAY

REMOVES WAX & FLOOR FINISH
FROM BASEBOARDS, STAIRS,
FLOOR EDGES, CORNERS
TILES AND PORCELAIN

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONS.

DANGER

Contains gas under pressure; may explode if heated.
May be corrosive to metals.
Causes severe skin burns and eye damage.

NET WEIGHT: 20 oz. (567 g)

FOR INDUSTRIAL/PROFESSIONAL USE ONLY.
NOT FOR RETAIL SALE.

LIQUI-GEM MARQUISE CUT GEL heavy duty cleaner removes copolymer floor finishes and wax from baseboards, floor edges and moldings, stairs, corners, tiles and porcelain. The special spray valve operates in the inverted position for easy application. **LIQUI-GEM MARQUISE CUT GEL's** clinging gel holds to vertical surfaces to loosen heavy accumulations of floor finish.



DANGER:

Contains gas under pressure; may explode if heated. May be corrosive to metals. Causes severe skin burns and eye damage.

PREVENTION:

Keep only in original container. Do not breathe mist. Wash thoroughly after handling. Wear protective gloves, protective clothing, eye protection, face protection.

RESPONSE:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a doctor, a POISON CENTER. Specific treatment (see First aid measures on this label). Wash contaminated clothing before reuse. Absorb spillage to prevent material damage.

STORAGE:

Store locked up. Store in corrosive resistant container with a resistant inner liner. Protect from sunlight. Store in a well-ventilated place.

DISPOSAL:

Dispose of contents/container to comply with local/regional/national/international regulations.

INGREDIENTS/CAS#: Butane (106-97-8); Glycol Ether EB (111-76-2); 2-aminoethanol, ethanalamine (141-43-5); Propane (74-98-6)

NFPA® RATING:

Health: 2; Flammability: 4; Reactivity: 0

DIRECTIONS:

- Always test this product in an inconspicuous area to be cleaned before using. Immediately wipe any overspray from furniture, walls and other surfaces.
- Shake well and hold can in inverted position.
- Hold can 6 to 10 inches from surface and spray a thin coating over areas to be stripped.
- Let stand for 3-5 minutes.
- For stubborn build-up of wax or floor finish, rub with sponge or scrub pad.
- Wipe residue from surface with wet sponge.



Please Recycle.

KEEP OUT OF REACH OF CHILDREN

Refer to SDS for further information.

8177.051815

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com