Melt Down
Safety Data Sheet

SECTION 1: Product and company identification

Product name	:	Melt Down
Use of the substance/mixture	:	Cleaner
Product code	:	042901
Company	:	Share Corporation P.O. Box 245013 Milwaukee, WI 53224 - USA T (414) 355-4000
Emergency number	:	Chemtrec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Met. Corr. 1	H290
Acute Tox. 4 (Oral)	H302
Skin Corr. 1B	H314

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :

GHS05 GHS07

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) :
May be corrosive to metals
Harmful if swallowed
Causes severe skin burns and eye damage

Precautionary statements (GHS-US) :
Keep only in original container
Do not breathe mist, spray
Wash thoroughly after handling
Do not eat, drink or smoke when using this product
Wear eye protection, protective clothing, protective gloves
If swallowed: Call a doctor, a POISON CENTER if you feel unwell
If swallowed: rinse mouth. Do NOT induce vomiting
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
If inhaled: Remove person to fresh air and keep comfortable for breathing
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Immediately call a doctor, a POISON CENTER
Specific treatment (see First aid measures on this label)
Rinse mouth
Wash contaminated clothing before reuse
Absorb spillage to prevent material damage
Store locked up
Store in corrosive resistant container with a resistant inner liner
Dispose of contents/container to comply with local/regional/national/international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
potassium hydroxide, 45%=<conc<50%, aqueous solutions	(CAS No) 1310-58-3	10-30	Met. Corr. 1, H290 Acute Tox. 3 (Oral), H301 Skin Corr. 1A, H314
Diethylene Glycol Monoethyl Ether	(CAS No) 111-90-0	3-7	Acute Tox. 4 (Oral), H302 Eye Irrit. 2A, H319
Sodium xylene sulphonate	(CAS No) 1300-72-7	1-5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Gluconic Acid	(CAS No) 526-95-4	1-5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
tetrapotassium pyrophosphate, anhydrous	(CAS No) 7320-34-5	1-5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.

First-aid measures after skin contact : Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes severe skin burns and eye damage. Harmful if swallowed.

Symptoms/injuries after inhalation : May cause respiratory irritation.

Symptoms/injuries after skin contact : Caustic burns/corrosion of the skin.

Symptoms/injuries after eye contact : Causes serious eye damage. Corrosion of the eye tissue. Permanent eye damage.

Symptoms/injuries after ingestion : Harmful if swallowed. Burns to the gastric/intestinal mucosa. Gastrointestinal complaints.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : All extinguishing media allowed.

5.2. Special hazards arising from the substance or mixture

Reactivity : Upon combustion: CO and CO2 are formed.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Take account of environmentally hazardous firefighting water.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Isolate from fire, if possible, without unnecessary risk.

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Protective goggles. Protective clothing.

Emergency procedures : Evacuate unnecessary personnel. Avoid contact with skin, eyes and clothing. Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent soil and water pollution.

6.3. Methods and material for containment and cleaning up

For containment : Contain released substance, pump into suitable containers.

Methods for cleaning up : This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Comply with the legal requirements. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Do not get in eyes, on skin, or on clothing.

Hygiene measures : Wash thoroughly after handling. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep container closed when not in use. Store locked up. Store in corrosive resistant container with a resistant inner liner.

Incompatible products : acids.

Incompatible materials : Heat sources. Open flame.

Storage area : Keep only in the original container. Store in a dry area. Store in a cool area.

Special rules on packaging : meet the legal requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

potassium hydroxide, 45%=<conc<50%, aqueous solutions (1310-58-3)		
ACGIH	ACGIH Ceiling (mg/m³)	2 mg/m³

8.2. Exposure controls

Personal protective equipment : Use appropriate personal protective equipment when risk assessment indicates this is necessary. Gloves. Safety glasses. Protective clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : clear. straw yellow. Liquid.

Odor : slight Ether

Odor threshold : No data available

pH : 13 - 14

Melting point : No data available

Freezing point : No data available

Boiling point : No data available

Flash point : > 200 °F Closed Cup

Relative evaporation rate (butyl acetate=1) : No data available

Flammability (solid, gas) : No data available

Explosion limits : No data available

Explosive properties : No data available

Oxidizing properties : No data available

Vapor pressure : No data available

Relative density : No data available

Relative vapor density at 20 °C : No data available

Specific gravity / density : 1.1 g/ml

Solubility : Soluble in water.

Log Pow : No data available

Log Kow : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity : No data available

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

VOC content : 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity
Upon combustion: CO and CO2 are formed.

10.2. Chemical stability
Stable under normal conditions.

10.3. Possibility of hazardous reactions
Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid
No additional information available

10.5. Incompatible materials
May be corrosive to metals.

10.6. Hazardous decomposition products
Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed.

Diethylene Glycol Monoethyl Ether (111-90-0)	
LD50 oral rat	1920 mg/kg

potassium hydroxide, 45%=<conc<50%, aqueous solutions (1310-58-3)	
LD50 oral rat	273 mg/kg (Rat)
ATE CLP (oral)	273.000 mg/kg body weight

tetrapotassium pyrophosphate, anhydrous (7320-34-5)	
LD50 dermal rabbit	> 4640 mg/kg (Rabbit)

Skin corrosion/irritation : Causes severe skin burns and eye damage.
pH: 13 - 14

Serious eye damage/irritation : Not classified
pH: 13 - 14

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : May cause respiratory irritation.

Symptoms/injuries after skin contact : Caustic burns/corrosion of the skin.

Symptoms/injuries after eye contact : Causes serious eye damage. Corrosion of the eye tissue. Permanent eye damage.

Symptoms/injuries after ingestion : Harmful if swallowed. Burns to the gastric/intestinal mucosa. Gastrointestinal complaints.

SECTION 12: Ecological information

12.1. Toxicity

potassium hydroxide, 45%=<conc<50%, aqueous solutions (1310-58-3)	
LC50 fish 1	28.6 mg/l (24 h; Pisces; Pure substance)
LC50 other aquatic organisms 1	100 - 1000 mg/l (96 h)
LC50 fish 2	80 mg/l (96 h; Gambusia affinis; Pure substance)
Threshold limit other aquatic organisms 1	100 - 1000,96 h

tetrapotassium pyrophosphate, anhydrous (7320-34-5)	
LC50 fish 1	> 750 mg/l (48 h; Leuciscus idus)

12.2. Persistence and degradability

potassium hydroxide, 45%=<conc<50%, aqueous solutions (1310-58-3)	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the components available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

tetrapotassium pyrophosphate, anhydrous (7320-34-5)	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

12.3. Bioaccumulative potential

potassium hydroxide, 45%=<conc<50%, aqueous solutions (1310-58-3)	
Bioaccumulative potential	Not bioaccumulative.

tetrapotassium pyrophosphate, anhydrous (7320-34-5)	
Bioaccumulative potential	Bioaccumulation: not applicable.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport document description : UN3266 Corrosive liquid, basic, inorganic, n.o.s. (Potassium Hydroxide), 8, II

UN-No.(DOT) : UN3266

Proper Shipping Name (DOT) : Corrosive liquid, basic, inorganic, n.o.s.

Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Hazard labels (DOT) : 8 - Corrosive

Packing group (DOT) : II - Medium Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 202

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102) : B2,IB2,T11,TP2,TP27

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 1 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 30 L

DOT Vessel Stowage Location : B

DOT Vessel Stowage Other : 40 - Stow ‘‘clear of living quarters’’,52 - Stow ‘‘separated from’’ acids

Additional information

Other information : This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D utilizing the exception found at 49 CFR 173.154.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Diethylene Glycol Monoethyl Ether	(CAS No) 111-90-0	3-7

potassium hydroxide, 45%=<conc<50%, aqueous solutions (1310-58-3)	
Not listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H290	May be corrosive to metals
H301	Toxic if swallowed
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 0 - Materials that will not burn.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.