

# Rubber & Tire Dressing

## Safety Data Sheet



### SECTION 1: Product and company identification

Product name : Rubber & Tire Dressing  
Use of the substance/mixture : Protectant  
Product code : 112501  
Company : Share Corporation  
P.O. Box 245013  
Milwaukee, WI 53224 - USA  
T (414) 355-4000  
Emergency number : Chemtrec: (800) 424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flam. Liq. 3 H226  
Asp. Tox. 1 H304  
Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02

GHS08

Signal word (GHS-US) : Danger  
Hazard statements (GHS-US) : Flammable liquid and vapor  
May be fatal if swallowed and enters airways  
Precautionary statements (GHS-US) : Keep away from heat, open flames, sparks. - No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof lighting, electrical equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Wear eye protection, protective clothing, protective gloves  
If swallowed: Immediately call a POISON CENTER, a doctor  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
Do NOT induce vomiting  
In case of fire: Use carbon dioxide (CO2), dry extinguishing powder, foam to extinguish  
Store in a well-ventilated place. Keep cool  
Store locked up  
Dispose of contents/container to comply with local/regional/national/international regulations

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substance

Not applicable

Full text of H-phrases: see section 16

#### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	(CAS No) 64742-47-8	75-90	Flam. Liq. 4, H227 Asp. Tox. 1, H304

A specific chemical identity and/or percentage of composition has been withheld as a trade secret. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.

# Rubber & Tire Dressing

## Safety Data Sheet



First-aid measures after skin contact	: Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention if you feel unwell.
First-aid measures after ingestion	: Rinse mouth with water. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: None under normal use.
Symptoms/injuries after skin contact	: Contact during a long period may cause light irritation.
Symptoms/injuries after eye contact	: Direct contact with the eyes is likely irritating.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide. Dry powder. Foam.
Unsuitable extinguishing media	: Water.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapor.
Reactivity	: Upon combustion: CO and CO <sub>2</sub> are formed.

### 5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Take account of environmentally hazardous firefighting water.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: No flames, No sparks. Eliminate all sources of ignition.
------------------	------------------------------------------------------------

#### 6.1.1. For non-emergency personnel

Protective equipment	: Protective goggles. Gloves. Protective clothing.
Emergency procedures	: Evacuate unnecessary personnel. Avoid contact with skin, eyes and clothing. Ventilate spillage area.

#### 6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Stop leak if safe to do so. Stop release. Ventilate area.

### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

### 6.3. Methods and material for containment and cleaning up

For containment	: Contain released substance, pump into suitable containers.
Methods for cleaning up	: This material and its container must be disposed of in a safe way, and as per local legislation.

### 6.4. Reference to other sections

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Comply with the legal requirements. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Do not get in eyes, on skin, or on clothing. Obtain special instructions before use.
Hygiene measures	: Wash thoroughly after handling. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Comply with applicable regulations.
Storage conditions	: Keep container closed when not in use.
Incompatible products	: Oxidizing agent.
Incompatible materials	: Heat sources. Sources of ignition.
Storage area	: Meet the legal requirements. Store in a dry area. Keep container in a well-ventilated place. Store in a cool area.
Special rules on packaging	: meet the legal requirements. Keep only in original container.

# Rubber & Tire Dressing

## Safety Data Sheet



### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

No additional information available

#### 8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Personal protective equipment : Use appropriate personal protective equipment when risk assessment indicates this is necessary.  
Gloves. Safety glasses. Protective clothing. Protective goggles.



### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: green.
Odor	: solvent odor
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 112 °F Closed Cup
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 0.8 g/ml
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: < 20 cSt
Viscosity, dynamic	: No data available
VOC content	: > 75 %

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Upon combustion: CO and CO<sub>2</sub> are formed.

#### 10.2. Chemical stability

No additional information available

#### 10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

#### 10.4. Conditions to avoid

No additional information available

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Rubber & Tire Dressing

## Safety Data Sheet



### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

##### hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)

LD50 dermal rabbit	> 5000 mg/kg body weight (Rabbit; Literature)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: None under normal use.
Symptoms/injuries after skin contact	: Contact during a long period may cause light irritation.
Symptoms/injuries after eye contact	: Direct contact with the eyes is likely irritating.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.
Likely routes of exposure	: Skin and eyes contact

### SECTION 12: Ecological information

#### 12.1. Toxicity

##### hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)

LC50 fish 1	<= mg/l >0.1 - <=1,NOEC
EC50 Daphnia 1	<= mg/l >1 - <=10,NOEC
LC50 fish 2	> 100 mg/l (LC50)
EC50 Daphnia 2	> 100 mg/l (EC50)
Threshold limit algae 1	> 100 mg/l (EC50)

#### 12.2. Persistence and degradability

##### hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)

Persistence and degradability	Readily biodegradable in water. Adsorbs into the soil.
-------------------------------	--------------------------------------------------------

#### 12.3. Bioaccumulative potential

##### hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)

Log Pow	6 - 8.2
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

##### Additional information

Other information : This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D utilizing the exception found at 49 CFR 173.150.

#### ADR

No additional information available

#### Transport by sea

No additional information available

#### Air transport

No additional information available

### SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

# Rubber & Tire Dressing

## Safety Data Sheet



Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

cumene	CAS No 98-82-8	0.1 - 1.0%
--------	----------------	------------

cumene (98-82-8)	
Listed on SARA Section 313 (Specific toxic chemical listings)	
CERCLA RQ	5000 lb

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

### SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.


Full text of H-phrases:

H226	Flammable liquid and vapor
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.*