

DEGREASER is a fast acting blend of emulsifiable solvents. It is designed for easy removal of thick grease, oil, sludge, tar, dirt and grime deposits.

DEGREASER may be safely used on metal, concrete, stone, tile, wood, glass, painted surfaces and some types of plastic. Do not use on asphalt floor tile. Test painted surfaces, plastics and other floor types by spraying on an inconspicuous area prior to using.

DEGREASER saves time, effort and money by cleaning barbeque grills, machinery, tools, engines, garage floors and a wide variety of other surfaces.

DIRECTIONS FOR USE

- Hold can upright with nozzle 10 to 12 inches from the surface to be cleaned.
- Spray to thoroughly cover deposits, and allow the degraser to penetrate for up to 10 minutes.
- Flush away loosened deposits with water types. For thick deposits, brush or serape to help speed removal then beliest application to clean surface completely.

DANGER: EXTREMELY FLAMMABLE

CONTENTS UNDER PRESSURE, Leep away from heat, spark or open name. Do not expose to remperature above 120°F. Do not puncture of incinerate can, Harmolf or fatal if swallowed. Avoid contact with eyes, skin or mucous membranes. Vapor is harmful. Avoid breathing apors or spray mist. Use only in well ventilated area. If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. If sprayed in eyes, flush eyes and under eyelids with plenty of water and obtain medical attention. For skin contact, wash with soap and water.

KEEP OUT OF REACH OF CHILDREN

8196 • 012307

Health 2
Flammability 4
Reactivity 0

HMIS NEPA
Severe 4 Extreme
Serious 3 High
Moderate 2 Moderate
Slight 1 Slight
Minimal 0 Insignificant

This product contains	CAS No.
Kerosene	9008-20-6
Mineral Spirits	
2-Butoxyethanol	111-76-2
Butane(Propellant)	106-97-8
Propane(Propellant)	74-98-6

Share Corp. • P.O. Box 245015 • Milwaukee, WI 53224 • (800) 776-7192 • www.aharecorp.com