Safety Data Sheet



SECTION 1: Product and company identification

Product name : Heavy Duty Multi-Purpose Grease Aerosol

Use of the substance/mixture : Aerosol

Grease

Product code : 885201

Company : Share Corporation P.O. Box 245013

Milwaukee, WI 53224 - USA

T (414) 355-4000

Emergency number : Chemtrec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Aerosol 1 H222 Repr. 2 H361 Asp. Tox. 1 H304 Aquatic Acute 2 H401 Aquatic Chronic 2 H411

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)







GHS09

IS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Extremely flammable aerosol

May be fatal if swallowed and enters airways Suspected of damaging fertility or the unborn child

Toxic to aquatic life

Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) : Obtain special instructions before use

Do not handle until all safety precautions have been read and understood Keep away from heat, sparks, open flames, hot surfaces. - No smoking

Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

Avoid release to the environment

Wear protective gloves, protective clothing, eye protection, face protection

If swallowed: Immediately call a POISON CENTER, a doctor if exposed or concerned: Get medical advice/attention

Do NOT induce vomiting Collect spillage

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Dispose of contents/container to comply with local/regional/national/international regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	(CAS No) 64742-47-8	20 - 40	Flam. Liq. 4, H227 Asp. Tox. 1, H304
propane	(CAS No) 74-98-6	10 - 20	Flam. Gas 1, H220 Compressed gas, H280

Date of issue: 1/8/2016 Revision date: 02/26/2015 Version: 1.0 P GHS SDS Page 1 of 7

Safety Data Sheet



Name	Product identifier	%	Classification (GHS-US)
heptane, n-heptane	(CAS No) 142-82-5	2.5 - 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Heptane, branched cyclic and linear	(CAS No) 426260-76-6	2.5 - 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Toluene	(CAS No) 108-88-3	0.1 - 1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Ensure that

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect

themselves.

First-aid measures after inhalation : Move the affected person away from the contaminated area and into the fresh air. Respiratory

problems: consult a doctor/medical service.

First-aid measures after skin contact : Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Direct contact with the eyes is likely irritating. Aspiration may cause pulmonary edema and

pneumonitis.

Symptoms/injuries after inhalation : No effects known. Symptoms/injuries after skin contact : No effects known.

Symptoms/injuries after eye contact : Direct contact with the eyes is likely irritating.

Symptoms/injuries after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry powder. Alcohol-resistant foam. Dry chemical powder. Carbon dioxide.

Unsuitable extinguishing media : Solid water jet ineffective as extinguishing medium.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Contents under pressure. Pressurized container: may burst if heated.

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Advice for firefighters

Firefighting instructions : Move containers away from the fire area if this can be done without risk. Use water spray or fog for cooling exposed containers. For massive fire in cargo area, use unmanned hose holder or monitor.

cooling exposed containers. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Stay upwind/keep distance from source. Gas is denser than air.

May accumulate in low areas e.g. close to the ground. Eliminate every possible source of ignition.

6.1.1. For non-emergency personnel

Protective equipment : Do not enter without an appropriate protective equipment. DO NOT touch spilled material.

Emergency procedures : Ventilate the area thoroughly, especially low lying areas (basements, work pits etc.). Advice local

authorities if considered necessary.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

Date of issue: 1/8/2016 Revision date: 02/26/2015 Version: 1.0 P GHS SDS Page 2 of 7

Safety Data Sheet



6.2. Environmental precautions

Prevent runoff from entering drains, sewers or waterways. Avoid discharge to the environment. Advice local authorities if considered necessary. Stop leak if safe to do so.

6.3. Methods and material for containment and cleaning up

For containment

: Eliminate every possible source of ignition. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if safe to do so. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent the product from entering drains or confined areas. For further information refer to section 8: Exposure-controls/personal protection"".

Methods for cleaning up

Take up liquid spill into absorbent material. Following product recovery, flush area with water.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Pressurized container: Do not pierce or burn, even after use.

Precautions for safe handling

: Do not use if spray button is missing or defective. Do not spray on a naked flame or any incandescent material. Do not smoke while handling product. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. . Handling this product may result in electrostatic accumulation. Use proper grounding procedures. Do not re-use empty containers. Avoid breathing dust, fume, gas, mist, spray, vapors. Use only outdoors or in a wellventilated area. Use personal protective equipment as required. Do not discharge the waste into the

: Use good personal hygiene practices. Hygiene measures

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

Pressurized container. Do not puncture, incinerate or crush. Take precautionary measures against

Storage conditions

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Refrigerate. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Incompatible materials

Heat sources. Sources of ignition.

Heat-ignition

KEEP SUBSTANCE AWAY FROM: heat sources. ignition sources.

Storage area Aerosol 2.

SECTION 8: Exposure controls/personal protection

Control parameters

propane (74-98-6)			
ACGIH	ACGIH TWA (ppm)	1000 ppm	
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm	
toluene (108-88-3)			
ACGIH	ACGIH TWA (ppm)	20 ppm	
ACGIH	Remark (ACGIH)	Visual impair; female repro;	
heptane, n-heptane (142-82-5)			
ACGIH	ACGIH TWA (ppm)	400 ppm	

8.2. Exposure controls

Appropriate engineering controls

Ensure good ventilation of the work station.

Personal protective equipment

Gloves. Protective clothing. Safety glasses. Use appropriate personal protective equipment when risk assessment indicates this is necessary.



Hand protection

Protective gloves

Eye protection Skin and body protection Chemical goggles or safety glasses. Wear suitable protective clothing.

Respiratory protection

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-

supplied respirator.

Thermal hazard protection

Use appropriate personal protective equipment when risk assessment indicates this is necessary.

Consumer exposure controls

When using do not smoke. Use good personal hygiene practices. Take off contaminated clothing and wash before reuse. Wash hands and other exposed areas with mild soap and water before eat,

drink or smoke and when leaving work.

Date of issue: 1/8/2016 Revision date: 02/26/2015 Version: 1.0 P GHS SDS Page 3 of 7

Safety Data Sheet



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties
Physical state : Liquid

Appearance : Aerosol. Liquid.

Odor : No data available on odor

Odor threshold : No data available pH : No data available Melting point : No data available Freezing point : No data available Boiling point : 209.3 °F Estimated

Flash point : -156 °F Propellant estimated

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available **Explosion limits** : No data available Explosive properties : No data available Oxidizing properties No data available : No data available Vapor pressure : No data available Relative density Relative vapor density at 20 °C : No data available Specific gravity / density : 0.511 g/ml estimated Solubility : Not determined. Log Pow : No data available Log Kow : No data available Auto-ignition temperature : No data available : No data available Decomposition temperature Viscosity No data available Viscosity, kinematic No data available Viscosity, dynamic No data available VOC content : Not Determined

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

10.4. Conditions to avoid

Aerosol containers are unstable at temperatures above 49°C. Avoid temperatures exceeding the flash point.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)		
LD50 dermal rabbit		> 5000 mg/kg body weight (Rabbit; Literature)
Skin corrosion/irritation	:	Not classified.

Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

toluene (108-88-3)	
IARC group	3 - Not Classifiable

 Date of issue: 1/8/2016
 Revision date: 02/26/2015
 Version: 1.0
 P GHS SDS
 Page 4 of 7

Safety Data Sheet

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Specific target organ toxicity (single exposure) : Not classified.

Specific target organ toxicity (repeated : Not classified.

exposure)

Aspiration hazard : May be fatal if swallowed and enters airways.

Potential Adverse human health effects and

symptoms

: Dizziness. Direct contact with the eyes is likely irritating.

. Bizzinoco. Biroci contact with the cycle to intery inflatin

Symptoms/injuries after inhalation : No effects known. Symptoms/injuries after skin contact : No effects known.

Symptoms/injuries after eye contact : Direct contact with the eyes is likely irritating.

Symptoms/injuries after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal

use.

Likely routes of exposure : Skin and eyes contact.

SECTION 12: Ecological information

12.1. Toxicity

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)	
LC50 fish 1 > 100 mg/l (Pisces)	
EC50 Daphnia 1	> 100 mg/l (Invertebrata)
Threshold limit algae 1	> 100 mg/l (Algae)

12.2. Persistence and degradability

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)	
Persistence and degradability	Readily biodegradable in water. Adsorbs into the soil.

12.3. Bioaccumulative potential

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)	
Log Pow	6 - 8.2
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Collect and reclaim or dispose in sealed containers at licensed waste disposal site. . Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container to comply with

local/regional/national/international regulations.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Additional information : Empty containers should be taken for recycle, recovery or waste in accordance with local

regulation. Handle empty containers with care because residual vapors are flammable. Handle

unclean empty containers as full ones. Do not re-use empty containers.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950
Proper Shipping Name (DOT) : Aerosols

flammable, (each not exceeding 1 L capacity)

Transport hazard class(es) (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



Dangerous for the environment : Yes

 Date of issue: 1/8/2016
 Revision date: 02/26/2015
 Version: 1.0
 P GHS SDS
 Page 5 of 7

Safety Data Sheet

Marine pollutant : Yes



: 75 kg

: 150 kg

DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None DOT Special Provisions (49 CFR 172.102) : N82 DOT Packaging Exceptions (49 CFR : 306

DOT Quantity Limitations Passenger

aircraft/rail (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft

only (49 CFR 175.75)

DOT Vessel Stowage Location : A

DOT Vessel Stowage Other : 25 - Shade from radiant heat,87 - Stow "separated from" Class 1 (explosives) except Division

14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Additional information

Other information : This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D

utilizing the exception found at 49 CFR 173.306.

ADR

No additional information available

Transport by sea

UN-No. (IMDG) : UN1950
Proper Shipping Name (IMDG) : Aerosols

Class (IMDG) : 2.1 - Flammable gases

Air transport

toluene

List of Lists)

UN-No.(IATA) : UN1950
Proper Shipping Name (IATA) : Aerosols

Class (IATA) : 2.1 - Gases : Flammable

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

propane (74-98-6)	
Not listed on SARA Section 313 (Specific toxic ch	nemical listings)
toluene (108-88-3)	
Listed on SARA Section 313 (Specific toxic chem	ical listings)
RQ (Reportable quantity, section 304 of EPA's	1000 lb

CAS No 108-88-3

0.1 - 1

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2

Date of issue: 1/8/2016 Revision date: 02/26/2015 Version: 1.0 P GHS SDS Page 6 of 7

Safety Data Sheet




Asp. Tox. 1	Aspiration hazard Category 1
Compressed gas	Gases under pressure Compressed gas
Flam. Aerosol 1	Flammable aerosol Category 1
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 4	Flammable liquids Category 4
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H227	Combustible liquid
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated
	exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in

air and will burn readily.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.

 Date of issue: 1/8/2016
 Revision date: 02/26/2015
 Version: 1.0
 P GHS SDS
 Page 7 of 7