DECENTRALIZED SLIP-39 RECOVERY SHEET

3 OF 5 | 20 WORDS PER SHARE | 4 LETTER PREFIX BURN AFTER USE

RECOVERY AND VERIFICATION PROCEDURE

1. Use each escrow's pre-verified contact details.
2. Ask for ciphertext groups 01-02 before giving personal information.
3. Compare the received groups with the expected ciphertext stored below.
4. Complete agreed ID checks; retain the notice of the 7-day release time.
5. Receive all 20 groups; enter them in C; verify the stored SHA-256.
6. Decrypt locally; enter each four-letter word prefix into a hardware wallet to recover the share.
7. Validate each complete mnemonic; obtain three distinct valid shares.
8. Restore on a compatible offline device; verify the wallet, then follow the wipe plan.

At setup: complete contacts, expected ciphertext, K and the SHA-256 digest. During recovery: fill C and decrypt locally. Keep K and cleartext private.

DECRYPT LOCALLY: P = (C - K) mod 26 K = pad / C = ciphertext / P = plaintext

LETTER / NUMBER CONVERSION

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25

SHARE 01

Authentication / notice (UTC): _____ Release due (UTC): _____

Company: _____
Jurisdiction: _____
Account / reference: _____
Phone: _____
Email / website: _____

EXPECTED FIRST TWO CIPHERTEXT GROUPS

01 [ ][ ][ ][ ] 02 [ ][ ][ ][ ]

Expected SHA-256: 64 hex digits, top row first

20 groups x 4 letters = 80 letters

	01	02	03	04	05	06	07	08	09	10
K										
C										

	11	12	13	14	15	16	17	18	19	20
K										
C										

SHARE 02

Authentication / notice (UTC): _____ Release due (UTC): _____

Company: _____
Jurisdiction: _____
Account / reference: _____
Phone: _____
Email / website: _____

EXPECTED FIRST TWO CIPHERTEXT GROUPS

01 [ ][ ][ ][ ] 02 [ ][ ][ ][ ]

Expected SHA-256: 64 hex digits, top row first

20 groups x 4 letters = 80 letters

	01	02	03	04	05	06	07	08	09	10
K										
C										

	11	12	13	14	15	16	17	18	19	20
K										
C										

SHARE 03

Authentication / notice (UTC): _____ Release due (UTC): _____

Company: _____
Jurisdiction: _____
Account / reference: _____
Phone: _____
Email / website: _____

EXPECTED FIRST TWO CIPHERTEXT GROUPS

01 [ ][ ][ ][ ] 02 [ ][ ][ ][ ]

Expected SHA-256: 64 hex digits, top row first

20 groups x 4 letters = 80 letters

	01	02	03	04	05	06	07	08	09	10
K										
C										

	11	12	13	14	15	16	17	18	19	20
K										
C										

SHARE 04

Authentication / notice (UTC): _____ Release due (UTC): _____

Company: _____
Jurisdiction: _____
Account / reference: _____
Phone: _____
Email / website: _____

EXPECTED FIRST TWO CIPHERTEXT GROUPS

01 [ ][ ][ ][ ] 02 [ ][ ][ ][ ]

Expected SHA-256: 64 hex digits, top row first

20 groups x 4 letters = 80 letters

	01	02	03	04	05	06	07	08	09	10
K										
C										

	11	12	13	14	15	16	17	18	19	20
K										
C										

SHARE 05

Authentication / notice (UTC): _____ Release due (UTC): _____

Company: _____
Jurisdiction: _____
Account / reference: _____
Phone: _____
Email / website: _____

EXPECTED FIRST TWO CIPHERTEXT GROUPS

01 [ ][ ][ ][ ] 02 [ ][ ][ ][ ]

Expected SHA-256: 64 hex digits, top row first

20 groups x 4 letters = 80 letters

	01	02	03	04	05	06	07	08	09	10
K										
C										

	11	12	13	14	15	16	17	18	19	20
K										
C										

ACCOUNTS / WALLET PASSPHRASES

One record per wallet. Preserve exact case and spaces; explicitly mark an empty passphrase. A public address helps verify the recovered wallet.

NO.	ACCOUNT / WALLET LABEL	PASSPHRASE - EXACT TEXT	KNOWN PUBLIC ADDRESS / WALLET CHECK
01		☐ Empty	
02		☐ Empty	
03		☐ Empty	

Format: 20-word SLIP-39 shares (128-bit master secret); each dictionary word has a unique four-letter prefix. This form does not fit 33-word shares.
Pad: 80 independently uniform A-Z letters per share. Use a different pad for every share; never reuse it for another plaintext. Decrypt locally only.
SHA-256: hash exactly 80 uppercase ASCII ciphertext letters in order, without spaces, line breaks or group numbers.
Write the full SHA-256 digest as 64 uppercase hex digits (0-9, A-F), including leading zeroes. Compare it with the digest recorded at setup.
The first two words identify the backup set, not its group. Group information begins in word 3. A static ciphertext prefix is replayable, not proof of escrow identity.
Completed C plus K reveals a share. Protect the sheet and handle recovered plaintext under your recovery plan; validate the complete SLIP-39 checksum.

References: github.com/satoshilabs/slips/blob/master/slip-0039.md | docs.python.org/3/library/hashlib.html