abc= anti bounce counter
_ac_= acceleration
acc= air conditioning compressor
accin= aircon compressor request
accout= aircon compressor deactivation
acin= aircon activated
_ad_= criteria for adaption
add= lambda adaption additive
adh= adhesion detection
afl= air/fuel-ratio lean
afr= air/fuel-ratio rich
_aj_= anti-jerk
amp= ambient pressure
amt= automatic transmission
_as_= application system
ast= after start
_at_= automatic transmission
_av_= actual-value

bat= battery ampere
bls= brake light switch

cast= cold, after start
cdn= condition
_ch_= catalyst heating-condition
_cha_bat_= battery charging current
conf= configuration
cop= catalyst overheating protection
cor= correction
cps= evap system
cppwm= pwm control of evap solenoid
_cr_= ?clutch released?
crlc= correlation constant
cru= cruise control
_cs_= clutch switch
cst= cold start
ctl= control/intervention
ctr= counter
cyctr= cycle-counter

deacc= deacceleration
dec= decrease
dhp= dashpot
diag= diagnose
dif= difference/differential
dly= delay
dmtl= diagnose module tank leakage
dri= check for AT at Drive or Reverse
_dy_= dynamic
dyw= window for limited dynamic

ecf= engine cooling fan
ect= engine coolant thermostat
_ef_= e xhaust flap
egr= exhaust gas recirculation
eoi= end of injection

_er_=	engine roughness calculation

fac=	lambda adaption multiplicative
fco=	fuel consumption
fil=	filtered/normalized
_fl_=	full-load
frq=	frequency
ftl=	fuel tank level
fuc=	checking conditions of filler cap (removal)

gear=	gear
grd=	gradient (fade out duration)
_gp_=	gear protection
_gs_=	gear shift

_h_=	higher as
hys=	hysteresis

icl*=	instrument cluster
iga=	°ignition advance
_iga_optm_=	optimal ignition map
igab=	°basic ignition map
igcfb=	°ignition current feedback
igk=	ignition key
inc=	increase
inf=	intercept function
_is_=	idle-speed/partial load
isapwm=	idle speed actuator
ivvtpwm=	individual variable valve timing

knk=	knock (-control)
_knk_1_=	knock, intensity 1
_knk_2_=	knock, intensity 2

_l_=	lower as
lam=	lambdaintegrator
LDP_=	axis descriptor
lgrd=	gradient limitation
lih=	limp home
lim=	limit
_ls_=	lambdasensor
_ls*_up_=	before-cat lambdasensor
_ls*_down_=	post-cat lambdasensor
lsh=	lambdasensor heater
lshpwm=	pwm controlling of lambdasensor heater

maf=	maf sensor
max=	max limiter
mdl=	model
mis=	misfire
_mis_a_=	misfire carb a
_mis_b_=	misfire carb b
mpl=	multiple

-msw-= multifunction steering wheel
_mt_= manual transmission
mtc= motorized throttle control
mtcpwm= pwm control of throttle body
_mv_= mean value
mmv= moving mean value

_n_= engine speed
_nl_= knock circuit noise level

_pl_= part-load
plaus= plausibility
puc= overrun fuel cut
°pste= Power-Steering
pvs= acceleration pedal°

_r_= resistance, electrical
ref= reference
refu= refueling
rep= repeated
rest= restart-condition
ris= restart fuel-feed at idlespeed
rly= relay
rpl= smooth acceleration (restart fuel-feed at partload)

saf= secondary airflow
sap= secondary air pump
sav= secondary air valve
soi= start of injection
_sp_= set-point
ssc= single cylinder fuel-cut
ssg= SMG gearbox
sub= substitute
sum= switch after x jumps
supp= supress
swi= switch

tam= temperature ambient
_tco_1= coolant temperature, cold engine
_tco_2= coolant temperature, warm engine
_td_= ignition-coil dwell time
teg= temperature exhaust gas
thd= threshold
tia= temperature intake
tib= injection time, basic
tipr= pre injection time
tmag= substitute for toil
toil= temperature oil
tout= time-out
tps= throttle position sensor
_tq_= torque
tqd= torque, drag
tqfr= torque, friction
tqi= torque, indexed/indicated
tqr= torque reduction due to intervention

tra=	transient correction [strong acceleration (instationary)

_vb_=	voltage battery
vim=	Disa
_vo_=	valve overlap
vol=	intake manifold volume
_vs_=	vehicle speed
vls=	voltage lambdasensor

_wf_=	weighing factor
_wu_=	warm-up