

O'REILLY®

Third
Edition

Hands-On Machine Learning with Scikit-Learn, Keras & TensorFlow

Concepts, Tools, and Techniques
to Build Intelligent Systems

powered by



Aurélien Géron

Hands-On Machine Learning with Scikit-Learn, Keras, and TensorFlow

THIRD EDITION

Concepts, Tools, and Techniques to Build Intelligent
Systems

Aurélien Géron

O'REILLY®

Beijing • Boston • Farnham • Sebastopol • Tokyo

**Hands-On Machine Learning with Scikit-Learn, Keras, and
TensorFlow**

by Aurélien Géron

Copyright © 2023 Aurélien Géron. All rights
reserved. Printed in the United States of America.

Published by O'Reilly Media, Inc., 1005 Gravenstein Highway North,
Sebastopol, CA 95472.

O'Reilly books may be purchased for educational, business, or sales
promotional use. Online editions are also available for most titles
(<https://oreilly.com>). For more information, contact our
corporate/institutional sales department: 800-998-9938 or
corporate@oreilly.com.

Acquisitions Editor: Nicole Butterfield

Development Editors: Nicole Taché and
Michele Cronin

Production Editor: Beth Kelly

Copyeditor: Kim Cofer

Proofreader: Rachel Head

Indexer: Potomac Indexing, LLC

Interior Designer: David Futato

Cover Designer: Karen Montgomery

Illustrator: Kate Dullea

March 2017: First Edition

September 2019: Second Edition

October 2022: Third Edition

Revision History for the Third Edition

2022-10-03: First Release

See <https://oreilly.com/catalog/errata.csp?isbn=9781492032649> for release details.

The O'Reilly logo is a registered trademark of O'Reilly Media, Inc. *Hands On Machine Learning with Scikit-Learn, Keras, and TensorFlow*, the cover image, and related trade dress are trademarks of O'Reilly Media, Inc.

The views expressed in this work are those of the author, and do not represent the publisher's views. While the publisher and the author have used good faith efforts to ensure that the information and instructions contained in this work are accurate, the publisher and the author disclaim all responsibility for errors or omissions, including without limitation responsibility for damages resulting from the use of or reliance on this work. Use of the information and instructions contained in this work is at your own risk. If any code samples or other technology this work contains or describes is subject to open source licenses or the intellectual property rights of others, it is your responsibility to ensure that your use thereof complies with such licenses and/or rights.

978-1-098-12597-4

[LSI]

Preface

The Machine Learning Tsunami

1

In 2006, Geoffrey Hinton et al. published a paper showing how to train a deep neural network capable of recognizing handwritten digits with state of-the-art precision (>98%). They branded this technique “deep learning”. A

deep neural network is a (very) simplified model of our cerebral cortex, composed of a stack of layers of artificial neurons. Training a deep neural 2 net was widely considered impossible at the time, and most researchers had abandoned the idea in the late 1990s. This paper revived the interest of the scientific community, and before long many new papers demonstrated that deep learning was not only possible, but capable of mind-blowing achievements that no other machine learning (ML) technique could hope to match (with the help of tremendous computing power and great amounts of data). This enthusiasm soon extended to many other areas of machine learning.

A decade later, machine learning had conquered the industry, and today it is at the heart of much of the magic in high-tech products, ranking your web search results, powering your smartphone’s speech recognition, recommending videos, and perhaps even driving your car.

Machine Learning in Your Projects

So, naturally you are excited about machine learning and would love to join the party!

Perhaps you would like to give your homemade robot a brain of its own? Make it recognize faces? Or learn to walk around?

Or maybe your company has tons of data (user logs, financial data, production data, machine sensor data, hotline stats, HR reports, etc.), and more than likely you could unearth some hidden gems if you just knew where to look. With machine learning, you could accomplish the following and much more:

- Segment customers and find the best marketing strategy for each group.

- Recommend products for each client based on what similar clients bought.

- Detect which transactions are likely to be fraudulent.

Forecast next year's revenue.

Whatever the reason, you have decided to learn machine learning and implement it in your projects. Great idea!

Objective and Approach

This book assumes that you know close to nothing about machine learning. Its goal is to give you the concepts, tools, and intuition you need to implement programs capable of *learning from data*.

We will cover a large number of techniques, from the simplest and most commonly used (such as linear regression) to some of the deep learning techniques that regularly win competitions. For this, we will be using production-ready Python frameworks:

Scikit-Learn is very easy to use, yet it implements many machine learning algorithms efficiently, so it makes for a great entry point to learning machine learning. It was created by David Cournapeau in 2007, and is now led by a team of researchers at the French Institute for Research in Computer Science and Automation (Inria).

TensorFlow is a more complex library for distributed numerical computation. It makes it possible to train and run very large neural networks efficiently by distributing the computations across potentially hundreds of multi-GPU (graphics processing unit) servers. TensorFlow (TF) was created at Google and supports many of its large-scale machine learning applications. It was open sourced in November 2015, and version 2.0 was released in September 2019.

Keras is a high-level deep learning API that makes it very simple to train and run neural networks. Keras comes bundled with TensorFlow, and it relies on TensorFlow for all the intensive computations.

The book favors a hands-on approach, growing an intuitive understanding of machine learning through concrete working examples and just a little bit of theory.

TIP

While you can read this book without picking up your laptop, I highly recommend you experiment with the code examples.

Code Examples

All the code examples in this book are open source and available online at <https://github.com/ageron/handson-ml3>, as Jupyter notebooks. These are interactive documents containing text, images, and executable code snippets (Python in our case). The easiest and quickest way to get started is to run these notebooks using Google Colab: this is a free service that allows you to run any Jupyter notebook directly online, without having to install anything on your machine. All you need is a web browser and a Google account.

NOTE

In this book, I will assume that you are using Google Colab, but I have also tested the notebooks on other online platforms such as Kaggle and Binder, so you can use those if you prefer. Alternatively, you can install the required libraries and tools (or the Docker image for this book) and run the notebooks directly on your own machine. See the instructions at <https://homl.info/install>.

This book is here to help you get your job done. If you wish to use additional content beyond the code examples, and that use falls outside the scope of fair use guidelines, (such as selling or distributing content from O'Reilly books, or incorporating a significant amount of material from this book into your product's documentation), please reach out to us for permission, at permissions@oreilly.com.

We appreciate, but do not require, attribution. An attribution usually includes the title, author, publisher, and ISBN. For example: “*Hands-On Machine Learning with Scikit-Learn, Keras, and TensorFlow* by Aurélien Géron. Copyright 2023 Aurélien Géron, 978-1-098-12597-4.”

Prerequisites

This book assumes that you have some Python programming experience. If you don't know Python yet, <https://learnpython.org> is a great place to start. The official tutorial on [Python.org](https://python.org) is also quite good.

This book also assumes that you are familiar with Python's main scientific libraries—in particular, [NumPy](#), [Pandas](#), and [Matplotlib](#). If you have never used these libraries, don't worry; they're easy to learn, and I've created a tutorial for each of them. You can access them online at <https://homl.info/tutorials>.

Moreover, if you want to fully understand how the machine learning

algorithms work (not just how to use them), then you should have at least a basic understanding of a few math concepts, especially linear algebra. Specifically, you should know what vectors and matrices are, and how to perform some simple operations like adding vectors, or transposing and multiplying matrices. If you need a quick introduction to linear algebra (it's really not rocket science!), I provide a tutorial at <https://homl.info/tutorials>. You will also find a tutorial on differential calculus, which may be helpful to understand how neural networks are trained, but it's not entirely essential to grasp the important concepts. This book also uses other mathematical concepts occasionally, such as exponentials and logarithms, a bit of probability theory, and some basic statistics concepts, but nothing too advanced. If you need help on any of these, please check out <https://khanacademy.org>, which offers many excellent and free math courses online.

Roadmap

This book is organized in two parts. **Part I, “The Fundamentals of Machine Learning”**, covers the following topics:

- What machine learning is, what problems it tries to solve, and the main categories and fundamental concepts of its systems

- The steps in a typical machine learning project

- Learning by fitting a model to data

- Optimizing a cost function

- Handling, cleaning, and preparing data

- Selecting and engineering features

- Selecting a model and tuning hyperparameters using cross-validation

- The challenges of machine learning, in particular underfitting and overfitting (the bias/variance trade-off)

- The most common learning algorithms: linear and polynomial regression, logistic regression, k -nearest neighbors, support vector machines, decision trees, random forests, and ensemble methods

- Reducing the dimensionality of the training data to fight the “curse of dimensionality”

- Other unsupervised learning techniques, including clustering, density

estimation, and anomaly detection

Part II, “Neural Networks and Deep Learning”, covers the following topics:

What neural nets are and what they’re good for

Building and training neural nets using TensorFlow and Keras

The most important neural net architectures: feedforward neural nets for tabular data, convolutional nets for computer vision, recurrent nets and long short-term memory (LSTM) nets for sequence processing, encoder–decoders and transformers for natural language processing (and more!), autoencoders, generative adversarial networks (GANs), and diffusion models for generative learning

Techniques for training deep neural nets

How to build an agent (e.g., a bot in a game) that can learn good strategies through trial and error, using reinforcement learning

Loading and preprocessing large amounts of data efficiently

Training and deploying TensorFlow models at scale

The first part is based mostly on Scikit-Learn, while the second part uses TensorFlow and Keras.

CAUTION

Don’t jump into deep waters too hastily: while deep learning is no doubt one of the most exciting areas in machine learning, you should master the fundamentals first. Moreover, most problems can be solved quite well using simpler techniques such as random forests and ensemble methods (discussed in **Part I**). deep learning is best suited for complex problems such as image recognition, speech recognition, or natural language processing, and it requires a lot of data, computing power, and patience (unless you can leverage a pretrained neural network, as you will see).

Changes Between the First and the Second Edition

If you have already read the first edition, here are the main changes between the first and the second edition:

All the code was migrated from TensorFlow 1.x to TensorFlow 2.x, and I replaced most of the low-level TensorFlow code (graphs, sessions, feature columns, estimators, and so on) with much simpler

Keras code.

The second edition introduced the Data API for loading and preprocessing large datasets, the distribution strategies API to train and deploy TF models at scale, TF Serving and Google Cloud AI Platform to productionize models, and (briefly) TF Transform, TFLite, TF Addons/Seq2Seq, TensorFlow.js, and TF Agents.

It also introduced many additional ML topics, including a new chapter on unsupervised learning, computer vision techniques for object detection and semantic segmentation, handling sequences using convolutional neural networks (CNNs), natural language processing (NLP) using recurrent neural networks (RNNs), CNNs and transformers, GANs, and more.

See <https://homl.info/changes2> for more details.

Changes Between the Second and the Third Edition

If you read the second edition, here are the main changes between the second and the third edition:

All the code was updated to the latest library versions. In particular, this third edition introduces many new additions to Scikit-Learn (e.g., feature name tracking, histogram-based gradient boosting, label propagation, and more). It also introduces the *Keras Tuner* library for hyperparameter tuning, Hugging Face's *Transformers* library for natural language processing, and Keras's new preprocessing and data augmentation layers.

Several vision models were added (ResNeXt, DenseNet, MobileNet, CSPNet, and EfficientNet), as well as guidelines for choosing the right one.

Chapter 15 now analyzes the Chicago bus and rail ridership data instead of generated time series, and it introduces the ARMA model and its variants.

Chapter 16 on natural language processing now builds an English-to-Spanish translation model, first using an encoder–decoder RNN, then using a transformer model. The chapter also covers language models such as Switch Transformers, DistilBERT, T5, and PaLM (with chain

of-thought prompting). In addition, it introduces vision transformers (ViTs) and gives an overview of a few transformer-based visual models, such as data-efficient image transformers (DeiT), Perceiver, and DINO, as well as a brief overview of some large multimodal models, including CLIP, DALL·E, Flamingo, and GATO.

Chapter 17 on generative learning now introduces diffusion models, and shows how to implement a denoising diffusion probabilistic model (DDPM) from scratch.

Chapter 19 migrated from Google Cloud AI Platform to Google Vertex AI, and uses distributed Keras Tuner for large-scale hyperparameter search. The chapter now includes TensorFlow.js code that you can experiment with online. It also introduces additional distributed training techniques, including PipeDream and Pathways.

In order to allow for all the new content, some sections were moved online, including installation instructions, kernel principal component analysis (PCA), mathematical details of Bayesian Gaussian mixtures, TF Agents, and former appendices A (exercise solutions), C (support vector machine math), and E (extra neural net architectures).

See <https://homl.info/changes3> for more details.

Other Resources

Many excellent resources are available to learn about machine learning. For example, Andrew Ng's **ML course on Coursera** is amazing, although it requires a significant time investment.

There are also many interesting websites about machine learning, including Scikit-Learn's exceptional **User Guide**. You may also enjoy **Dataquest**, which provides very nice interactive tutorials, and ML blogs such as those listed on **Quora**.

There are many other introductory books about machine learning. In particular:

Joel Grus's ***Data Science from Scratch***, 2nd edition (O'Reilly), presents the fundamentals of machine learning and implements some of the main algorithms in pure Python (from scratch, as the name suggests).

Stephen Marsland's *Machine Learning: An Algorithmic Perspective*, 2nd edition (Chapman & Hall), is a great introduction to machine learning, covering a wide range of topics in depth with code examples in Python (also from scratch, but using NumPy).

Sebastian Raschka's *Python Machine Learning*, 3rd edition (Packt Publishing), is also a great introduction to machine learning and leverages Python open source libraries (Pylearn 2 and Theano).

François Chollet's *Deep Learning with Python*, 2nd edition (Manning), is a very practical book that covers a large range of topics in a clear and concise way, as you might expect from the author of the excellent Keras library. It favors code examples over mathematical theory.

Andriy Burkov's *The Hundred-Page Machine Learning Book* (self published) is very short but covers an impressive range of topics, introducing them in approachable terms without shying away from the math equations.

Yaser S. Abu-Mostafa, Malik Magdon-Ismail, and Hsuan-Tien Lin's *Learning from Data* (AMLBook) is a rather theoretical approach to ML that provides deep insights, in particular on the bias/variance trade-off (see [Chapter 4](#)).

Stuart Russell and Peter Norvig's *Artificial Intelligence: A Modern Approach*, 4th edition (Pearson), is a great (and huge) book covering an incredible amount of topics, including machine learning. It helps put ML into perspective.

Jeremy Howard and Sylvain Gugger's *Deep Learning for Coders with fastai and PyTorch* (O'Reilly) provides a wonderfully clear and practical introduction to deep learning using the fastai and PyTorch libraries.

Finally, joining ML competition websites such as [Kaggle.com](#) will allow you to practice your skills on real-world problems, with help and insights from some of the best ML professionals out there.

Conventions Used in This Book

The following typographical conventions are used in this book:

Italic

Indicates new terms, URLs, email addresses, filenames, and file extensions.

Constant width

Used for program listings, as well as within paragraphs to refer to

program elements such as variable or function names, databases, data types, environment variables, statements, and keywords.

Constant width bold

Shows commands or other text that should be typed literally by the user.

Constant width italic

Shows text that should be replaced with user-supplied values or by values determined by context.

Punctuation

To avoid any confusion, punctuation appears outside of quotes throughout the book. My apologies to the purists.

TIP

This element signifies a tip or suggestion.

NOTE

This element signifies a general note.

WARNING

This element indicates a warning or caution.

O'Reilly Online Learning

NOTE

For more than 40 years, *O'Reilly Media* has provided technology and business training, knowledge, and insight to help companies succeed.

Our unique network of experts and innovators share their knowledge and expertise through books, articles, and our online learning platform.

O'Reilly's online learning platform gives you on-demand access to live training courses, in-depth learning paths, interactive coding environments, and a vast collection of text and video from O'Reilly and 200+ other

publishers. For more information, visit <https://oreilly.com>.

How to Contact Us

Please address comments and questions concerning this book to the publisher:

O'Reilly Media, Inc.

1005 Gravenstein Highway North

Sebastopol, CA 95472

800-998-9938 (in the United States or Canada)

707-829-0515 (international or local)

707-829-0104 (fax)

We have a web page for this book, where we list errata, examples, and any additional information. You can access this page at

<https://homl.info/oreilly3>.

Email bookquestions@oreilly.com to comment or ask technical questions about this book.

For news and information about our books and courses, visit <https://oreilly.com>.

Find us on LinkedIn: <https://linkedin.com/company/oreilly-media>

Follow us on Twitter: <https://twitter.com/oreillymedia>

Watch us on YouTube: <https://youtube.com/oreillymedia>

Acknowledgments

Never in my wildest dreams did I imagine that the first and second editions of this book would get such a large audience. I received so many messages from readers, many asking questions, some kindly pointing out errata, and most sending me encouraging words. I cannot express how grateful I am to all these readers for their tremendous support. Thank you all so very much! Please do not hesitate to **file issues on GitHub** if you find errors in the code examples (or just to ask questions), or to submit **errata** if you find errors in the text. Some readers also shared how this book helped them get their first job, or how it helped them solve a concrete problem they were working on.

I find such feedback incredibly motivating. If you find this book helpful, I would love it if you could share your story with me, either privately (e.g., via [LinkedIn](#)) or publicly (e.g., tweet me at [@aureliengeron](#) or write an [Amazon review](#)).

Huge thanks as well to all the wonderful people who offered their time and expertise to review this third edition, correcting errors and making countless suggestions. This edition is so much better thanks to them: Olzhas Akpambetov, George Bonner, François Chollet, Siddha Gangju, Sam Goodman, Matt Harrison, Sasha Sobran, Lewis Tunstall, Leandro von Werra, and my dear brother Sylvain. You are all amazing!

I am also very grateful to the many people who supported me along the way, by answering my questions, suggesting improvements, and contributing to the code on GitHub: in particular, Yannick Assogba, Ian Beauguard, Ulf Bissbort, Rick Chao, Peretz Cohen, Kyle Gallatin, Hannes Hapke, Victor Khaustov, Soonson Kwon, Eric Lebigot, Jason Mayes, Laurence Moroney, Sara Robinson, Joaquín Ruales, and Yuefeng Zhou.

This book wouldn't exist without O'Reilly's fantastic staff, in particular Nicole Taché, who gave me insightful feedback and was always cheerful, encouraging, and helpful: I could not dream of a better editor. Big thanks to Michele Cronin as well, who cheered me on through the final chapters and managed to get me past the finish line. Thanks to the whole production team, in particular Elizabeth Kelly and Kristen Brown. Thanks as well to Kim Cofer for the thorough copyediting, and to Johnny O'Toole, who managed the relationship with Amazon and answered many of my questions. Thanks to Kate Dullea for greatly improving my illustrations. Thanks to Marie Beaugureau, Ben Lorica, Mike Loukides, and Laurel Ruma for believing in this project and helping me define its scope. Thanks to Matt Hacker and all of the Atlas team for answering all my technical questions regarding formatting, AsciiDoc, MathML, and LaTeX, and thanks to Nick Adams, Rebecca Demarest, Rachel Head, Judith McConville, Helen Monroe, Karen Montgomery, Rachel Roumeliotis, and everyone else at O'Reilly who contributed to this book.

I'll never forget all the wonderful people who helped me with the first and second editions of this book: friends, colleagues, experts, including many members of the TensorFlow team. The list is long: Olzhas Akpambetov, Karmel Allison, Martin Andrews, David Andrzejewski, Paige Bailey, Lukas Biewald, Eugene Brevdo, William Chargin, François Chollet, Clément Courbet, Robert Crowe, Mark Daoust, Daniel "Wolff" Dobson, Julien Dubois, Mathias Kende, Daniel Kitachewsky, Nick Felt, Bruce Fontaine, Justin Francis, Goldie Gadde, Irene Giannoumis, Ingrid von

Glehn, Vincent Guilbeau, Sandeep Gupta, Priya Gupta, Kevin Haas, Eddy Hung, Konstantinos Katsiapis, Viacheslav Kovalevskyi, Jon Krohn, Allen Lavoie, Karim Matrah, Grégoire Mesnil, Clemens Mewald, Dan Moldovan, Dominic Monn, Sean Morgan, Tom O'Malley, James Pack, Alexander Pak, Haesun Park, Alexandre Passos, Ankur Patel, Josh Patterson, André Susano Pinto, Anthony Platanios, Anosh Raj, Oscar Ramirez, Anna Revinskaya, Saurabh Saxena, Salim Sémaoune, Ryan Sepassi, Vitor Sessak, Jiri Simsa, Iain Smears, Xiaodan Song, Christina Sorokin, Michel Tessier, Wiktor Tomczak, Dustin Tran, Todd Wang, Pete Warden, Rich Washington, Martin Wicke, Edd Wilder-James, Sam Witteveen, Jason Zaman, Yuefeng Zhou, and my brother Sylvain.

Last but not least, I am infinitely grateful to my beloved wife, Emmanuelle, and to our three wonderful children, Alexandre, Rémi, and Gabrielle, for encouraging me to work hard on this book. Their insatiable curiosity was priceless: explaining some of the most difficult concepts in this book to my wife and children helped me clarify my thoughts and directly improved many parts of it. Plus, they keep bringing me cookies and coffee, who could ask for more?

¹ Geoffrey E. Hinton et al., “A Fast Learning Algorithm for Deep Belief Nets”, *Neural Computation* 18 (2006): 1527–1554.

² Despite the fact that Yann LeCun’s deep convolutional neural networks had worked well for image recognition since the 1990s, although they were not as general-purpose.

Part I. The Fundamentals of Machine Learning

Chapter 1. The Machine Learning Landscape

Not so long ago, if you had picked up your phone and asked it the way home, it would have ignored you—and people would have questioned your sanity. But machine learning is no longer science fiction: billions of people use it every day. And the truth is it has actually been around for decades in some specialized applications, such as optical character recognition (OCR). The first ML application that really became mainstream, improving the lives of hundreds of millions of people, took over the world back in the 1990s: the *spam filter*. It’s not exactly a self-aware robot, but it does

technically qualify as machine learning: it has actually learned so well that you seldom need to flag an email as spam anymore. It was followed by hundreds of ML applications that now quietly power hundreds of products and features that you use regularly: voice prompts, automatic translation, image search, product recommendations, and many more.

Where does machine learning start and where does it end? What exactly does it mean for a machine to *learn* something? If I download a copy of all Wikipedia articles, has my computer really learned something? Is it suddenly smarter? In this chapter I will start by clarifying what machine learning is and why you may want to use it.

Then, before we set out to explore the machine learning continent, we will take a look at the map and learn about the main regions and the most notable landmarks: supervised versus unsupervised learning and their variants, online versus batch learning, instance-based versus model-based learning. Then we will look at the workflow of a typical ML project, discuss the main challenges you may face, and cover how to evaluate and fine-tune a machine learning system.

This chapter introduces a lot of fundamental concepts (and jargon) that every data scientist should know by heart. It will be a high-level overview (it's the only chapter without much code), all rather simple, but my goal is to ensure everything is crystal clear to you before we continue on to the rest of the book. So grab a coffee and let's get started!

TIP

If you are already familiar with machine learning basics, you may want to skip directly to [Chapter 2](#). If you are not sure, try to answer all the questions listed at the end of the chapter before moving on.

What Is Machine Learning?

Machine learning is the science (and art) of programming computers so they can *learn from data*.

Here is a slightly more general definition:

[Machine learning is the] field of study that gives computers the ability to learn without being explicitly programmed.

—Arthur Samuel, 1959

And a more engineering-oriented one:

A computer program is said to learn from experience E with respect to some task T and some performance measure P , if its performance on T , as measured by P , improves with experience E .

—Tom Mitchell, 1997

Your spam filter is a machine learning program that, given examples of spam emails (flagged by users) and examples of regular emails (nonspam, also called “ham”), can learn to flag spam. The examples that the system uses to learn are called the *training set*. Each training example is called a *training instance* (or *sample*). The part of a machine learning system that learns and makes predictions is called a *model*. Neural networks and random forests are examples of models.

In this case, the task T is to flag spam for new emails, the experience E is the *training data*, and the performance measure P needs to be defined; for example, you can use the ratio of correctly classified emails. This particular performance measure is called *accuracy*, and it is often used in classification tasks.

If you just download a copy of all Wikipedia articles, your computer has a lot more data, but it is not suddenly better at any task. This is not machine learning.

Why Use Machine Learning?

Consider how you would write a spam filter using traditional programming techniques (Figure 1-1):

1. First you would examine what spam typically looks like. You might notice that some words or phrases (such as “4U”, “credit card”, “free”, and “amazing”) tend to come up a lot in the subject line. Perhaps you would also notice a few other patterns in the sender’s name, the email’s body, and other parts of the email.
2. You would write a detection algorithm for each of the patterns that you noticed, and your program would flag emails as spam if a number of these patterns were detected.
3. You would test your program and repeat steps 1 and 2 until it was good enough to launch.




Figure 1-1. The traditional approach

Since the problem is difficult, your program will likely become a long list of complex rules—pretty hard to maintain.

In contrast, a spam filter based on machine learning techniques automatically learns which words and phrases are good predictors of spam by detecting unusually frequent patterns of words in the spam examples compared to the ham examples (Figure 1-2). The program is much shorter, easier to maintain, and most likely more accurate.




Figure 1-2. The machine learning approach

What if spammers notice that all their emails containing “4U” are blocked? They might start writing “For U” instead. A spam filter using traditional

programming techniques would need to be updated to flag “For U” emails. If spammers keep working around your spam filter, you will need to keep writing new rules forever.

In contrast, a spam filter based on machine learning techniques automatically notices that “For U” has become unusually frequent in spam flagged by users, and it starts flagging them without your intervention (Figure 1-3).




Figure 1-3. Automatically adapting to change

Another area where machine learning shines is for problems that either are too complex for traditional approaches or have no known algorithm. For example, consider speech recognition. Say you want to start simple and write a program capable of distinguishing the words “one” and “two”. You might notice that the word “two” starts with a high-pitch sound (“T”), so you could hardcode an algorithm that measures high-pitch sound intensity and use that to distinguish ones and twos—but obviously this technique will not scale to thousands of words spoken by millions of very different people in noisy environments and in dozens of languages. The best solution (at least today) is to write an algorithm that learns by itself, given many example recordings for each word.

Finally, machine learning can help humans learn (Figure 1-4). ML models can be inspected to see what they have learned (although for some models this can be tricky). For instance, once a spam filter has been trained on enough spam, it can easily be inspected to reveal the list of words and combinations of words that it believes are the best predictors of spam. Sometimes this will reveal unsuspected correlations or new trends, and thereby lead to a better understanding of the problem. Digging into large amounts of data to discover hidden patterns is called *data mining*, and machine learning excels at it.




Figure 1-4. Machine learning can help humans learn

To summarize, machine learning is great for:

Problems for which existing solutions require a lot of fine-tuning or long lists of rules (a machine learning model can often simplify code and perform better than the traditional approach)

Complex problems for which using a traditional approach yields no good solution (the best machine learning techniques can perhaps find a solution)

Fluctuating environments (a machine learning system can easily be retrained on new data, always keeping it up to date)

Getting insights about complex problems and large amounts of data

Examples of Applications

Let's look at some concrete examples of machine learning tasks, along with the techniques that can tackle them:

Analyzing images of products on a production line to automatically classify them

This is image classification, typically performed using convolutional neural networks (CNNs; see [Chapter 14](#)) or sometimes transformers (see [Chapter 16](#)).

Detecting tumors in brain scans

This is semantic image segmentation, where each pixel in the image is classified (as we want to determine the exact location and shape of tumors), typically using CNNs or transformers.

Automatically classifying news articles

This is natural language processing (NLP), and more specifically text classification, which can be tackled using recurrent neural networks (RNNs) and CNNs, but transformers work even better (see [Chapter 16](#)).

Automatically flagging offensive comments on discussion forums

This is also text classification, using the same NLP tools.

Summarizing long documents automatically

This is a branch of NLP called text summarization, again using the same tools.

Creating a chatbot or a personal assistant

This involves many NLP components, including natural language understanding (NLU) and question-answering modules.

Forecasting your company's revenue next year, based on many performance metrics

This is a regression task (i.e., predicting values) that may be tackled using any regression model, such as a linear regression or polynomial regression model (see [Chapter 4](#)), a regression support vector machine (see [Chapter 5](#)), a regression random forest (see [Chapter 7](#)), or an artificial neural network (see [Chapter 10](#)). If you want to take into account sequences of past performance metrics, you may want to use RNNs, CNNs, or transformers (see [Chapters 15 and 16](#)).

Making your app react to voice commands

This is speech recognition, which requires processing audio samples: since they are long and complex sequences, they are typically processed using RNNs, CNNs, or transformers (see [Chapters 15 and 16](#)).

Detecting credit card fraud

This is anomaly detection, which can be tackled using isolation forests, Gaussian mixture models (see [Chapter 9](#)), or autoencoders (see [Chapter 17](#)).

Segmenting clients based on their purchases so that you can design a different marketing strategy for each segment

This is clustering, which can be achieved using k -means, DBSCAN, and more (see [Chapter 9](#)).

Representing a complex, high-dimensional dataset in a clear and insightful diagram

This is data visualization, often involving dimensionality reduction techniques (see [Chapter 8](#)).

Recommending a product that a client may be interested in, based on past purchases

This is a recommender system. One approach is to feed past purchases (and other information about the client) to an artificial neural network (see [Chapter 10](#)), and get it to output the most likely next purchase.

This neural net would typically be trained on past sequences of purchases across all clients.

Building an intelligent bot for a game

This is often tackled using reinforcement learning (RL; see [Chapter 18](#)), which is a branch of machine learning that trains agents (such as bots) to pick the actions that will maximize their rewards over time (e.g., a bot may get a reward every time the player loses some life points), within a given environment (such as the game). The famous AlphaGo program that beat the world champion at the game of Go was built using RL.

This list could go on and on, but hopefully it gives you a sense of the incredible breadth and complexity of the tasks that machine learning can tackle, and the types of techniques that you would use for each task.

Types of Machine Learning Systems

There are so many different types of machine learning systems that it is useful to classify them in broad categories, based on the following criteria:

How they are supervised during training (supervised, unsupervised, semi-supervised, self-supervised, and others)

Whether or not they can learn incrementally on the fly (online versus

batch learning)

Whether they work by simply comparing new data points to known data points, or instead by detecting patterns in the training data and building a predictive model, much like scientists do (instance-based versus model-based learning)

These criteria are not exclusive; you can combine them in any way you like. For example, a state-of-the-art spam filter may learn on the fly using a deep neural network model trained using human-provided examples of spam and ham; this makes it an online, model-based, supervised learning system.

Let's look at each of these criteria a bit more closely.

Training Supervision

ML systems can be classified according to the amount and type of supervision they get during training. There are many categories, but we'll discuss the main ones: supervised learning, unsupervised learning, self supervised learning, semi-supervised learning, and reinforcement learning.

Supervised learning

In *supervised learning*, the training set you feed to the algorithm includes the desired solutions, called *labels* (Figure 1-5).




Figure 1-5. A labeled training set for spam classification (an example of supervised learning)

A typical supervised learning task is *classification*. The spam filter is a good example of this: it is trained with many example emails along with their *class* (spam or ham), and it must learn how to classify new emails.

Another typical task is to predict a *target* numeric value, such as the price of a car, given a set of *features* (mileage, age, brand, etc.). This sort of task is called *regression* (Figure 1-6). To train the system, you need to give it ¹

many examples of cars, including both their features and their targets (i.e., their prices).

Note that some regression models can be used for classification as well, and vice versa. For example, *logistic regression* is commonly used for classification, as it can output a value that corresponds to the probability of belonging to a given class (e.g., 20% chance of being spam).




Figure 1-6. A regression problem: predict a value, given an input feature (there are usually multiple input features, and sometimes multiple output values)

NOTE

The words *target* and *label* are generally treated as synonyms in supervised learning, but *target* is more common in regression tasks and *label* is more common in classification tasks. Moreover, *features* are sometimes called *predictors* or *attributes*. These terms may refer to individual samples (e.g., “this car’s mileage feature is equal to 15,000”) or to all samples (e.g., “the mileage feature is strongly correlated with price”).

Unsupervised learning

In *unsupervised learning*, as you might guess, the training data is unlabeled (Figure 1-7). The system tries to learn without a teacher.

For example, say you have a lot of data about your blog’s visitors. You may want to run a *clustering* algorithm to try to detect groups of similar visitors (Figure 1-8). At no point do you tell the algorithm which group a visitor belongs to: it finds those connections without your help. For example, it might notice that 40% of your visitors are teenagers who love comic books and generally read your blog after school, while 20% are adults who enjoy sci-fi and who visit during the weekends. If you use a *hierarchical clustering* algorithm, it may also subdivide each group into smaller groups. This may help you target your posts for each group.




Figure 1-7. An unlabeled training set for unsupervised learning




Figure 1-8. Clustering

Visualization algorithms are also good examples of unsupervised learning: you feed them a lot of complex and unlabeled data, and they output a 2D or 3D representation of your data that can easily be plotted (Figure 1-9). These algorithms try to preserve as much structure as they can (e.g., trying to keep separate clusters in the input space from overlapping in the visualization) so that you can understand how the data is organized and perhaps identify unsuspected patterns.

A related task is *dimensionality reduction*, in which the goal is to simplify the data without losing too much information. One way to do this is to merge several correlated features into one. For example, a car's mileage may be strongly correlated with its age, so the dimensionality reduction algorithm will merge them into one feature that represents the car's wear and tear. This is called *feature extraction*.




Figure 1-9. Example of a t-SNE visualization highlighting semantic clusters 2

TIP

It is often a good idea to try to reduce the number of dimensions in your training data using a dimensionality reduction algorithm before you feed it to another machine learning algorithm (such as a supervised learning algorithm). It will run much faster, the data will take up less disk and memory space, and in some cases it may also perform better.

Yet another important unsupervised task is *anomaly detection*—for example, detecting unusual credit card transactions to prevent fraud, catching manufacturing defects, or automatically removing outliers from a dataset before feeding it to another learning algorithm. The system is shown mostly normal instances during training, so it learns to recognize them; then, when it sees a new instance, it can tell whether it looks like a normal one or whether it is likely an anomaly (see [Figure 1-10](#)). A very similar task is *novelty detection*: it aims to detect new instances that look different from all instances in the training set. This requires having a very “clean” training set, devoid of any instance that you would like the algorithm to detect. For example, if you have thousands of pictures of dogs, and 1% of these pictures represent Chihuahuas, then a novelty detection algorithm should not treat new pictures of Chihuahuas as novelties. On the other hand, anomaly detection algorithms may consider these dogs as so rare and so different from other dogs that they would likely classify them as anomalies (no offense to Chihuahuas).




Figure 1-10. Anomaly detection

Finally, another common unsupervised task is *association rule learning*, in which the goal is to dig into large amounts of data and discover interesting relations between attributes. For example, suppose you own a supermarket. Running an association rule on your sales logs may reveal that people who purchase barbecue sauce and potato chips also tend to buy steak. Thus, you may want to place these items close to one another.

Semi-supervised learning

Since labeling data is usually time-consuming and costly, you will often have plenty of unlabeled instances, and few labeled instances. Some algorithms can deal with data that's partially labeled. This is called *semi supervised learning* (Figure 1-11).




Figure 1-11. Semi-supervised learning with two classes (triangles and squares): the unlabeled examples (circles) help classify a new instance (the cross) into the triangle class rather than the square class, even though it is closer to the labeled squares

Some photo-hosting services, such as Google Photos, are good examples of this. Once you upload all your family photos to the service, it automatically recognizes that the same person A shows up in photos 1, 5, and 11, while another person B shows up in photos 2, 5, and 7. This is the unsupervised part of the algorithm (clustering). Now all the system needs is for you to tell

3

it who these people are. Just add one label per person and it is able to name everyone in every photo, which is useful for searching photos.

Most semi-supervised learning algorithms are combinations of

unsupervised and supervised algorithms. For example, a clustering algorithm may be used to group similar instances together, and then every unlabeled instance can be labeled with the most common label in its cluster. Once the whole dataset is labeled, it is possible to use any supervised learning algorithm.

Self-supervised learning

Another approach to machine learning involves actually generating a fully labeled dataset from a fully unlabeled one. Again, once the whole dataset is labeled, any supervised learning algorithm can be used. This approach is called *self-supervised learning*.

For example, if you have a large dataset of unlabeled images, you can randomly mask a small part of each image and then train a model to recover the original image (Figure 1-12). During training, the masked images are used as the inputs to the model, and the original images are used as the labels.



Figure 1-12. Self-supervised learning example: input (left) and target (right)

The resulting model may be quite useful in itself—for example, to repair damaged images or to erase unwanted objects from pictures. But more often than not, a model trained using self-supervised learning is not the final goal. You'll usually want to tweak and fine-tune the model for a slightly different task—one that you actually care about.

For example, suppose that what you really want is to have a pet classification model: given a picture of any pet, it will tell you what species it belongs to. If you have a large dataset of unlabeled photos of pets, you can start by training an image-repairing model using self-supervised learning. Once it's performing well, it should be able to distinguish different

pet species: when it repairs an image of a cat whose face is masked, it must know not to add a dog's face. Assuming your model's architecture allows it (and most neural network architectures do), it is then possible to tweak the model so that it predicts pet species instead of repairing images. The final step consists of fine-tuning the model on a labeled dataset: the model already knows what cats, dogs, and other pet species look like, so this step is only needed so the model can learn the mapping between the species it already knows and the labels we expect from it.

NOTE

Transferring knowledge from one task to another is called *transfer learning*, and it's one of the most important techniques in machine learning today, especially when using *deep neural networks* (i.e., neural networks composed of many layers of neurons). We will discuss this in detail in [Part II](#).

Some people consider self-supervised learning to be a part of unsupervised learning, since it deals with fully unlabeled datasets. But self-supervised learning uses (generated) labels during training, so in that regard it's closer to supervised learning. And the term “unsupervised learning” is generally used when dealing with tasks like clustering, dimensionality reduction, or anomaly detection, whereas self-supervised learning focuses on the same tasks as supervised learning: mainly classification and regression. In short, it's best to treat self-supervised learning as its own category.

Reinforcement learning

Reinforcement learning is a very different beast. The learning system, called an *agent* in this context, can observe the environment, select and perform actions, and get *rewards* in return (or *penalties* in the form of negative rewards, as shown in [Figure 1-13](#)). It must then learn by itself what is the best strategy, called a *policy*, to get the most reward over time. A policy defines what action the agent should choose when it is in a given situation.




Figure 1-13. Reinforcement learning

For example, many robots implement reinforcement learning algorithms to learn how to walk. DeepMind's AlphaGo program is also a good example of reinforcement learning: it made the headlines in May 2017 when it beat Ke Jie, the number one ranked player in the world at the time, at the game of Go. It learned its winning policy by analyzing millions of games, and then playing many games against itself. Note that learning was turned off during the games against the champion; AlphaGo was just applying the policy it had learned. As you will see in the next section, this is called *offline learning*.

Batch Versus Online Learning

Another criterion used to classify machine learning systems is whether or not the system can learn incrementally from a stream of incoming data.

Batch learning

In *batch learning*, the system is incapable of learning incrementally: it must be trained using all the available data. This will generally take a lot of time and computing resources, so it is typically done offline. First the system is trained, and then it is launched into production and runs without learning anymore; it just applies what it has learned. This is called *offline learning*.

Unfortunately, a model's performance tends to decay slowly over time, simply because the world continues to evolve while the model remains unchanged. This phenomenon is often called *model rot* or *data drift*. The solution is to regularly retrain the model on up-to-date data. How often you need to do that depends on the use case: if the model classifies pictures of cats and dogs, its performance will decay very slowly, but if the model deals with fast-evolving systems, for example making predictions on the financial market, then it is likely to decay quite fast.

WARNING

Even a model trained to classify pictures of cats and dogs may need to be retrained regularly, not because cats and dogs will mutate overnight, but because cameras keep changing, along with image formats, sharpness, brightness, and size ratios. Moreover, people may love different breeds next year, or they may decide to dress their pets with tiny hats—who knows?

If you want a batch learning system to know about new data (such as a new type of spam), you need to train a new version of the system from scratch on the full dataset (not just the new data, but also the old data), then replace the old model with the new one. Fortunately, the whole process of training, evaluating, and launching a machine learning system can be automated fairly easily (as we saw in [Figure 1-3](#)), so even a batch learning system can adapt to change. Simply update the data and train a new version of the system from scratch as often as needed.

This solution is simple and often works fine, but training using the full set of data can take many hours, so you would typically train a new system only every 24 hours or even just weekly. If your system needs to adapt to rapidly changing data (e.g., to predict stock prices), then you need a more reactive solution.

Also, training on the full set of data requires a lot of computing resources (CPU, memory space, disk space, disk I/O, network I/O, etc.). If you have a lot of data and you automate your system to train from scratch every day, it will end up costing you a lot of money. If the amount of data is huge, it may even be impossible to use a batch learning algorithm.

Finally, if your system needs to be able to learn autonomously and it has limited resources (e.g., a smartphone application or a rover on Mars), then carrying around large amounts of training data and taking up a lot of resources to train for hours every day is a showstopper.

A better option in all these cases is to use algorithms that are capable

of learning incrementally.

Online learning

In *online learning*, you train the system incrementally by feeding it data instances sequentially, either individually or in small groups called *mini batches*. Each learning step is fast and cheap, so the system can learn about new data on the fly, as it arrives (see [Figure 1-14](#)).




Figure 1-14. In online learning, a model is trained and launched into production, and then it keeps learning as new data comes in

Online learning is useful for systems that need to adapt to change extremely rapidly (e.g., to detect new patterns in the stock market). It is also a good option if you have limited computing resources; for example, if the model is trained on a mobile device.

Additionally, online learning algorithms can be used to train models on huge datasets that cannot fit in one machine's main memory (this is called *out-of-core* learning). The algorithm loads part of the data, runs a training step on that data, and repeats the process until it has run on all of the data (see [Figure 1-15](#)).



Figure 1-15. Using online learning to handle huge datasets

One important parameter of online learning systems is how fast they should adapt to changing data: this is called the *learning rate*. If you set a high learning rate, then your system will rapidly adapt to new data, but it will also tend to quickly forget the old data (and you don't want a spam filter to flag only the latest kinds of spam it was shown). Conversely, if you set a low learning rate, the system will have more inertia; that is, it will learn more slowly, but it will also be less sensitive to noise in the new data or to sequences of nonrepresentative data points (outliers).

WARNING

Out-of-core learning is usually done offline (i.e., not on the live system), so *online learning* can be a confusing name. Think of it as *incremental learning*.

A big challenge with online learning is that if bad data is fed to the system, the system's performance will decline, possibly quickly (depending on the data quality and learning rate). If it's a live system, your clients will notice. For example, bad data could come from a bug (e.g., a malfunctioning sensor on a robot), or it could come from someone trying to game the system (e.g., spamming a search engine to try to rank high in search results). To reduce this risk, you need to monitor your system closely and promptly switch learning off (and possibly revert to a previously working state) if you detect a drop in performance. You may also want to monitor the input data and react to abnormal data; for example, using an anomaly

detection algorithm (see [Chapter 9](#)).

Instance-Based Versus Model-Based Learning

One more way to categorize machine learning systems is by how they *generalize*. Most machine learning tasks are about making predictions. This means that given a number of training examples, the system needs to be able to make good predictions for (generalize to) examples it has never seen before. Having a good performance measure on the training data is good, but insufficient; the true goal is to perform well on new instances.

There are two main approaches to generalization: instance-based learning and model-based learning.

Instance-based learning

Possibly the most trivial form of learning is simply to learn by heart. If you were to create a spam filter this way, it would just flag all emails that are identical to emails that have already been flagged by users—not the worst solution, but certainly not the best.

Instead of just flagging emails that are identical to known spam emails, your spam filter could be programmed to also flag emails that are very similar to known spam emails. This requires a *measure of similarity* between two emails. A (very basic) similarity measure between two emails could be to count the number of words they have in common. The system would flag an email as spam if it has many words in common with a known spam email.

This is called *instance-based learning*: the system learns the examples by heart, then generalizes to new cases by using a similarity measure to compare them to the learned examples (or a subset of them). For example, in [Figure 1-16](#) the new instance would be classified as a triangle because the majority of the most similar instances belong to that class.




Figure 1-16. Instance-based learning

Model-based learning and a typical machine learning workflow

Another way to generalize from a set of examples is to build a model of these examples and then use that model to make *predictions*. This is called *model-based learning* (Figure 1-17).




Figure 1-17. Model-based learning

For example, suppose you want to know if money makes people happy, so you download the Better Life Index data from the [OECD's website](#) and [World Bank stats](#) about gross domestic product (GDP) per capita. Then you join the tables and sort by GDP per capita. [Table 1-1](#) shows an excerpt of what you get.

Table 1-1. Does money make people happier?

Country	GDP per capita (USD)	Life satisfaction
---------	----------------------	-------------------

Turkey	28,384	5.5
--------	--------	-----

Hungary	31,008	5.6
---------	--------	-----

France 42,026 6.5

United States 60,236 6.9

New Zealand 42,404 7.3

Australia 48,698 7.3

Denmark 55,938 7.6

Let's plot the data for these countries (Figure 1-18).




Figure 1-18. Do you see a trend here?

There does seem to be a trend here! Although the data is *noisy* (i.e., partly random), it looks like life satisfaction goes up more or less linearly as the country's GDP per capita increases. So you decide to model life satisfaction as a linear function of GDP per capita. This step is called *model selection*: you selected a *linear model* of life satisfaction with just one attribute, GDP per capita (Equation 1-1).

Equation 1-1. A simple linear model

$$\text{life_satisfaction} = \theta_0 + \theta_1 \times \text{GDP_per_capita}$$

This model has two *model parameters*, θ_0 and θ_1 . By tweaking these parameters, you can make your model represent any linear function, as shown in Figure 1-19.



Figure 1-19. A few possible linear models

Before you can use your model, you need to define the parameter values θ_0 and θ_1 . How can you know which values will make your model perform best? To answer this question, you need to specify a performance measure. You can either define a *utility function* (or *fitness function*) that measures how *good* your model is, or you can define a *cost function* that measures how *bad* it is. For linear regression problems, people typically use a cost function that measures the distance between the linear model's predictions and the training examples; the objective is to minimize this distance.

This is where the linear regression algorithm comes in: you feed it your training examples, and it finds the parameters that make the linear model fit best to your data. This is called *training* the model. In our case, the algorithm finds that the optimal parameter values are $\theta_0 = 3.75$ and $\theta_1 = -5.678 \times 10^{-5}$.

WARNING

Confusingly, the word “model” can refer to a *type of model* (e.g., linear regression), to a *fully specified model architecture* (e.g., linear regression with one input and one output), or to the *final trained model* ready to be used for predictions (e.g., linear regression with

one input and one output, using $\theta_0 = 3.75$ and $\theta_1 = -5.678 \times 10^{-5}$). Model selection consists in choosing the type of model and fully specifying its architecture. Training a model means running an algorithm to find the model parameters that will make it best fit the training data, and hopefully make good predictions on new data.

Now the model fits the training data as closely as possible (for a linear model), as you can see in [Figure 1-20](#).



Figure 1-20. The linear model that fits the training data best

You are finally ready to run the model to make predictions. For example, say you want to know how happy Cypriots are, and the OECD data does not have the answer. Fortunately, you can use your model to make a good prediction: you look up Cyprus's GDP per capita, find \$37,655, and then apply your model and find that life satisfaction is likely to be somewhere –5 around $3.75 + 37,655 \times 6.78 \times 10 = 6.30$.

To whet your appetite, **Example 1-1** shows the Python code that loads the data, separates the inputs X from the labels y , creates a scatterplot for 5 visualization, and then trains a linear model and makes a prediction.

Example 1-1. Training and running a linear model using Scikit-Learn

```
import matplotlib.pyplot as plt
import numpy as np
import pandas as pd
from sklearn.linear_model import LinearRegression

# Download and prepare the data
data_root = "https://github.com/ageron/data/raw/main/"
lifesat = pd.read_csv(data_root + "lifesat/lifesat.csv")
X = lifesat[["GDP per capita (USD)"]].values
y = lifesat[["Life satisfaction"]].values

# Visualize the data
lifesat.plot(kind='scatter', grid=True,
             x="GDP per capita (USD)", y="Life satisfaction")
plt.axis([23_500, 62_500, 4, 9])
plt.show()

# Select a linear model
model = LinearRegression()

# Train the model
model.fit(X, y)
```



```
# Make a prediction for Cyprus
X_new = [[37_655.2]] # Cyprus' GDP per capita in 2020
print(model.predict(X_new)) # output: [[6.30165767]]
```

NOTE

If you had used an instance-based learning algorithm instead, you would have found that Israel has the closest GDP per capita to that of Cyprus (\$38,341), and since the OECD data tells us that Israelis' life satisfaction is 7.2, you would have predicted a life satisfaction of 7.2 for Cyprus. If you zoom out a bit and look at the two next-closest countries, you will find Lithuania and Slovenia, both with a life satisfaction of 5.9. Averaging these three values, you get 6.33, which is pretty close to your model-based prediction. This simple algorithm is called *k-nearest neighbors* regression (in this example, $k = 3$).

Replacing the linear regression model with *k*-nearest neighbors regression in the previous code is as easy as replacing these lines:

```
from sklearn.linear_model import LinearRegression
model = LinearRegression()
```

with these two:

```
from sklearn.neighbors import KNeighborsRegressor
model = KNeighborsRegressor(n_neighbors=3)
```

If all went well, your model will make good predictions. If not, you may need to use more attributes (employment rate, health, air pollution, etc.), get more or better-quality training data, or perhaps select a more powerful model (e.g., a polynomial regression model).

In summary:

You studied the data.

You selected a model.

You trained it on the training data (i.e., the learning algorithm searched for the model parameter values that minimize a cost function).

Finally, you applied the model to make predictions on new cases (this is called *inference*), hoping that this model will generalize well.

This is what a typical machine learning project looks like. In **Chapter 2** you will experience this firsthand by going through a project end to end.

We have covered a lot of ground so far: you now know what machine learning is really about, why it is useful, what some of the most common categories of ML systems are, and what a typical project workflow looks like. Now let's look at what can go wrong in learning and prevent you from

making accurate predictions.

Main Challenges of Machine Learning

In short, since your main task is to select a model and train it on some data, the two things that can go wrong are “bad model” and “bad data”. Let’s start with examples of bad data.

Insufficient Quantity of Training Data

For a toddler to learn what an apple is, all it takes is for you to point to an apple and say “apple” (possibly repeating this procedure a few times). Now the child is able to recognize apples in all sorts of colors and shapes. Genius.

Machine learning is not quite there yet; it takes a lot of data for most machine learning algorithms to work properly. Even for very simple problems you typically need thousands of examples, and for complex problems such as image or speech recognition you may need millions of examples (unless you can reuse parts of an existing model).

THE UNREASONABLE EFFECTIVENESS OF DATA

In a **famous paper** published in 2001, Microsoft researchers Michele Banko and Eric Brill showed that very different machine learning algorithms, including fairly simple ones, performed almost identically

6

well on a complex problem of natural language disambiguation once they were given enough data (as you can see in **Figure 1-21**).

As the authors put it, “these results suggest that we may want to reconsider the trade-off between spending time and money on algorithm development versus spending it on corpus development”.

The idea that data matters more than algorithms for complex problems was further popularized by Peter Norvig et al. in a paper titled “**The 7 Unreasonable Effectiveness of Data**”, published in 2009. It should be noted, however, that small and medium-sized datasets are still very common, and it is not always easy or cheap to get extra training data—so don’t abandon algorithms just yet.



8

Figure 1-21. The importance of data versus algorithms

Nonrepresentative Training Data

In order to generalize well, it is crucial that your training data be representative of the new cases you want to generalize to. This is true whether you use instance-based learning or model-based learning.

For example, the set of countries you used earlier for training the linear model was not perfectly representative; it did not contain any country with a GDP per capita lower than \$23,500 or higher than \$62,500. **Figure 1-22** shows what the data looks like when you add such countries.

If you train a linear model on this data, you get the solid line, while the old model is represented by the dotted line. As you can see, not only does adding a few missing countries significantly alter the model, but it makes it clear that such a simple linear model is probably never going to work well. It seems that very rich countries are not happier than moderately rich

countries (in fact, they seem slightly unhappier!), and conversely some poor countries seem happier than many rich countries.

By using a nonrepresentative training set, you trained a model that is unlikely to make accurate predictions, especially for very poor and very rich countries.




Figure 1-22. A more representative training sample

It is crucial to use a training set that is representative of the cases you want to generalize to. This is often harder than it sounds: if the sample is too small, you will have *sampling noise* (i.e., nonrepresentative data as a result of chance), but even very large samples can be nonrepresentative if the sampling method is flawed. This is called *sampling bias*.

EXAMPLES OF SAMPLING BIAS

Perhaps the most famous example of sampling bias happened during the US presidential election in 1936, which pitted Landon against Roosevelt: the *Literary Digest* conducted a very large poll, sending mail to about 10 million people. It got 2.4 million answers, and predicted with high confidence that Landon would get 57% of the votes. Instead, Roosevelt won with 62% of the votes. The flaw was in the *Literary Digest*'s sampling method:

First, to obtain the addresses to send the polls to, the *Literary Digest* used telephone directories, lists of magazine subscribers, club membership lists, and the like. All of these lists tended to favor wealthier people, who were more likely to vote Republican (hence Landon).

Second, less than 25% of the people who were polled answered. Again this introduced a sampling bias, by potentially ruling out people who didn't care much about politics, people who didn't like the *Literary Digest*, and other key groups. This is a special type of sampling bias called *nonresponse bias*.

Here is another example: say you want to build a system to recognize

funk music videos. One way to build your training set is to search for “funk music” on YouTube and use the resulting videos. But this assumes that YouTube’s search engine returns a set of videos that are representative of all the funk music videos on YouTube. In reality, the search results are likely to be biased toward popular artists (and if you live in Brazil you will get a lot of “funk carioca” videos, which sound nothing like James Brown). On the other hand, how else can you get a large training set?

Poor-Quality Data

Obviously, if your training data is full of errors, outliers, and noise (e.g., due to poor-quality measurements), it will make it harder for the system to detect the underlying patterns, so your system is less likely to perform well. It is often well worth the effort to spend time cleaning up your training data. The truth is, most data scientists spend a significant part of their time doing just that. The following are a couple examples of when you’d want to clean up training data:

If some instances are clearly outliers, it may help to simply discard them or try to fix the errors manually.

If some instances are missing a few features (e.g., 5% of your customers did not specify their age), you must decide whether you want to ignore this attribute altogether, ignore these instances, fill in the missing values (e.g., with the median age), or train one model with the feature and one model without it.

Irrelevant Features

As the saying goes: garbage in, garbage out. Your system will only be capable of learning if the training data contains enough relevant features and not too many irrelevant ones. A critical part of the success of a machine learning project is coming up with a good set of features to train on. This process, called *feature engineering*, involves the following steps:

Feature selection (selecting the most useful features to train on among existing features)

Feature extraction (combining existing features to produce a more useful one—as we saw earlier, dimensionality reduction algorithms can help)

Creating new features by gathering new data

Now that we have looked at many examples of bad data, let’s look at a

couple examples of bad algorithms.

Overfitting the Training Data

Say you are visiting a foreign country and the taxi driver rips you off. You might be tempted to say that *all* taxi drivers in that country are thieves. Overgeneralizing is something that we humans do all too often, and unfortunately machines can fall into the same trap if we are not careful. In machine learning this is called *overfitting*: it means that the model performs well on the training data, but it does not generalize well.

Figure 1-23 shows an example of a high-degree polynomial life satisfaction model that strongly overfits the training data. Even though it performs much better on the training data than the simple linear model, would you really trust its predictions?




Figure 1-23. Overfitting the training data

Complex models such as deep neural networks can detect subtle patterns in the data, but if the training set is noisy, or if it is too small, which introduces sampling noise, then the model is likely to detect patterns in the noise itself (as in the taxi driver example). Obviously these patterns will not generalize to new instances. For example, say you feed your life satisfaction model many more attributes, including uninformative ones such as the country's name. In that case, a complex model may detect patterns like the fact that all countries in the training data with a *w* in their name have a life satisfaction greater than 7: New Zealand (7.3), Norway (7.6), Sweden (7.3), and Switzerland (7.5). How confident are you that the *w*-satisfaction rule generalizes to Rwanda or Zimbabwe? Obviously this pattern occurred in the training data by pure chance, but the model has no way to tell whether a pattern is real or simply the result of noise in the data.

WARNING

Overfitting happens when the model is too complex relative to the amount and noisiness of the training data. Here are possible solutions:

Simplify the model by selecting one with fewer parameters (e.g., a linear model rather than a high-degree polynomial model), by reducing the number of attributes in the training data, or by constraining the model.

Gather more training data.

Reduce the noise in the training data (e.g., fix data errors and remove outliers).

Constraining a model to make it simpler and reduce the risk of overfitting is called *regularization*. For example, the linear model we defined earlier has two parameters, θ_0 and θ_1 . This gives the learning algorithm two *degrees of*

freedom to adapt the model to the training data: it can tweak both the height (θ_0) and the slope (θ_1) of the line. If we forced $\theta_1 = 0$, the algorithm would

have only one degree of freedom and would have a much harder time fitting the data properly: all it could do is move the line up or down to get as close as possible to the training instances, so it would end up around the mean. A very simple model indeed! If we allow the algorithm to modify θ_1 but we

force it to keep it small, then the learning algorithm will effectively have somewhere in between one and two degrees of freedom. It will produce a model that's simpler than one with two degrees of freedom, but more complex than one with just one. You want to find the right balance between fitting the training data perfectly and keeping the model simple enough to ensure that it will generalize well.

Figure 1-24 shows three models. The dotted line represents the original model that was trained on the countries represented as circles (without the countries represented as squares), the solid line is our second model trained with all countries (circles and squares), and the dashed line is a model trained with the same data as the first model but with a regularization constraint. You can see that regularization forced the model to have a smaller slope: this model does not fit the training data (circles) as well as the first model, but it actually generalizes better to new examples that it did not see during training (squares).



Figure 1-24. Regularization reduces the risk of overfitting

The amount of regularization to apply during learning can be controlled by a *hyperparameter*. A hyperparameter is a parameter of a learning algorithm (not of the model). As such, it is not affected by the learning algorithm itself; it must be set prior to training and remains constant during training. If you set the regularization hyperparameter to a very large value, you will get an almost flat model (a slope close to zero); the learning algorithm will almost certainly not overfit the training data, but it will be less likely to find a good solution. Tuning hyperparameters is an important part of building a machine learning system (you will see a detailed example in the next chapter).

Underfitting the Training Data

As you might guess, *underfitting* is the opposite of overfitting: it occurs when your model is too simple to learn the underlying structure of the data. For example, a linear model of life satisfaction is prone to underfit; reality is just more complex than the model, so its predictions are bound to be inaccurate, even on the training examples.

Here are the main options for fixing this problem:

- Select a more powerful model, with more parameters.

- Feed better features to the learning algorithm (feature engineering).

- Reduce the constraints on the model (for example by reducing the regularization hyperparameter).

Stepping Back

By now you know a lot about machine learning. However, we went through so many concepts that you may be feeling a little lost, so let's step back and look at the big picture:

Machine learning is about making machines get better at some task by

learning from data, instead of having to explicitly code rules.

There are many different types of ML systems: supervised or not, batch or online, instance-based or model-based.

In an ML project you gather data in a training set, and you feed the training set to a learning algorithm. If the algorithm is model-based, it tunes some parameters to fit the model to the training set (i.e., to make good predictions on the training set itself), and then hopefully it will be able to make good predictions on new cases as well. If the algorithm is instance-based, it just learns the examples by heart and generalizes to new instances by using a similarity measure to compare them to the learned instances.

The system will not perform well if your training set is too small, or if the data is not representative, is noisy, or is polluted with irrelevant features (garbage in, garbage out). Lastly, your model needs to be neither too simple (in which case it will underfit) nor too complex (in which case it will overfit).

There's just one last important topic to cover: once you have trained a model, you don't want to just "hope" it generalizes to new cases. You want to evaluate it and fine-tune it if necessary. Let's see how to do that.

Testing and Validating

The only way to know how well a model will generalize to new cases is to actually try it out on new cases. One way to do that is to put your model in production and monitor how well it performs. This works well, but if your model is horribly bad, your users will complain—not the best idea.

A better option is to split your data into two sets: the *training set* and the *test set*. As these names imply, you train your model using the training set, and you test it using the test set. The error rate on new cases is called the *generalization error* (or *out-of-sample error*), and by evaluating your model on the test set, you get an estimate of this error. This value tells you how well your model will perform on instances it has never seen before.

If the training error is low (i.e., your model makes few mistakes on the training set) but the generalization error is high, it means that your model is overfitting the training data.

TIP

It is common to use 80% of the data for training and *hold out* 20% for testing. However, this depends on the size of the dataset: if it contains 10 million instances, then holding out 1% means your test set will contain 100,000 instances, probably more than enough to get a good estimate of the generalization error.

Hyperparameter Tuning and Model Selection

Evaluating a model is simple enough: just use a test set. But suppose you are hesitating between two types of models (say, a linear model and a polynomial model): how can you decide between them? One option is to train both and compare how well they generalize using the test set.

Now suppose that the linear model generalizes better, but you want to apply some regularization to avoid overfitting. The question is, how do you choose the value of the regularization hyperparameter? One option is to train 100 different models using 100 different values for this hyperparameter. Suppose you find the best hyperparameter value that produces a model with the lowest generalization error—say, just 5% error. You launch this model into production, but unfortunately it does not perform as well as expected and produces 15% errors. What just happened?

The problem is that you measured the generalization error multiple times on the test set, and you adapted the model and hyperparameters to produce the best model *for that particular set*. This means the model is unlikely to perform as well on new data.

A common solution to this problem is called *holdout validation* (Figure 1-25): you simply hold out part of the training set to evaluate several candidate models and select the best one. The new held-out set is called the *validation set* (or the *development set*, or *dev set*). More specifically, you train multiple models with various hyperparameters on the reduced training set (i.e., the full training set minus the validation set), and you select the model that performs best on the validation set. After this holdout validation process, you train the best model on the full training set (including the validation set), and this gives you the final model. Lastly, you evaluate this final model on the test set to get an estimate of the generalization error.



Figure 1-25. Model selection using holdout validation

This solution usually works quite well. However, if the validation set is too small, then the model evaluations will be imprecise: you may end up selecting a suboptimal model by mistake. Conversely, if the validation set is too large, then the remaining training set will be much smaller than the full training set. Why is this bad? Well, since the final model will be trained on the full training set, it is not ideal to compare candidate models trained on a much smaller training set. It would be like selecting the fastest sprinter to participate in a marathon. One way to solve this problem is to perform repeated *cross-validation*, using many small validation sets. Each model is evaluated once per validation set after it is trained on the rest of the data. By averaging out all the evaluations of a model, you get a much more accurate measure of its performance. There is a drawback, however: the training time is multiplied by the number of validation sets.

Data Mismatch

In some cases, it's easy to get a large amount of data for training, but this data probably won't be perfectly representative of the data that will be used in production. For example, suppose you want to create a mobile app to take pictures of flowers and automatically determine their species. You can easily download millions of pictures of flowers on the web, but they won't be perfectly representative of the pictures that will actually be taken using the app on a mobile device. Perhaps you only have 1,000 representative pictures (i.e., actually taken with the app).

In this case, the most important rule to remember is that both the validation set and the test set must be as representative as possible of the data you expect to use in production, so they should be composed exclusively of representative pictures: you can shuffle them and put half in the validation

set and half in the test set (making sure that no duplicates or near-duplicates end up in both sets). After training your model on the web pictures, if you observe that the performance of the model on the validation set is disappointing, you will not know whether this is because your model has overfit the training set, or whether this is just due to the mismatch between the web pictures and the mobile app pictures.

One solution is to hold out some of the training pictures (from the web) in yet another set that Andrew Ng dubbed the *train-dev set* (Figure 1-26). After the model is trained (on the training set, *not* on the train-dev set), you can evaluate it on the train-dev set. If the model performs poorly, then it must have overfit the training set, so you should try to simplify or regularize the model, get more training data, and clean up the training data. But if it performs well on the train-dev set, then you can evaluate the model on the dev set. If it performs poorly, then the problem must be coming from the data mismatch. You can try to tackle this problem by preprocessing the web images to make them look more like the pictures that will be taken by the mobile app, and then retraining the model. Once you have a model that performs well on both the train-dev set and the dev set, you can evaluate it one last time on the test set to know how well it is likely to perform in production.




Figure 1-26. When real data is scarce (right), you may use similar abundant data (left) for training and hold out some of it in a train-dev set to evaluate overfitting; the real data is then used to evaluate data mismatch (dev set) and to evaluate the final model's performance (test set)

NO FREE LUNCH THEOREM

A model is a simplified representation of the data. The simplifications are meant to discard the superfluous details that are unlikely to generalize to new instances. When you select a particular type of model, you are implicitly making *assumptions* about the data. For example, if you choose a linear model, you are implicitly assuming that the data is fundamentally linear and that the distance between the instances and the straight line is just noise, which can safely be ignored.

In a famous 1996 paper, David Wolpert demonstrated that if you make absolutely no assumption about the data, then there is no reason to prefer one model over any other. This is called the *No Free Lunch*

(NFL) theorem. For some datasets the best model is a linear model, while for other datasets it is a neural network. There is no model that is *a priori* guaranteed to work better (hence the name of the theorem). The only way to know for sure which model is best is to evaluate them all. Since this is not possible, in practice you make some reasonable assumptions about the data and evaluate only a few reasonable models. For example, for simple tasks you may evaluate linear models with various levels of regularization, and for a complex problem you may evaluate various neural networks.

Exercises

In this chapter we have covered some of the most important concepts in machine learning. In the next chapters we will dive deeper and write more code, but before we do, make sure you can answer the following questions:

1. How would you define machine learning?
2. Can you name four types of applications where it shines?
3. What is a labeled training set?
4. What are the two most common supervised tasks?
5. Can you name four common unsupervised tasks?
6. What type of algorithm would you use to allow a robot to walk in various unknown terrains?
7. What type of algorithm would you use to segment your customers into multiple groups?
8. Would you frame the problem of spam detection as a supervised learning problem or an unsupervised learning problem?
9. What is an online learning system?
10. What is out-of-core learning?
11. What type of algorithm relies on a similarity measure to make predictions?
12. What is the difference between a model parameter and a model hyperparameter?
13. What do model-based algorithms search for? What is the most

common strategy they use to succeed? How do they make predictions?

14. Can you name four of the main challenges in machine learning?
15. If your model performs great on the training data but generalizes poorly to new instances, what is happening? Can you name three possible solutions?
16. What is a test set, and why would you want to use it?
17. What is the purpose of a validation set?
18. What is the train-dev set, when do you need it, and how do you use it?
19. What can go wrong if you tune hyperparameters using the test set?

Solutions to these exercises are available at the end of this chapter's notebook, at <https://homl.info/colab3>.

- 1 Fun fact: this odd-sounding name is a statistics term introduced by Francis Galton while he was studying the fact that the children of tall people tend to be shorter than their parents. Since the children were shorter, he called this *regression to the mean*. This name was then applied to the methods he used to analyze correlations between variables.
- 2 Notice how animals are rather well separated from vehicles and how horses are close to deer but far from birds. Figure reproduced with permission from Richard Socher et al., “Zero-Shot Learning Through Cross-Modal Transfer”, *Proceedings of the 26th International Conference on Neural Information Processing Systems* 1 (2013): 935–943.
- 3 That's when the system works perfectly. In practice it often creates a few clusters per person, and sometimes mixes up two people who look alike, so you may need to provide a few labels per person and manually clean up some clusters.
- 4 By convention, the Greek letter θ (theta) is frequently used to represent model parameters.
- 5 It's OK if you don't understand all the code yet; I will present Scikit-Learn in the following chapters.
- 6 For example, knowing whether to write “to”, “two”, or “too”, depending on the context.
- 7 Peter Norvig et al., “The Unreasonable Effectiveness of Data”, *IEEE Intelligent Systems* 24, no. 2 (2009): 8–12.
- 8 Figure reproduced with permission from Michele Banko and Eric Brill, “Scaling to Very Very Large Corpora for Natural Language Disambiguation”, *Proceedings of the 39th Annual Meeting of the Association for Computational Linguistics* (2001): 26–33.
- 9 David Wolpert, “The Lack of A Priori Distinctions Between Learning Algorithms”, *Neural Computation* 8, no. 7 (1996): 1341–1390.

Chapter 2. End-to-End Machine Learning Project

In this chapter you will work through an example project end to end,

pretending to be a recently hired data scientist at a real estate company. This example is fictitious; the goal is to illustrate the main steps of a machine learning project, not to learn anything about the real estate business. Here are the main steps we will walk through:

1. Look at the big picture.
2. Get the data.
3. Explore and visualize the data to gain insights.
4. Prepare the data for machine learning algorithms.
5. Select a model and train it.
6. Fine-tune your model.
7. Present your solution.
8. Launch, monitor, and maintain your system.

Working with Real Data

When you are learning about machine learning, it is best to experiment with real-world data, not artificial datasets. Fortunately, there are thousands of open datasets to choose from, ranging across all sorts of domains. Here are a few places you can look to get data:

Popular open data repositories:

[OpenML.org](#)

[Kaggle.com](#)

[PapersWithCode.com](#)

[UC Irvine Machine Learning Repository](#)

[Amazon's AWS datasets](#)

[TensorFlow datasets](#)

Meta portals (they list open data repositories):

[DataPortals.org](#)

[OpenDataMonitor.eu](#)

Other pages listing many popular open data repositories:

In this chapter we'll use the California Housing Prices dataset from the StatLib repository (see [Figure 2-1](#)¹). This dataset is based on data from the 1990 California census. It is not exactly recent (a nice house in the Bay Area was still affordable at the time), but it has many qualities for learning, so we will pretend it is recent data. For teaching purposes I've added a categorical attribute and removed a few features.




Figure 2-1. California housing prices

Look at the Big Picture

Welcome to the Machine Learning Housing Corporation! Your first task is to use California census data to build a model of housing prices in the state. This data includes metrics such as the population, median income, and median housing price for each block group in California. Block groups are the smallest geographical unit for which the US Census Bureau publishes sample data (a block group typically has a population of 600 to 3,000 people). I will call them “districts” for short.

Your model should learn from this data and be able to predict the median

housing price in any district, given all the other metrics.

TIP

Since you are a well-organized data scientist, the first thing you should do is pull out your machine learning project checklist. You can start with the one in [Appendix A](#); it should work reasonably well for most machine learning projects, but make sure to adapt it to your needs. In this chapter we will go through many checklist items, but we will also skip a few, either because they are self-explanatory or because they will be discussed in later chapters.

Frame the Problem

The first question to ask your boss is what exactly the business objective is. Building a model is probably not the end goal. How does the company expect to use and benefit from this model? Knowing the objective is important because it will determine how you frame the problem, which algorithms you will select, which performance measure you will use to evaluate your model, and how much effort you will spend tweaking it.

Your boss answers that your model's output (a prediction of a district's median housing price) will be fed to another machine learning system (see

2

[Figure 2-2](#)), along with many other signals. This downstream system will determine whether it is worth investing in a given area. Getting this right is critical, as it directly affects revenue.

The next question to ask your boss is what the current solution looks like (if any). The current situation will often give you a reference for performance, as well as insights on how to solve the problem. Your boss answers that the district housing prices are currently estimated manually by experts: a team gathers up-to-date information about a district, and when they cannot get the median housing price, they estimate it using complex rules.



Figure 2-2. A machine learning pipeline for real estate investments

This is costly and time-consuming, and their estimates are not great; in cases where they manage to find out the actual median housing price, they

often realize that their estimates were off by more than 30%. This is why the company thinks that it would be useful to train a model to predict a district's median housing price, given other data about that district. The census data looks like a great dataset to exploit for this purpose, since it includes the median housing prices of thousands of districts, as well as other data.

PIPELINES

A sequence of data processing components is called a data *pipeline*. Pipelines are very common in machine learning systems, since there is a lot of data to manipulate and many data transformations to apply.

Components typically run asynchronously. Each component pulls in a large amount of data, processes it, and spits out the result in another data store. Then, some time later, the next component in the pipeline pulls in this data and spits out its own output. Each component is fairly self-contained: the interface between components is simply the data store. This makes the system simple to grasp (with the help of a data flow graph), and different teams can focus on different components. Moreover, if a component breaks down, the downstream components can often continue to run normally (at least for a while) by just using the last output from the broken component. This makes the architecture quite robust.

On the other hand, a broken component can go unnoticed for some time if proper monitoring is not implemented. The data gets stale and the overall system's performance drops.

With all this information, you are now ready to start designing your system. First, determine what kind of training supervision the model will need: is it a supervised, unsupervised, semi-supervised, self-supervised, or reinforcement learning task? And is it a classification task, a regression task, or something else? Should you use batch learning or online learning techniques? Before you read on, pause and try to answer these questions for yourself.

Have you found the answers? Let's see. This is clearly a typical supervised learning task, since the model can be trained with *labeled* examples (each instance comes with the expected output, i.e., the district's median housing price). It is a typical regression task, since the model will be asked to predict a value. More specifically, this is a *multiple regression* problem, since the system will use multiple features to make a prediction (the district's population, the median income, etc.). It is also a *univariate regression* problem, since we are only trying to predict a single value for

each district. If we were trying to predict multiple values per district, it would be a *multivariate regression* problem. Finally, there is no continuous flow of data coming into the system, there is no particular need to adjust to changing data rapidly, and the data is small enough to fit in memory, so plain batch learning should do just fine.

TIP

If the data were huge, you could either split your batch learning work across multiple servers (using the MapReduce technique) or use an online learning technique.

Select a Performance Measure

Your next step is to select a performance measure. A typical performance measure for regression problems is the *root mean square error* (RMSE). It gives an idea of how much error the system typically makes in its predictions, with a higher weight given to large errors. **Equation 2-1** shows the mathematical formula to compute the RMSE.

Equation 2-1. Root mean square error (RMSE)

$$\text{RMSE}(X, h) = \sqrt{\frac{1}{m} \sum_{i=1}^m (h(x^{(i)}) - y^{(i)})^2}$$

NOTATIONS

This equation introduces several very common machine learning notations that I will use throughout this book:

m is the number of instances in the dataset you are measuring the RMSE on.

For example, if you are evaluating the RMSE on a validation set of 2,000 districts, then $m = 2,000$.

$x^{(i)}$ is a vector of all the feature values (excluding the label) of the i th instance in the dataset, and $y^{(i)}$ is its label (the desired output value for that instance).

For example, if the first district in the dataset is located at longitude -118.29° , latitude 33.91° , and it has 1,416

inhabitants with a median income of \$38,372, and the median house value is \$156,400 (ignoring other features for now), then:

$$\mathbf{x}^{(1)} = \begin{pmatrix} -118.29 \\ 1,416 \\ 38,372 \end{pmatrix}$$

and:

$$y^{(1)} = 156,400$$

$\mathbf{X}$ is a matrix containing all the feature values (excluding labels) of all instances in the dataset. There is one row per instance, and the i th row is equal to the transpose of $\mathbf{x}^{(i)}$, noted $(\mathbf{x}^{(i)})^\top$.

For example, if the first district is as just described, then the matrix $\mathbf{X}$ looks like this:

$$\mathbf{X} = \begin{pmatrix} (\mathbf{x}^{(1)})^\top & (\mathbf{x}^{(2)})^\top & \dots & (\mathbf{x}^{(1999)})^\top & (\mathbf{x}^{(2000)})^\top \\ -118.29 & 33.91 & \dots & \vdots & \vdots \end{pmatrix}$$

h is your system's prediction function, also called a *hypothesis*.

When your system is given an instance's feature vector $\mathbf{x}^{(i)}$, it outputs a predicted value $\hat{y} = h(\mathbf{x}^{(i)})$ for that instance ($\hat{y}$ is pronounced “y-hat”).

For example, if your system predicts that the median housing price in the first district is \$158,400, then $\hat{y} = h(\mathbf{x}^{(1)}) = 158,400$. The prediction error for this district is $\hat{y} - y = 2,000$.

$\text{RMSE}(\mathbf{X}, h)$ is the cost function measured on the set of examples using your hypothesis h .

We use lowercase italic font for scalar values (such as m or y) and function names (such as h), lowercase bold font for vectors (such as $\mathbf{x}$), and uppercase bold font for matrices (such as $\mathbf{X}$).

Although the RMSE is generally the preferred performance measure for regression tasks, in some contexts you may prefer to use another function. For example, if there are many outlier districts. In that case, you may consider using the *mean absolute error* (MAE, also called the *average absolute deviation*), shown in **Equation 2-2**:

Equation 2-2. Mean absolute error (MAE)

$$\text{MAE}(\mathbf{X}, h) = \frac{1}{m} \sum_{i=1}^m |h(\mathbf{x}^{(i)}) - y^{(i)}|$$

Both the RMSE and the MAE are ways to measure the distance between two vectors: the vector of predictions and the vector of target values. Various distance measures, or *norms*, are possible:

Computing the root of a sum of squares (RMSE) corresponds to the *Euclidean norm*: this is the notion of distance we are all familiar with. It is also called the ℓ_2 norm, noted $\|\cdot\|_2$ (or just $\|\cdot\|$).

Computing the sum of absolutes (MAE) corresponds to the ℓ_1 norm, noted $\|\cdot\|_1$. This is sometimes called the *Manhattan norm* because it measures the distance between two points in a city if you can only travel along orthogonal city blocks.

More generally, the ℓ_k norm of a vector $\mathbf{v}$ containing n elements is

defined as $\|\mathbf{v}\|_k = \left(|v_1|^k + |v_2|^k + \dots + |v_n|^k \right)^{1/k}$. k gives the number of nonzero elements in the vector, and ℓ_∞ gives the maximum absolute value in the vector.

The higher the norm index, the more it focuses on large values and neglects

small ones. This is why the RMSE is more sensitive to outliers than the MAE. But when outliers are exponentially rare (like in a bell-shaped curve), the RMSE performs very well and is generally preferred.

Check the Assumptions

Lastly, it is good practice to list and verify the assumptions that have been made so far (by you or others); this can help you catch serious issues early on. For example, the district prices that your system outputs are going to be fed into a downstream machine learning system, and you assume that these prices are going to be used as such. But what if the downstream system converts the prices into categories (e.g., “cheap”, “medium”, or “expensive”) and then uses those categories instead of the prices themselves? In this case, getting the price perfectly right is not important at all; your system just needs to get the category right. If that’s so, then the problem should have been framed as a classification task, not a regression task. You don’t want to find this out after working on a regression system for months.

Fortunately, after talking with the team in charge of the downstream system, you are confident that they do indeed need the actual prices, not just categories. Great! You’re all set, the lights are green, and you can start coding now!

Get the Data

It’s time to get your hands dirty. Don’t hesitate to pick up your laptop and walk through the code examples. As I mentioned in the preface, all the code examples in this book are open source and available **online** as Jupyter notebooks, which are interactive documents containing text, images, and executable code snippets (Python in our case). In this book I will assume you are running these notebooks on Google Colab, a free service that lets you run any Jupyter notebook directly online, without having to install anything on your machine. If you want to use another online platform (e.g., Kaggle) or if you want to install everything locally on your own machine, please see the instructions on the book’s GitHub page.

Running the Code Examples Using Google Colab

First, open a web browser and visit <https://homl.info/colab3>: this will lead you to Google Colab, and it will display the list of Jupyter notebooks for this book (see **Figure 2-3**). You will find one notebook per chapter, plus a

few extra notebooks and tutorials for NumPy, Matplotlib, Pandas, linear algebra, and differential calculus. For example, if you click *02_end_to_end_machine_learning_project.ipynb*, the notebook from **Chapter 2** will open up in Google Colab (see **Figure 2-4**).

A Jupyter notebook is composed of a list of cells. Each cell contains either executable code or text. Try double-clicking the first text cell (which contains the sentence “Welcome to Machine Learning Housing Corp!”). This will open the cell for editing. Notice that Jupyter notebooks use