

Vidyavardhini's College of Engineering & Technology Department of Artificial Intelligence and Data Science

EXPERIMENT 01

Aim: Design and Implementation of a product cipher using Substitution and Transposition ciphers.

Theory:

Substitution Ciphers: These replace each letter in the plaintext with another letter or symbol according to a predetermined key. Examples include Caesar cipher, Atbash cipher, and the more complex polyalphabetic ciphers like the Vigenère cipher.

Transposition Ciphers: Instead of replacing characters, these ciphers rearrange the order of characters in the plaintext according to a specific rule. Examples include the Rail Fence cipher and Columnar Transposition cipher.

A product cipher combines multiple cryptographic techniques, such as substitution and transposition ciphers, to enhance security.

Below is a Python implementation of a product cipher that combines a substitution cipher (Caesar cipher) and a transposition cipher (Rail Fence cipher):

Code:

```
def caesar_cipher_encrypt(text, shift):
  encrypted_text = ""
  for char in text:
     # Encrypt uppercase letters
     if char.isupper():
       encrypted text += chr((ord(char) - 65 + shift) % 26 + 65)
     # Encrypt lowercase letters
     elif char.islower():
       encrypted text += chr((ord(char) - 97 + shift) % 26 + 97)
     # Leave other characters unchanged
     else:
       encrypted_text += char
  return encrypted_text
def rail_fence_cipher_encrypt(text, rails):
  fence = [[] for _ in range(rails)]
  rail = 0
  direction = 1
  for char in text:
     fence[rail].append(char)
     rail += direction
     if rail == rails - 1 or rail == 0:
       direction *=-1
  encrypted text = ""
```



Vidyavardhini's College of Engineering & Technology Department of Artificial Intelligence and Data Science

```
for rail in fence:
     encrypted_text += ".join(rail)
  return encrypted_text
def product cipher encrypt(plaintext, caesar shift, rail fence rails):
  # Step 1: Apply Caesar cipher encryption
  caesar_encrypted_text = caesar_cipher_encrypt(plaintext, caesar_shift)
  # Step 2: Apply Rail Fence cipher encryption
  product_cipher_text = rail_fence_cipher_encrypt(caesar_encrypted_text, rail_fence_rails)
  return product_cipher_text
def main():
  plaintext = input("Enter the plaintext to encrypt: ")
  caesar_shift = int(input("Enter the Caesar cipher shift value (positive integer): "))
  rail fence rails = int(input("Enter the number of rails for Rail Fence cipher (positive integer): "))
  encrypted_text = product_cipher_encrypt(plaintext, caesar_shift, rail_fence_rails)
  print("Encrypted text:", encrypted_text)
if __name__ == "__main__":
  main()
```

Here's a brief overview of how the program works:

- 1. The 'caesar_cipher_encrypt' function encrypts the plaintext using the Caesar cipher with a specified shift value.
- 2. The 'rail_fence_cipher_encrypt' function encrypts the text using the Rail Fence cipher with a specified number of rails.
- 3. The 'product_cipher_encrypt' function applies both the Caesar cipher and the Rail Fence cipher to the plaintext in sequence.
- 4. The 'main' function prompts the user to enter the plaintext, Caesar cipher shift value, and the number of rails for the Rail Fence cipher.
- 5. It then calls the 'product cipher encrypt' function with the provided input and prints the encrypted text.



Vidyavardhini's College of Engineering & Technology Department of Artificial Intelligence and Data Science

Output:

Conclusion:

```
刘 File Edit Selection View Go Run …
                                                                                                                                                                  ▷ ∨ 
□ …
                          ··· 🍦 product_cipher.py 🗡

∨ PROGRAMS

                                  product cipher.pv
                                         def caesar_cipher_encrypt(text, shift):
                                             encrypted_text =
☆
                                               for char in text:
if char.isupper():
                                                       encrypted text += chr((ord(char) - 65 + shift) % 26 + 65)
encrypted_text += chr((ord(char) - 97 + shift) % 26 + 97)
                                                       encrypted_text += char
6
                                               return encrypted_text
                                          def rail_fence_cipher_encrypt(text, rails):
                                              fence = [[] for _ in range(rails)]
      > OUTLINE
      > TIMELINE
                   OUTPUT DEBUG CONSOLE TERMINAL PORTS SQL CONSOLE
                                                                                                                                                         oxed{\Sigma} C Compiler Terminal \oxed{+} \lor \oxed{	ilde{\square}} \oxed{	ilde{\square}} \cdots \oxed{\times}
        PS D:\Vartak college\SEM 6\CSS\Exp\Programs> python .\product_cipher.py
        Enter the plaintext to encrypt: Mokshad
Enter the Caesar cipher shift value (positive integer): 20
Enter the number of rails for Rail Fence cipher (positive integer): 5
            rypted text: Giexmub
        PS D:\Vartak college\SEM 6\CSS\Exp\Programs>
£553
                                                                                          Q Spaces: 4 UTF-8 {} Python A Select Interpreter P Go Live Ninja O Prettier
```

In this experiment, a product cipher combining the Caesar cipher and Rail Fence cipher was implemented in Python. The Caesar cipher substitutes each letter in the plaintext with another letter based on a shift value, while the Rail Fence cipher rearranges the order of characters according to a specified number of rails. By applying both ciphers sequentially, the security of the encryption is enhanced. The program prompts the user for plaintext, Caesar cipher shift value, and the number of rails for the Rail Fence cipher, then produces the encrypted text.