Cross-configuration result heatmap

Tool Filter minus No Defense

ΔBU / ΔUA (percentage points)

−100 −75 −50 −25 0

Darker red = larger utility loss

ΔASR (percentage points)

−50 −25 0

Darker green = larger ASR reduction

Completion coverage (%)

0 25 50 75 100

Darker blue = higher completion coverage

Configuration	ΔBU (pp)	ΔUA (pp)	ΔASR (pp)	Completion coverage (%)	Statistical support		
					BU	UA	ASR
Groq | GPT-OSS-120B	-84.6	-60.5	-18.6	72.3	●	●	●
Groq | GPT-OSS-20B	-57.1	-62.8	-10.3	67.2	○	●	●
OpenRouter | Cohere north-mini-code	-100.0	-47.1	-17.6	28.6	○	●	○
OpenRouter | dots-3-note-preview	-64.7	-3.3	-46.7	100.0	●	○	●
OpenRouter | MiniMax minimax-m2.7	-43.8	-37.0	-10.9	80.5	●	●	○
OpenRouter | MiniMax minimax-m3	-52.9	-70.4	0.0	92.2	●	●	○
OpenRouter | Nemotron 3-nano	-70.6	-80.4	-3.6	94.8	●	●	○
OpenRouter | Nemotron 3-super	-100.0	-27.6	-32.8	96.1	●	●	●
OpenRouter | Nemotron 3-ultra	-68.8	-65.5	0.0	96.1	●	●	○
OpenRouter | Nemotron 3.5-lightning	-94.1	-54.4	-24.6	96.1	●	●	●
OpenRouter | Poolside laguna-s-2.1	-56.2	-69.0	-13.8	96.1	●	●	○
OpenRouter | Poolside laguna-xs-2.1	-80.0	-59.3	-11.1	89.6	●	●	○

Utility degradation was consistent across configurations, whereas security gains were heterogeneous.

● = supported (Holm-adjusted $p < 0.05$)

○ = not supported