Cyber Security

Class no 02 (Theory class)

12 Sep 2024

Lab Part:

```
┌──(shariful㉿kali)-[~]
└─$ cd ~/Desktop      → Change directory location from any directory
```

```
┌──(shariful㉿kali)-[~/Desktop]
└─$ mkdir test1  → make directory
```

```
┌──(shariful㉿kali)-[~/Desktop]
└─$ ls   → check all files and folder in this directory
test1
```

```
┌──(shariful㉿kali)-[~/Desktop]
└─$ cd test1  → change directory for test1
```

```
┌──(shariful㉿kali)-[~/Desktop/test1]
└─$ ls
```

```
┌──(shariful㉿kali)-[~/Desktop/test1]
└─$ touch test.txt → Create .txt file
```

```
┌──(shariful㉿kali)-[~/Desktop/test1]
└─$ ls
test.txt
```

```
┌──(shariful㉿kali)-[~/Desktop/test1]
└─$ open test.txt  → open test.txt folder
```

──(shariful⊗kali)-[~/Desktop/test1]

└─$ cat test.txt → show details in test.txt folder

┌──(shariful⊗kali)-[~/Desktop/test1]
└─$ cd ..   → back one directory

┌──(shariful⊗kali)-[~/Desktop]
└─$ mkdir test2

┌──(shariful⊗kali)-[~/Desktop]
└─$ ls
test1 test2

┌──(shariful⊗kali)-[~/Desktop]
└─$ mv ./test1/test.txt ./test2 →mode test.txt file form test1 folder to test2 folder

┌──(shariful⊗kali)-[~/Desktop]
└─$ cd test2

┌──(shariful⊗kali)-[~/Desktop/test2]
└─$ ls
test.txt

┌──(shariful⊗kali)-[~/Desktop/test2]
└─$