

DATABASE LAB - 14

Task – 01

```
mysql> CREATE DATABASE WeddingDress_0506;  
Query OK, 1 row affected (0.06 sec)
```

Task – 02

```
mysql> CREATE TABLE Customer_0506 (  
->     customer_id INT PRIMARY KEY,  
->     c_name VARCHAR(10) NOT NULL,  
->     c_age INT NOT NULL,  
->     c_addrs VARCHAR(20) NOT NULL,  
->     c_contact_number VARCHAR(25)  
-> );  
Query OK, 0 rows affected (0.12 sec)
```

Task – 03

```
mysql> INSERT INTO Customer_0506 (customer_id, c_name, c_age, c_addrs, c_contact_number) VALUES  
-> (1, 'Ayesha', 24, 'Johar Town', '0300-1234567'),  
-> (4, 'Ahmad', 29, 'Wapda Town', '0333-1234567'),  
-> (6, 'Rameen', 27, 'DHA', NULL),  
-> (2, 'Amina', 20, 'Model Town', '0321-1234567'),  
-> (3, 'Kashif', 18, 'Gulberg', '0313-1234567');  
Query OK, 5 rows affected (0.05 sec)  
Records: 5  Duplicates: 0  Warnings: 0
```

Task – 04

```
mysql> CREATE TABLE Designer_0506 (  
->     designer_id INT PRIMARY KEY,  
->     d_name VARCHAR(15) NOT NULL,  
->     d_category VARCHAR(20) NOT NULL,  
->     d_contact_number VARCHAR(25)  
-> );  
Query OK, 0 rows affected (0.06 sec)  
  
mysql>
```

Task – 05

```
mysql> INSERT INTO Designer_0506 (designer_id, d_name, d_category, d_contact  
_number) VALUES  
-> (100, 'MariaB', 'Unstitched Ladies', '0300-7654321'),  
-> (101, 'Charcoal', 'Men Dressing', '0333-7654321'),  
-> (102, 'Sana Safinaz', 'Unstitched Ladies', '0321-7654321'),  
-> (103, 'Khaadi', 'Unstitched Ladies', '0345-7654321'),  
-> (104, 'Oxford', 'Warm Cloths', '0310-7654321');  
Query OK, 5 rows affected (0.01 sec)  
Records: 5  Duplicates: 0  Warnings: 0
```

Task – 06

```
mysql> CREATE TABLE CustomerDesigner_0506 (  
->     cd_id INT AUTO_INCREMENT PRIMARY KEY,  
->     customer_id INT NOT NULL,  
->     designer_id INT NOT NULL,  
->     dress_type VARCHAR(20) NOT NULL,  
->     priority VARCHAR(25) DEFAULT 'Normal',  
->     FOREIGN KEY (customer_id) REFERENCES Customer_0506(customer_id),  
->     FOREIGN KEY (designer_id) REFERENCES Designer_0506(designer_id)  
-> );  
Query OK, 0 rows affected (0.10 sec)
```

Task – 07

```
mysql> INSERT INTO CustomerDesigner_0506 (customer_id, designer_id, dress_type, priority) VALUES
-> (1, 103, 'Sari', 'Normal'),
-> (1, 102, 'Fancy Suit', 'Normal'),
-> (1, 103, 'Fancy Suit', 'Urgent'),
-> (4, 101, 'Waistcoat', 'Urgent'),
-> (4, 104, 'Sweater', 'Urgent'),
-> (6, 100, 'Fancy Suit', 'Normal'),
-> (2, 100, 'Winter Suit', 'Normal'),
-> (6, 100, 'Winter Suit', 'Urgent'),
-> (3, 104, 'Kurta', 'Normal'),
-> (3, 104, 'Sweater', 'Normal');
Query OK, 10 rows affected (0.02 sec)
Records: 10  Duplicates: 0  Warnings: 0
```

Task – 08

```
mysql> SELECT COUNT(*) AS total_orders
-> FROM CustomerDesigner_0506;
+-----+
| total_orders |
+-----+
|          10 |
+-----+
1 row in set (0.01 sec)
```

Task – 09

```
mysql> SELECT customer_id, COUNT(*) AS total_orders
-> FROM CustomerDesigner_0506
-> GROUP BY customer_id;
+-----+-----+
| customer_id | total_orders |
+-----+-----+
|          1 |          3 |
|          2 |          1 |
|          3 |          2 |
|          4 |          2 |
|          6 |          2 |
+-----+-----+
5 rows in set (0.00 sec)
```

Task – 10

```
mysql> SELECT designer_id, COUNT(*) AS orders_taken
-> FROM CustomerDesigner_0506
-> GROUP BY designer_id;
```

designer_id	orders_taken
100	3
101	1
102	1
103	2
104	3

```
5 rows in set (0.00 sec)
```

Task – 11

```
mysql> SELECT COUNT(*) AS normal_priority_orders
-> FROM CustomerDesigner_0506
-> WHERE priority = 'Normal';
```

normal_priority_orders
6

```
1 row in set (0.01 sec)
```

Task – 12

```
mysql> SELECT c.c_name
-> FROM Customer_0506 c
-> JOIN CustomerDesigner_0506 cd ON c.customer_id = cd.customer_id
-> GROUP BY c.customer_id, c.c_name
-> HAVING COUNT(cd.cd_id) > 1;
```

c_name
Ayesha
Kashif
Ahmad
Rameen

```
4 rows in set (0.01 sec)
```

Task – 13

```
mysql> SELECT d.d_name
-> FROM Designer_0506 d
-> JOIN CustomerDesigner_0506 cd ON d.designer_id = cd.designer_id
-> GROUP BY d.designer_id, d.d_name
-> HAVING COUNT(cd.cd_id) = (
->     SELECT MAX(order_count)
->     FROM (SELECT COUNT(*) AS order_count FROM CustomerDesigner_0506 G
ROUP BY designer_id) AS counts
-> );
+-----+
| d_name |
+-----+
| MariaB |
| Oxford |
+-----+
2 rows in set (0.01 sec)
```

Task – 14

```
mysql> SELECT c.c_name
-> FROM Customer_0506 c
-> JOIN CustomerDesigner_0506 cd ON c.customer_id = cd.customer_id
-> GROUP BY c.customer_id, c.c_name
-> HAVING COUNT(cd.cd_id) = (
->     SELECT MIN(order_count)
->     FROM (SELECT COUNT(*) AS order_count FROM CustomerDesigner_0506 G
ROUP BY customer_id) AS counts
-> );
+-----+
| c_name |
+-----+
| Amina  |
+-----+
1 row in set (0.00 sec)
```

Task – 15

```
mysql> SELECT d_name
-> FROM Designer_0506
-> ORDER BY d_name ASC
-> LIMIT 1;
```

```
+-----+
| d_name |
+-----+
| Charcoal |
+-----+
```

```
1 row in set (0.00 sec)
```

Task – 16

```
mysql> SELECT c.c_name, d.d_name
-> FROM CustomerDesigner_0506 cd
-> JOIN Customer_0506 c ON cd.customer_id = c.customer_id
-> JOIN Designer_0506 d ON cd.designer_id = d.designer_id
-> ORDER BY cd.cd_id ASC
-> LIMIT 1;
```

```
+-----+-----+
| c_name | d_name |
+-----+-----+
| Ayesha | Khaadi |
+-----+-----+
```

```
1 row in set (0.00 sec)
```


Task – 17

```
mysql> SELECT c.c_name, cd.dress_type
-> FROM Customer_0506 c
-> JOIN CustomerDesigner_0506 cd ON c.customer_id = cd.customer_id;
```

c_name	dress_type
Ayesha	Sari
Ayesha	Fancy Suit
Ayesha	Fancy Suit
Amina	Winter Suit
Kashif	Kurta
Kashif	Sweater
Ahmad	Waistcoat
Ahmad	Sweater
Rameen	Fancy Suit
Rameen	Winter Suit

10 rows in set (0.00 sec)

Task – 18

```
mysql> SELECT c.c_name AS customer_name, d.d_name AS designer_name, cd.priority
-> FROM CustomerDesigner_0506 cd
-> JOIN Customer_0506 c ON cd.customer_id = c.customer_id
-> JOIN Designer_0506 d ON cd.designer_id = d.designer_id;
```

customer_name	designer_name	priority
Ayesha	Khaadi	Normal
Ayesha	Sana Safinaz	Normal
Ayesha	Khaadi	Urgent
Amina	MariaB	Normal
Kashif	Oxford	Normal
Kashif	Oxford	Normal
Ahmad	Charcoal	Urgent
Ahmad	Oxford	Urgent
Rameen	MariaB	Normal
Rameen	MariaB	Urgent

10 rows in set (0.00 sec)

Task – 19

```
mysql> ALTER TABLE Designer_0506
-> MODIFY COLUMN d_category VARCHAR(35) NOT NULL;
Query OK, 0 rows affected (0.05 sec)
Records: 0  Duplicates: 0  Warnings: 0
```

Task – 20

```
mysql> UPDATE Designer_0506
-> SET d_category = 'Unstitched Ladies Suit'
-> WHERE d_category = 'Unstitched Ladies';
Query OK, 3 rows affected (0.02 sec)
Rows matched: 3  Changed: 3  Warnings: 0
```

Task – 21

```
mysql> SELECT c.c_name, cd.dress_type, cd.priority
-> FROM CustomerDesigner_0506 cd
-> JOIN Customer_0506 c ON cd.customer_id = c.customer_id
-> JOIN Designer_0506 d ON cd.designer_id = d.designer_id
-> WHERE d.d_name = 'MariaB';
+-----+-----+-----+
| c_name | dress_type | priority |
+-----+-----+-----+
| Rameen | Fancy Suit | Normal  |
| Amina  | Winter Suit | Normal  |
| Rameen | Winter Suit | Urgent  |
+-----+-----+-----+
3 rows in set (0.01 sec)
```

Task – 22

```
mysql> DELETE FROM CustomerDesigner_0506
-> WHERE customer_id = (SELECT customer_id FROM Customer_0506 WHERE c_name = 'Kashif');
Query OK, 2 rows affected (0.01 sec)

mysql> DELETE FROM Customer_0506
-> WHERE c_name = 'Kashif';
Query OK, 1 row affected (0.02 sec)
```

Task – 23

```
mysql> UPDATE Designer_0506
      -> SET d_contact_number = '0300-1111111'
      -> WHERE d_name = 'Khaadi';
Query OK, 1 row affected (0.01 sec)
Rows matched: 1  Changed: 1  Warnings: 0
```

Task – 24

```
mysql> SELECT DISTINCT d.d_name, d.d_contact_number
      -> FROM Designer_0506 d
      -> JOIN CustomerDesigner_0506 cd ON d.designer_id = cd.designer_id
      -> WHERE cd.priority = 'Urgent';
+-----+-----+
| d_name | d_contact_number |
+-----+-----+
| Khaadi | 0300-1111111    |
| Charcoal | 0333-7654321    |
| Oxford | 0310-7654321    |
| MariaB | 0300-7654321    |
+-----+-----+
4 rows in set (0.01 sec)
```