



# Recommender Systems

Advanced Machine Learning  
Data Mining &  
Artificial Intelligence  
CSCI E-82  
Fall 2018

Peter V. Henstock



## Administrivia

- Lecture: Recommender systems
- Saturday section (Rashmi)
  - Recommender systems
  - Intro to Dask – parallelization
    - Scaling Pandas, scikit-learn, numpy workflows
- Next week lecture December 13:
  - Some reinforcement learning
  - Future of AI and hot topics
  - Review of course
  - Possible final presentations?
- Final project December 20


©2018 Peter V. Henstock

## Administrivia

- Final Presentations
  - Held (some possibly) next week
  - Most held 12/20 on the last day
  - Project due 12/19 – no late days
- Start time 12/20 is TBD
  - Will have survey this week
- Short presentations:
  - Context/problem + what you did + result
  - Request video cameras on

©2018 Peter V. Henstock

## Information: 34 GB/day (2009)



[http://bits.blogs.nytimes.com/2009/12/09/the-american-diet-34-gigabytes-a-day/?\\_r=0](http://bits.blogs.nytimes.com/2009/12/09/the-american-diet-34-gigabytes-a-day/?_r=0)

©2018 Peter V. Henstock

## How much data?

- 285 pieces of media content per day
- 54,000 words (63% of network)
- Up to 1000 clickable links
- 443 minutes of video ~ 4 movies

©2018 Peter V. Henstock

## How do we manage to live?

- How can we at least find stuff that is worth our time?
- Ask our friends
  - Seen any good movies lately?
  - Is the iphone XR worth it?
  - Have any good resources for network analysis methods?

©2018 Peter V. Henstock

## Commercial Recommenders

- Amazon
- Yelp
- Match.com/Tinder
- Pretty much every commercial site has some kind of recommender
- RecSys
  - Lovestruck.com
  - ArtFinder
  - Big White Wall: mental health advice


©2018 Peter V. Henstock

## Recommender Space

- Brick & mortar has different space
  - Items are limited by space
  - Can direct customers around store
    - Grocery store
  - Can advertise certain items
- eStores
  - No limit on shelf space
  - Massive space of items—what to buy?
  - Online market provides too many options
  - Recommender systems

©2018 Peter V. Henstock


## Power Law



- X-axis = rankings of items
- Y-axis = number of items
- Power law describes natural distribution

©2018 Peter V. Henstock

## “Long Tail”



- Power law describes natural distribution
- Many discuss the “long tail” distribution

©2018 Peter V. Henstock

## Search vs. Recommender

- Search (Information Retrieval):
  - One-time query of information
  - Google, etc.
  - No model of a user
- Recommender System
  - Utilizes a user profile
  - Amazon.com
  - Often no query

©2018 Peter V. Henstock

## Recommenders

- Ants leave pheromones as a trail
  - Social navigation
  - Following the crowd
- Information Retrieval
  - Extract relevant information
  - TFIDF
  - Rank the retrieved information by relevance
- Information filtering
  - Filter away useless items
  - Profile creation

©2018 Peter V. Henstock

## Successful Recommenders

### amazon

- Reorganized around AI – not one site
- Recommendation engine generates 35% of the company's \$180B revenue
  - Forbes July 16, 2018 by Blake Morgan


### ebay

- Machine Learning is driving incremental sales > \$1B/year
  - VentureBeat August 2, 2018

### NETFLIX

- Saved \$1 Billion from AI
  - Forbes July 9, 2017 by Louis Columbus

## LinkedIn: separate recommenders



©2018 Peter V. Henstock

## LinkedIn

- Job Recommendation
- Talent Match when recruiters post
- News recommendation
- Companies you may want to follow
- Groups to join
- PYMK: similar profiles
  
- 50% of job applications and views are by recommendation

<https://www.quora.com/How-does-LinkedIn-recommendation-system-work>

©2018 Peter V. Henstock

## History of Recommender Systems

- Manual community filtering
  - Forwarding jokes based on taste
  - Small community has similar tastes
  - 1992 **Tapestry** system – Xerox Parc
  
- Collaborative Filtering
  - 1994 **GroupLens**: U Minnesota
  - 1994 **Ringo Music** recommendations MIT
  
- Case Based Reasoning 1980s
  - Roger Schank @yale
  - Initially interest from military

©2018 Peter V. Henstock



## Case-Based Reasoning (CBR)

- Database form used in AI
- Go from specific to general in search
- Know how to solve an ML problem because you've seen something similar before and can apply knowledge
- Adapted to case-based recommendation
- Steer you to personalized approaches
  - Ask questions and have links
  - Easy to explain to the user

©2018 Peter V. Henstock

## Automated Collaborative Filtering

- GroupLens 1994 from Univ. Minnesota
  - Predicted what news articles you would like
  - Nearest neighbor approach based on people preferences
  - Much higher than just average predictions
  - Customized based on similar preferences
- Firefly music recommender from MIT
  - 1995-1999 (RIP) bought by Microsoft in 1998
- Video Recommender from BellCore

©2018 Peter V. Henstock

## GroupLens

- <http://grouplens.org/>
- Cyclopath (bike routes)
- LensKit for building/researching/studying recommender systems
  - Open-Source
- MovieLens

©2018 Peter V. Henstock

## Recommendation Framework

- 1) Domain: what recommending?
- 2) Purpose: sales, help, join
- 3) Context: how/when it's used
- 4) Whose opinions:
- 5) Extent of Personalization:
  - Purchase knowledge of customers
- 6) Privacy & Personal Information:
- 7) Output recommendations, scores, etc.
- 8) Recommendation Algorithm:
  - Content-, Collaborative, etc.

Source: Joseph Konstan

©2018 Peter V. Henstock

## What are recommenders?

- Typically a 2-step process
- 1) Prediction of a ranking (e.g. 1-5 stars) that a given person would assign to a given item
  - 2) Sorting/presentation/interactive process with a user and the ranked values


©2018 Peter V. Henstock

## KDD 2014

### Recommendation as data mining

The core of the Recommendation Engine can be assimilated to a general data mining problem

(Amatriain et al. *Data Mining Methods for Recommender Systems in Recommender Systems Handbook*)




- Xavier Amatriain – August 2014 – KDD

©2018 Peter V. Henstock

## Recommenders & Predictions

- Isn't a recommender system just the same as prediction?




- How is it different?

©2018 Peter V. Henstock

## Recommenders & Predictions

- Isn't a recommender system just the same as prediction?



- What specifically is the Feature Matrix?
- What are the Predictions?

©2018 Peter V. Henstock

## The recommendation problem

	Top Gun	Titanic	Citizen Kane	Toy Story	Brazil
Me		???	1	5	1
Shaggy	5	5	2		1
Scooby	2	2			
Thelma			3		3
Louise	5				

- Assume ratings on 1-5 scale
- Can we easily predict how I would rate Titanic?



©2018 Peter V. Henstock

## Utility Matrix

	Top Gun	Titanic	Citizen Kane	Toy Story	Brazil
Me		???	1	5	1
Shaggy	5	5	2		1
Scooby	2	2			
Thelma			3		3
Louise	5				

- Problem is that the utility matrix is sparse
- Thousands of movies I haven't seen
- Millions of people have seen less
- Main problem: predicting unknowns

©2018 Peter V. Henstock

# New User on Amazon (or other)

- Just created an account – no info

- 1) List of top trending Christmas presents
- 2) Search for L.O.L. Glam Glitter
  - Ranked list of top selling products
  - **Non-personalized ranking statistics**
- 3) Might tell system you like x, y, z
  - Builds **content-based filtering** system for you
- 4) Might figure out preferences from your purchase/ranking similarity to others
  - **Collaborative filtering**

©2018 Peter V. Henstock

## Zagat Guide: “Summary Statistics”

- Average a score based on users



Henstock

## Non-Personalized Scores

- How should the scoring be done?
- Do you take the average of scores?
- Do you take the median?
- Do you take the percentage of users giving positive recommendations?

©2018 Peter V. Henstock



## Limit of Non-Personalized Scores

- Diversity of consumers
- What kind of restaurant do you like?
  - Caviar and champagne?
  - Greasy spoon diner?
  - Ethiopian fusion?
  - Kid-friendly place?
- Business traveler vs. family vacation?

©2018 Peter V. Henstock

## Product association recommender

- Amazon recommends X goes with Y
  - Iphone case with the iphone
  - Tongs and cover with the grill
- Connections to other categories
- More specific recommendations based on similar purchases
- Context changes from time to product

©2018 Peter V. Henstock



## Frequent Itemsets

- Examine what items are bought at the same time
- For Home Depot projects
  - Get X, Y and Z
  - Get home and realize I need Y and H
  - Try Y and H and don't have the right tool
  - Next week buy right tool but then use X
- Point = how to define an itemset?

©2018 Peter V. Henstock


## Time-Valued Scores Issue

- Only consider recent scores where hotel has been frequented in past 2 years
- If you went once and hated it
  - You gave it a bad rating
  - You don't return
- If you went many times and liked it
  - You give it a decent rating
  - You return
- Selection bias

©2018 Peter V. Henstock

# TripAdvisor

## Top Things to Do in Cambridge




**ATTRACTION TYPE:**

- Sights & Landmarks (21)
- Museums (14)
- Tours & Activities (7)
- Outdoor Activities (7)
- Nature & Parks (10)
- Shopping (26)
- Theater & Concerts (14)
- Nightlife (26)
- Boat Tours & Water Sports (2)
- More


**SORT BY:** [Ranking](#) [Book Online](#) [Book tickets & tours in a](#)

**Travel Guides**


- Kid-Friendly Cambridge**
- Day tripping in Boston and Cambridge**

**Mt. Auburn Cemetery** 

#1 of 71 things to do in Cambridge  
 336 reviews  
 "Gorgeous place to take pictures in..." 11/20/2015  
 "An arboretum at the beginning of B..." 11/20/2015  
[Cemeteries](#)

**Harvard University** 

#2 of 71 things to do in Cambridge  
 1,474 reviews  
 "Harvard" 11/30/2015  
 "Harvard" 11/30/2015  
[Educational sites](#) [Historic Sites](#)

**Charles River** 

#3 of 71 things to do in Cambridge  
 401 reviews  
 "Nice area for a walk" 11/22/2015  
 "Beautiful and easy to access" 11/19/2015  
[Scenic Drives](#) [Bodies of Water](#)

©2018 Peter V. Henstock

## How to Present Ranking?

**Harvard Square**

#7 of 71 things to do in Cambridge  
 648 reviews  
 "A walk through history" 11/30/2015  
 "Great place" 11/29/2015  
[Points of Interest & Landmarks](#)

**Longfellow House Washington's Headquarters National Historic Site**

#8 of 71 things to do in Cambridge  
 81 reviews  
 "Fascinating Though Little Known Tr..." 10/27/2015  
 "The most American house on planet..." 10/04/2015  
[Historic Sites](#)

**Historical & Heritage Tours (3)**

#9 of 71 things to do in Cambridge  
 See all 3 Historical & Heritage Tours, including  
 Cambridge Historical Tours  
 The Hahvahd Tour  
 Harvard Historical Walking Tour

**MIT Museum**

#10 of 71 things to do in Cambridge  
 334 reviews  
 "Decent size & some variety (w/rota..." 11/21/2015  
 "Lots of hands on exhibits" 11/18/2015  
[Specialty Museums](#) [Art Galleries](#)

©2018 Peter V. Henstock

## Home Depot microwaves

Best Match 12/6/18



Nostalgia 0.9 cu. ft. Countertop Microwave Oven in Aqua  
Model# RMO44Q  
★★★★☆ (8)  
\$104<sup>55</sup>



Toshiba 1.6 cu. ft. Stainless Steel Countertop Microwave Oven with Inverter Technology  
Model# EM24S4SC-CHSS  
★★★★★ (1)  
\$149<sup>99</sup>



Toshiba 1.2 cu. ft. Black Stainless Steel Countertop Microwave Oven with Smart Sensor  
Model# EM131A5C-CHBS  
★★★★☆ (10)  
\$92<sup>99</sup>



More Options Available  
GE 1.6 cu. ft. Over the Range Microwave Oven in Black  
Model# JVM3160DFBB  
★★★★☆ (10243)  
\$229<sup>00</sup>

- 4.1 stars      6 reviewers
- 5 stars      1 reviewer
- 4 stars      10 reviewers
- 4.2 stars      10243 reviewers

©2018 Peter V. Henstock

## How do display scores for news?

- Have a bunch of stories and want to display the best stories first
- Users have given + or – for each

- How would you display them?

- [www.evanmiller.org/how-not-to-sort-by-average-rating.html](http://www.evanmiller.org/how-not-to-sort-by-average-rating.html)

- Score = #positive - #negative
  - Urban dictionary makes this mistake
- Average rating = #positive / total
  - Amazon makes this mistake

©2018 Peter V. Henstock

## Correct Solution

- Lower bound of Wilson score confidence interval for a Bernoulli parameter
- “Given the ratings, 95% chance that the real fraction of positive ratings is at least” this value

$$\left( \hat{p} + \frac{z_{\alpha/2}^2}{2n} \pm z_{\alpha/2} \sqrt{[\hat{p}(1 - \hat{p}) + z_{\alpha/2}^2/4n]/n} \right) / (1 + z_{\alpha/2}^2/n).$$

- Only works for +/- rankings

©2018 Peter V. Henstock

## Content-Based Filtering

©2018 Peter V. Henstock

## Personalization w/o Collab Filtering

- Flipboard news feeder
  - Stores interest in machine learning
  - Stores enterprise software engineering
  - Stores scripting languages
  - Stores visualization articles
- Local restaurants
- Australian, British, Japanese culture
- Technology
- Ballroom dancing
- Irish fiddling
- Jazz piano

©2018 Peter V. Henstock

## Personalized Scores

- Previously, it was not tailored for user
- General ranking for everyone
- Don't really care if the average person likes Taylor Swift
- How would we come up with a system that makes recommendations based on my preferences?

©2018 Peter V. Henstock

## Content-Based Filtering

- Item profiles
  - Set of features describing an item
- User profile:
  - User recommends/scores various items
  - Set of features that user likes
- Main idea:
  - Matching of user profile to item profiles
  - Often use TFIDF for the features since frequent features are kind of boring
  - Idea: weighted sum of features of ranks

©2018 Peter V. Henstock

## Content-Based Filtering

- User ratings
  - User has specific actors they like
  - User has specific genres they like
  - User has news content topics they like
- Generate a content-based profile designed for an end user
- Keyword vector table
  - Update model based on user feedback
  - Use vector table to rate a given movie
  - Use vector dot product

©2018 Peter V. Henstock

## Personalized Recommender

- Use sparse matrix
  - Rows = users
  - Columns = items
  - Cells = ratings
  - How sparse?
- Recommendation:
  - Predict a value for cell in their columns
  - Select a high value for similar user
- Dimensionality reduction on sparse data

©2018 Peter V. Henstock

## Constructing Content Profile

- Ask the user up front but takes time
- Start with generic news and increase customization over time
  - Clicks
  - Time spent on articles
- Might allow user to edit their profile
- Explicit + Implicit

©2018 Peter V. Henstock

## Data Model for Content

- List of attributes that like/hate
- Compare incoming article against list of attributes in list
- Counts of attributes
- TFIDF form of attributes

©2018 Peter V. Henstock

## Content-Based Filtering

- Attribute/Feature based
- Customized news reader like Flipboard
- Do you want to know about the latest news as well?
- How do you balance these?

©2018 Peter V. Henstock



## Challenges of Content-Based

- Need to have well structured data with clear attributes that allow you to be steered toward a given place
- Restaurant:
  - Price, cuisine, parking, wait-time, service
  - Easy to choose restaurant based on these
- Perfect chocolate chip cookie:
  - Kind of soft, chocolate content, sweet, ?
- Good for choosing between alternatives
- Not good for finding complements

©2018 Peter V. Henstock

## Content-Based Filtering

- Advantages
  - Customized for a single user
  - Explainable to the user
  - Can rate a previously unseen item if can obtain features for it
- Disadvantages
  - How to choose features?
    - User could choose features (hard)
    - System could extract features from ratings (hard)
    - Feature space that works is very hard
  - Lack of diversity—no serendipity/surprise
  - “Cold start” problem: new user has no profile

©2018 Peter V. Henstock



# Collaborative Filtering

©2018 Peter V. Henstock



## Content-Based vs. Collaborative

- Content-Based
  - Utilizes attributes or features of objects
  - Prediction based upon attributes
  - Often easy to understand/explain
- Collaborative Filtering
  - Leverages similarities of your tastes against other people's—not just content
  - Prediction based on similar people's preferences
  - Sparse matrix
  - Difficult to explain

©2018 Peter V. Henstock

## Collaborative Filtering

- For music, I like
  - Top 40 alternative
  - 80s rock
  - Irish fiddling
  - Jazz piano
  - J-pop
- Hard to find a coherent set of features that capture these
- Likely people who overlap some of these genres who have ranked their favorites
- Idea: find similar people to me and leverage their rankings to predict mine

©2018 Peter V. Henstock

## Collaborative Filtering

	Top Gun	Titanic	Braveheart	Citizen Kane	Psycho
Peter	5		2	1	
Paul	1		What rank?	3	5
Mary			1		4

- How could we figure out what recommendation we should make for Paul with Braveheart?
- Asking a question of predicting Paul's tastes in movies

©2018 Peter V. Henstock

## Collaborative Filtering

	Top Gun	Titanic	Braveheart	Citizen Kane	Psycho
Peter	5		2	1	
Paul	1		What rank?	3	5
Mary		5	1	3	4

- Strategy:
  - Find people who have similar tastes to Paul
    - Find the closest N users
  - Use their rankings to estimate the rating
    - Take weighted average perhaps

©2018 Peter V. Henstock


## Collaborative Filtering

	Top Gun	Titanic	Braveheart	Citizen Kane	Psycho
Peter	5		2	1	
Paul	1		What rank?	3	5
Mary		5	1		4

- How to figure out the closest people?
- What distance measure to use?

©2018 Peter V. Henstock


## Vector Concept



©2018 Peter V. Henstock

## Cosine Distance

- $\cos(\theta) = \frac{x \cdot y}{||x|| ||y||}$
- Can use the  $\cos(\theta)$  as similarity metric
- Recommend item  $y$  to user  $x$  when  $\cos(\theta)$  is small
- Works in N-dim space



©2018 Peter V. Henstock

## Collaborative Filtering

	Top Gun	Titanic	Braveheart	Citizen Kane	Psycho
Peter	5		2	1	
Paul	1		What rank?	3	5
Mary		5	1		

- Problem: What to do with missing values?

©2018 Peter V. Henstock

## Pearson Correlation

$$\rho_{X,Y} = \frac{E[(X - \mu_X)(Y - \mu_Y)]}{\sigma_X \sigma_Y}$$

- Notice that the values are centered on the mean values in numerator
  - Subtract mean of each row
- Cancels out the effects of having happy or grumpy reviewers
- Allows us to use 0 for missing values
- Cos difference using de-meaned values is equivalent to the Pearson correlation

©2018 Peter V. Henstock

## Collaborative Filtering

- Identify the people who have the most similar tastes
  - Other constraint?

	Top Gun	Titanic	Braveheart	Citizen Kane	Psycho
Peter	5		2	1	
Paul	1		What rank?	3	5
Mary		5	1		4

©2018 Peter V. Henstock

## Collaborative Filtering

- Identify the  $k$  people who have the most similar tastes *who have rated the movie*

	Top Gun	Titanic	Braveheart	Citizen Kane	Psycho
Peter	5		2	1	
Paul	1		What rank?	3	5
Mary		5	1		4

- What do we do with them?

©2018 Peter V. Henstock

## Choosing Neighborhood

- Can use all the neighbors
  - Cost issues
  - Not particularly useful
- Take the neighbors within threshold
- Take the closest k nearest neighbors
  - Typical scores are 20-100 depending on the topic and data

©2018 Peter V. Henstock

## Range of scores?

- What if prediction is 5.5 out 1 to 5?
- What if negative similarities?
  - Might exclude neighbors with these

©2018 Peter V. Henstock



## Clustering

- What if you cluster the users?
- Doing blindly doesn't usually work
- Can work if done carefully

©2018 Peter V. Henstock

## Collaborative Filtering

- Identify the people who have the most similar tastes *who have rated the movie*

	Top Gun	Titanic	Braveheart	Citizen Kane	Psycho
Peter	5		2	1	
Paul	1		What rank?	3	5
Mary		5	1		4

- What do we do next?

©2018 Peter V. Henstock

## Collaborative Filtering Equation

- Simple option:
  - $Rating(user, item) = \frac{\sum_{k \text{ neighbors}} Rating(k, item)}{k}$
  - Average of similar users' ratings for that particular item (movie)
- How can we improve upon this?

©2018 Peter V. Henstock

## Collaborative Filtering Equation

- Simple option:
  - $Rating(user, item) = \frac{\sum_{k \text{ neighbors}} Rating(k, item)}{k}$
  - Average of similar users' ratings for that particular item (movie)
- Better option:
  - $Rating(user, item) = \frac{\sum_{k \text{ neighbors}} sim(k, user) * Rating(k, item)}{\sum_{k \text{ neighbors}} sim(k, user)}$
- Other aspect: adjust up/down based on whether user tends to give high/low ratings

©2018 Peter V. Henstock

## Item-Item Collaborative Filtering

- Previously focused on user similarity
- Similar users have similar tastes
- Alternative is to focus on item similarity
- Similar items will have similar properties
- Use exactly same equation replacing k similar users with k similar items
- $Rating(user, item) = \frac{\sum_{k \text{ neighbors}} sim(item, k) * Rating(user, k)}{\sum_{k \text{ neighbors}} sim(item, k)}$

©2018 Peter V. Henstock

## Neighborhood of similarity

- How to choose neighborhood?
- Choose the similar items
  - Could choose the k-nearest neighbors
  - Could threshold a distance
- Typically choose  $k \sim 20$
- Precompute item similarities
  - Items are more stable
  - $O(\#items^2)$
  - Tradeoff of k and accuracy

©2018 Peter V. Henstock

## Which works better?

- User-user collaborative filtering
- Item-item collaborative filtering

©2018 Peter V. Henstock

## Which works better?

- User-user collaborative filtering
- Item-item collaborative filtering
- Users are fickle
- Tastes change over time
- Tastes are often not precise
- Represent items with robust features
- Easier to describe items than tastes

©2018 Peter V. Henstock

## Serendipity/Surprise

- User-user collaborative filtering
- Item-item collaborative filtering
- Which method is more likely to let you discovery a new and exciting item through recommendations?

©2018 Peter V. Henstock

## What's the next step?

- *Unifying User-based and Item-based Collaborative Filtering Approaches by Similarity Fusion* by Wang et al. 2006
  - [http://siplab.tudelft.nl/sites/default/files/sigir06\\_similarityfusion.pdf](http://siplab.tudelft.nl/sites/default/files/sigir06_similarityfusion.pdf)
- Combines predictions based on ratings of
  - same item by other users
  - similar items by same user
  - similar items by other users

©2018 Peter V. Henstock

## Computational Issues

- Computation to find the neighborhood?

©2018 Peter V. Henstock

## Computational Issues

- Computation to find the neighborhood?
  - For all rows
    - For all columns
      - Compute difference
  - Proportional to #entries in matrix
- How to get around this problem?

©2018 Peter V. Henstock

## Computational Issues

- Computation to find the neighborhood?
  - For all rows
    - For all columns
      - Compute difference
  - Proportional to #entries in matrix
- How to get around this problem?
  - Pre-cluster the users
  - SVD-like dimensionality reduction
  - Pre-compute neighbors

©2018 Peter V. Henstock

## Locally Sensitive Hashing

- Python Lshash
  - <https://pypi.python.org/pypi/lshash/0.0.4dev>
- Hash:  $x \rightarrow y$ 
  - Generally a unique key  $\rightarrow$  value mapping
  - Eventually there are “collisions” where duplicates occur
- Relax condition of uniqueness, you can create a set of hashes randomly such that similar entries get mapped together
- Rapid nearest neighbor approach

©2018 Peter V. Henstock

## What goes wrong?

- Harry Potter Effect
  - [musicmachinery.com](http://musicmachinery.com) discussion
  - [Whimsley.typepad.com](http://Whimsley.typepad.com)
- Collaborative Filtering recommends popular items
- Recommended popular items become more popular
- Feedback loop

©2018 Peter V. Henstock

## What goes wrong?

- Based on assumption that can find people who have similar tastes as you
- What if your tastes shift?
- What is the scope of your taste?
  - If similar movies → similar music? fashion?

©2018 Peter V. Henstock



## What goes wrong?

- Yelp has an issue where restaurant owners pay people to recommend the restaurant
- Huge issue for all recommender systems and current area of research
- Detecting fakes
  - Ratings that match others too closely
  - Account creation between times
  - Statistical correlation of distributions

©2018 Peter V. Henstock


## Trust-Based Recommenders

- Previously:
  - Similarity between users  $\rightarrow$  weight
- Now:
  - Trust between users  $\rightarrow$  weight
- Example site: Epinions
- Epinions has/had a “web of trust”
  - Bought by shopping.com in 2003
  - Bought by eBay in 2005

©2018 Peter V. Henstock

## Source & Sink Model

- How to compute trust?
  - Explicit measures for trust:
  - Implicit measures for trust:
    - Different answer depending on who asks
- Source asks friends if they trust sink
- Friends might know directly
- Friends might ask their friends
- Pass back weighted average




©2018 Peter V. Henstock

## Hybrid: Master trusted users

- Some users give great advice and are rewarded with a higher ranking
- High trust makes their comments more valuable
- Notion of global trust
- Recommendation system can weight high trusted users more
- Massa & Avesani 2004

©2018 Peter V. Henstock

## TrustWalker 2009



©2018 Peter V. Henstock

## Advantages & Disadvantages

- Advantages
  - Trust is a somewhat stronger link
  - Generally trust friends and they will give advice for you as compared to generic people with similar tastes
- Disadvantages
  - Hard to create a web of trust

©2018 Peter V. Henstock



# Hybrid Measures

©2018 Peter V. Henstock



## Hybrid Methods

- Similar idea to ensemble approaches
- Balance strengths & weaknesses
- Solving specific problems with your data
  - Might not have enough in some genre
  - Want to leverage other data
  - Aim to improve overall performance
  - “Everything else” category

©2018 Peter V. Henstock

## Feature-Weighted Linear Stacking

- Winner of Netflix prize
- $\text{Recommend}(u,i) = \sum \alpha_j \text{Recommend}_j(u,i)$ 
  - Simplest is just weighted sum of different recommenders
- Feature-weighted linear stacking
  - Replace  $\alpha_j$  with  $f_j(\text{user}, \text{item})$
  - Allows generalization to combine different results

©2018 Peter V. Henstock

## Hybridization Methods

### Hybridization Method

### Description

Weighted

Outputs from several techniques (in the form of scores or votes) are combined with different degrees of importance to offer final recommendations

Switching

Depending on situation, the system changes from one technique to another

Mixed

Recommendations from several techniques are presented at the same time

Feature combination

Features from different recommendation sources are combined as input to a single technique

Cascade

The output from one technique is used as input of another that refines the result

Feature augmentation

The output from one technique is used as input features to another

Meta-level

The model learned by one recommender is used as input to another

[https://cow.ceng.metu.edu.tr/Courses/download\\_courseFile.php?id=2861](https://cow.ceng.metu.edu.tr/Courses/download_courseFile.php?id=2861)

©2018 Peter V. Henstock

## Problems/Advantages of Hybrids

- Disadvantages
  - Requires additional tuning
  - Much more difficult to evaluate
  - More computation often involved
- Advantages
  - Widely used in practice
  - Generally try to combine content and collaborative filtering

©2018 Peter V. Henstock

## Evaluation Measures

©2018 Peter V. Henstock

## Evaluation is Difficult

- Data sets: not based on grad students
- Predict all or some of ratings accurately
- What criteria is useful?
  - RMSE?
  - Does business care about RMSE or sales?
- Assume that tastes are constant?
- What about:
  - Diversity
  - Serendipity
  - Non-obvious
  - Recommendations of products already own

©2018 Peter V. Henstock

## Evaluation Methods

- Accuracy/Error Measurements:
- Predictions: AUC, ROC, Precision/Recall
- User action metrics showing influence:
  - Following recommendations
  - How often do users view recommendations
- Business metrics:
  - Sales
  - Lift = increase in busying

©2018 Peter V. Henstock

## Errors

- Predicted vs. Provided recommendation
- 2-stars vs. 2.5-stars
- How can we measure error?
- Mean Absolute Error
  - $\text{Average}(|\text{Predicted} - \text{Actual}|)$
- Root Mean Squared Error
  - $\text{Sqrt}\{\text{Average} [(\text{Predicted} - \text{Actual})^2]\}$
- What are you averaging over?

©2018 Peter V. Henstock

## Netflix Prize

- 1-5 scale
- 100 Million ratings
- 480,000 random customers
- 18,000 movie titles
- 2.8 million customer/movie ID pairs with dates with ratings withheld
- Score used RMSE rounded 0.0001
- Winner 0.8567 (out of 5)
- Is this a good criterion?

©2018 Peter V. Henstock



## Information Retrieval Metrics


Precision-Recall is similar concept to the ROC curve

Google search returns 10 items

- Precision
  - Percentage returned that are correctly on topic
- Recall
  - Percentage of relevant that are selected
- Plot with a sliding threshold

©2018 Peter V. Henstock

## Precision-Recall & F1



- $$F1 = \frac{2 * Precision * Recall}{Precision + Recall}$$
- AUC is a single number ~ MAP
  - Mean Average Precision

©2018 Peter V. Henstock

## Recommending for Decisions

- Is there a difference between 2.5 and 2.6?
- May be better to focus on things they will like vs. things they won't
  - Top 10 should contain all things they like
  - Top 10 should not miss things they would like
- “Reversal” is large prediction error that switches the like/hate preference

©2018 Peter V. Henstock

## Recommending for Decisions

- Is there a difference between 2.5 and 2.6?
- “Reversal” is large prediction error that switches the like/hate preference
  - Should you count these instead?

©2018 Peter V. Henstock

## What is the truth for evaluation?

- Recommendations are only relevant to the individual
- Can't hire graduate students to read documents and determine truth
- How do you get the data?
  - Ask lots of questions?
  - Only look at what they recommended?
  - Request immediate feedback?

©2018 Peter V. Henstock

## How to assess rankings?

- Can't show all rankings but maybe only the top 10
  - Assess how good the recommender estimates are against a user's relative preference
- Mean Reciprocal Rank
  - Get a sorted listed of recommendations
  - $MRR = 1/j$  where  $j$ =first the user likes
  - Measures #items the users has to view in order to get what they like
    - Broccoli, cauliflower, okra, chocolate
    - $\frac{1}{4}$  for me since chocolate = #4

©2018 Peter V. Henstock

## Spearman Correlation

- Pearson correlation of the ranks
- Take correlation of ranks to truth

$$\rho = 1 - \frac{6 \sum d_i^2}{n(n^2 - 1)}$$

Wikipedia  
example answer:  
-0.17575

IQ, $X_i$	Hours of TV per week, $Y_i$	rank $x_i$	rank $y_i$	$d_i$	$d_i^2$
86	0	1	1	0	0
97	20	2	6	-4	16
99	28	3	8	-5	25
100	27	4	7	-3	9
101	50	5	10	-5	25
103	29	6	9	-3	9
106	7	7	3	4	16
110	17	8	5	3	9
112	6	9	2	7	49
113	12	10	4	6	36

With  $d_i^2$  found, add them to find  $\sum d_i^2 = 194$ . The value of  $n$  is 10.

©2018 Peter V. Henstock

## Discounted Cumulative Gain

- In Spearman correlation, all position shifts are equal—but is that useful?
- Notion of half-life
  - User is likely to click the first one item
  - User half as likely to click on 4<sup>th</sup> if half-life = 3
  - Weight accordingly with decreasing weight

$$\bullet \text{ DCG} = \text{rank1} = \sum_{i=2}^n \frac{\text{rank}i}{\log_2(i)}$$

$$\bullet \text{ Normalized DCG} = \frac{\text{DCG}}{\text{perfect DCG}}$$

©2018 Peter V. Henstock

## Wikipedia Example: DCG

- $DCG = rank1 + \sum_{i=2}^n \frac{rank_i}{\log_2(i)}$
- $Normalized\ DCG = \frac{DCG}{perfect\ DCG}$

DCG Table

i	Rank(i)	Log2(i)	Ranki/ log2(i)
1	3	0	N/A
2	2	1	2
3	3	1.585	1.892
4	0	2.0	0
5	1	2.322	0.431
6	2	2.584	0.774
		Total	5.10

Perfect DCG Table

i	Rank(i)	Log2(i)	Ranki/ log2(i)
1	3	0	N/A
2	3	1	3
3	2	1.585	1.262
4	2	2.0	1
5	1	2.322	0.431
6	0	2.584	0
		Total	5.693

- $DCG = 3 + 5.10$  perfect  $DCG = 3 + 5.693$
- $Normalized\ DCG = 8/10/8.693 = 0.932$

©2018 Peter V. Henstock

## Summary of Ranks

- Normalized DCG
  - most common
- Mean Reciprocal Rank
  - Widely used since it's a no-brainer
- Spearman correlation
  - Liked by statisticians (only)
  - More computational
  - Limited by treating all reorderings the same

©2018 Peter V. Henstock



# Other Considerations

©2018 Peter V. Henstock



## Data Collection

- Preference = what users like
- How can we get this information?
  - Types of reviews
    - #stars – but what does it mean?
    - Vote up/down (Reddit, Pandora, Tivo, Zite)
    - Like
  - When do you review?
    - During song or while reading a link
    - After a movie review/stay
    - A month later

©2018 Peter V. Henstock

## Issues with Rating

- Preferences change over time
- Perception of a song:
  - Annoying when you hear it 10x a day
  - Really great song but don't like it
  - Preference of styles changes
- Rating right after movie vs. a week later may not be the same
- What does a 4.0 mean exactly?

©2018 Peter V. Henstock

## Feedback Types

- Explicit Feedback
  - User ratings
  - Product/restaurant reviews
  - Surveys you've filled in
- Implicit Feedback
  - Clicks
  - Purchases
  - Time on page
  - "follow" (Twitter)
  - "skip" on Pandora
  - Leave in cart

©2018 Peter V. Henstock

## Psychology of Preferences

- Attribute Based
  - Evaluate table based notion
- Experience base: Case Based Reasoning
  - Use experience
- Consequences of actions?
- Sociability: see what other people like

©2018 Peter V. Henstock

## Sequences of Books/Movies



- Police Academy, 2, 3, 4, 5, 6



Harry Potter

©2018 Peter V. Henstock



## Extensions

- Too little data: sparse matrix
  - Collaborative filtering fails
  - Sparse matrix with rare items
  - Few recommenders for item
  - Few items recommended by neighbors
- Opposite: too much data
  - Items do not change
  - Preferences change
  - Nearest neighbor users change
  - Computational challenge

©2018 Peter V. Henstock

## Dimensionality Reduction

©2018 Peter V. Henstock

## Dimensionality Reduction

- Rating matrix is sparse
- Columns are generally individual items
  - Not using genres necessarily
  - Not using any ontology typically
- Information Retrieval:
  - Latent Semantic Indexing
  - Mathematical method (PCA/SVD)
  - Maps words into concepts
  - Maps documents into similar clumps

©2018 Peter V. Henstock


## Dimensionality Reduction

- PCA or SVD are dimensionality reduction techniques
- $\text{Rank}(\text{matrix}) = \text{fundamental dimensionality of a matrix}$
- Sparse matrices will generally have a lower rank and have greater compression
- Likely have a small error when project

©2018 Peter V. Henstock

## SVD for non-square matrices

- Previously we focused on SVD of covariance that was symmetric
- $A = \text{Users} \times \text{Items} = U \Sigma V^T$
- **U=User features, V=Item-feature**
- Reduce right side  $n \rightarrow k$  top (less to store)
- <http://slideplayer.com/slide/5186175/>



©2018 Peter V. Henstock

## Benefits of Dimensionality Reduction

- \*\*\*Identify hidden relationships
  - Similarities of items or users
- \*\*Error of projection can be ignored and attributed to noise
- \*Reduce the computation and storage for nearest neighbors, etc.

©2018 Peter V. Henstock

## Utility Matrix Reduction

- Utility matrix = recommender matrix
  - Users = rows
  - Items = columns
- Perform  $SVD(Utility) \rightarrow U\Sigma V^T$
- Choose a subspace of  $k$  dimensions
- Dimensions:
- $m \times n = m \times k \quad k \times k \quad k \times n$

©2018 Peter V. Henstock

## SVD Approximation

- Frobenius norm:  $\|M\|_F = \sqrt{\sum_{ij} M_{ij}^2}$
- $\|Utility - ApproxUtil\|_F = \sqrt{\sum_{ij} (Utility_{ij} - ApproxUtil_{ij})^2}$
- SVD is optimal in that it minimizes the Frobenius norm for a given  $k$ -dimensional approximation

©2018 Peter V. Henstock

## Alternative Notation

- $\text{SVD}(\text{Utility}) \rightarrow U\Sigma V^T$
- $U$  are column vectors
- $V$  are column vectors so  $V^T$  row vectors
- $\Sigma$  is a diagonal matrix
- We can do the math are rewrite it as
- $\text{SVD}(\text{Utility}) = \sum_{i=1}^k \sigma_i U_i V_i^T$
- Each  $U$  vector  $\sim \text{user} \rightarrow \text{concept}$
- Each  $V$  vector  $\sim \text{item} \rightarrow \text{concept}$
- What is the  $\sigma_i$  on diagonal of  $\Sigma$ ?

©2018 Peter V. Henstock

## Other Techniques

- Many approaches for working with sparse matrices such as with collaborative filtering
- singular value projection (SVP)
- spectral regularization algorithm (SoftImpute) *trace norm minimization*
- low rank matrix fitting (LMaFit)
- alternating minimization (AltMin) *alternating optimization*
- boosting type accelerated matrix-norm penalized solver (Boost)
- Jaggi's fast algorithm for trace norm constraint (JS)
- greedy efficient component optimization (GECO)
- Rank-one matrix pursuit (R1MP) *atomic decomposition*
- Economic rank-one matrix pursuit (ER1MP)

- <http://0xmachine.com/tutorials/tutorial-icdm2015sparse.pdf>

©2018 Peter V. Henstock

## How many dimensions?

- Movies need 13-20 dimensions
- Music needs similar numbers
- Determine #dimensions empirically
- Scaling issue
  - Many weights

©2018 Peter V. Henstock

## Honey, we shrunk the matrix!

- 100 users and 5 movies
- Have a utility matrix  $100 \times 5$
- Perform SVD  $\rightarrow U \Sigma V^T$
- Choose just 2 dimensions so  $k=2$
- Reduced Utility Matrix:
  - $U$ :  $100 \times 2$ ,
  - $V^T$ :  $2 \times 5$
  - $V$ :  $5 \times 2$

©2018 Peter V. Henstock

## Honey, we shrunk the matrix!

- What do you do with a shrunk matrix?

	Top Gun	Titanic	Braveheart	Citizen Kane	Psycho
Peter	5		2	1	
Paul	1		What rank?	3	5
Mary		5	1		
NewUser	2			3	3

©2018 Peter V. Henstock

## Honey, we shrunk the matrix!

- What do you do with a shrunk matrix?

	Top Gun	Titanic	Braveheart	Citizen Kane	Psycho
Peter	5		2	1	
Paul	1		What rank?	3	5
Mary		5	1		
NewUser	2			3	3

- Need to project a user's preferences into the corresponding "concept" space or latent variable space
- NewUser [2 0 0 3 3] \* what? →

©2018 Peter V. Henstock

## Honey, we shrunk the matrix!

- What do you do with a shrunk matrix?
- Need to project a user's preferences into the corresponding "concept" space or latent variable space

	Top Gun	Titanic	Braveheart	Citizen Kane	Psycho
Peter	5		2	1	
Paul	1		What rank?	3	5
Mary		5	1		
NewUser	2			3	3

- NewUser  $[2 \ 0 \ 0 \ 3 \ 3] * V \rightarrow 1 \times 2$  vector

©2018 Peter V. Henstock

## What have we gained?

©2018 Peter V. Henstock



## What have we gained?

- Less computation
  - Previously we had to math on a much larger matrix for every recommendation
  - Now we can compute an [expensive] reduce utility matrix once every now and then
- Primary advantage is...?

©2018 Peter V. Henstock

## What have we gained?

- Less computation
  - Previously we had to math on a much larger matrix for every recommendation
  - Now we can compute an [expensive] reduce utility matrix once every now and then
- Primary advantage is...?
  - Mapped movies into concepts
  - “Chick-flick romance comedy” concept
  - “Scify with explosions & car chases” concept
  - By mapping, automatically find similarity to concept even if no users actually had the movies in common

©2018 Peter V. Henstock

## Updating the Matrix

- $A = U\Sigma V^T$
- Compute this matrix occasionally (big)
- Can update new data called “fold-in”
- New users can be added
- New items can be added

©2018 Peter V. Henstock

## Problems with SVD

- Computation
  - $O(mn^2)$  where  $m \geq n$
  - But fairly fast to predict
  - Needs faster approximations
  - Needs incremental methods for adding data
- Interpretability
  - Linear combination of features
- Sparse Matrix
  - Didn't deal with this before

©2018 Peter V. Henstock

## Missing Value Problem

- Math assumes full matrix
- Could impute all the missing values
  - Lots of missing values
- Could zero-mean the values
  - Missing values becomes zeros

©2018 Peter V. Hensstock

## Convex Optimization

- Goal is to find the user and item features and solve the problem without the full matrix of linear algebra
- $A = \text{Users} \times \text{Items} = U \Sigma V^T$
- Actually not going to compute full  $A$  but an approximation to  $A$  based on the top  $k$ -eigenvalues
- $\min_X \|A - X\|_F : \text{rank}(X) = k$ 
  - Frobenius norm
- Achieves the minimum error

©2018 Peter V. Hensstock

## Simon Funk blog

<http://sifter.org/~simon/journal/20061211.html>



Auckland, NZ?

©2018 Peter V. Henstock

## FunkSVD

- Originated in the Netflix prize
- Gradient-descent approach for optimization
  - Uses learning rate and regularization term
  - Minimize predicted error vs. actual
- Train feature one at a time
- Ignore all missing values
- Solve

©2018 Peter V. Henstock

## Incremental SVD Solution

- Start with A matrix
  - U is  $m \times k$  matrix
  - V is  $n \times k$  matrix
  - Initialize U and V with small number
- Loop through each of k features
  - Predicted value = dot product  $u \cdot v$  for entry
  - $\text{Error}_{ij} = A_{ij} - \text{predicted}_{ij}$
  - Use error to update U and V for entry
    - Take learning rate and regularization into account
    - Uses a gradient descent algorithm

©2018 Peter V. Henstock

## Families of techniques

- SVD++
  - Extension of FunkSVD
- Add in other terms
  - Social networks
  - Recommendations of other media
  - Trust
  - Item similarity
  - Etc.

©2018 Peter V. Henstock

## Optimization

$$\min_{\mathbf{w} \in \mathbb{R}^d} \left\{ f(\mathbf{w}) = l(\mathbf{w}) + r(\mathbf{w}) = \frac{1}{n} \sum_{i=1}^n l_i(\mathbf{w}) + r(\mathbf{w}) \right\},$$

Name	Loss function $l_i(\mathbf{w})$
Least Squares	$\frac{1}{2}(y_i - \mathbf{x}_i^T \mathbf{w})^2$
Logistic Regression	$\log(1 + \exp(-y_i \mathbf{x}_i^T \mathbf{w}))$
Squared Hinge Loss	$\max(0, 1 - y_i \mathbf{x}_i^T \mathbf{w})^2$

Name	regularizer (penalty) $r(\mathbf{w})$
Lasso [49]	$\lambda \sum_{j=1}^d  w_j $
Fused Lasso [50]	$\lambda_1 \sum_{j=1}^d  w_j  + \lambda_2 \sum_{j=1}^{d-1}  w_j - w_{j+1} $
Graph Fused Lasso [8]	$\lambda_1 \sum_{j=1}^d  w_j  + \lambda_2 \sum_{(j,k) \in \mathcal{E}}  w_j - w_k $
Group Lasso [65]	$\lambda \sum_{k=1}^K \ \mathbf{w}_{\mathcal{G}_k}\ $
Sparse Group Lasso [13, 44]	$\lambda_1 \sum_{j=1}^d  w_j  + \lambda_2 \sum_{k=1}^K \ \mathbf{w}_{\mathcal{G}_k}\ $
Tree Lasso [34, 24]	$\sum_{j=1}^J \sum_{k=1}^{K_j} \lambda_k^j \ \mathbf{w}_{\mathcal{G}_k^j}\ $

<http://0xmachine.com/tutorials/tutorial-icdm2015sparse.pdf>

©2018 Peter V. Henstock

## Is SVD the best Decomposition?

- Yes, it is optimal but many others
- CUR Decomposition  $\sim O(mn)$ 
  - Mahoney & Drineas 2008
  - [www.pnas.org/content/106/3/697.abstract](http://www.pnas.org/content/106/3/697.abstract)
  - C = columns from original matrix
  - R = sample of rows from original matrix
  - U = pseudo-inverse of intersection of C&R
- $\|A - CUR\|_F \leq \|A - A_K\|_F + \varepsilon \|A\|_F$ 
  - True with probability of at least  $1 - \delta$
- Generally choose  $4 \cdot k$  columns and rows

©2018 Peter V. Henstock

## CUR Decomposition

- Different approach
- Typically 4x as many rows and columns
  - Over an order of magnitude bigger
- Not as good a fit
- Why would we do this?
  - Less computation  $O(mn)$  vs.  $O(mn^2)$

©2018 Peter V. Henstock

## CUR Row/Col Selection

- Probabilistic selection of columns
  - Define probability of column to be proportional to the length of the column
  - All probabilities have to add to 1 so normalize to sum of all lengths
- Randomly select using probabilities from previous step
- Choose columns and normalize them
- Repeat for rows

©2018 Peter V. Henstock

## U Matrix calculation

- Take the product of C and R
  - C is subset of c columns
  - R is subset of r rows
  - Product will be  $c \times r$  (matrix multiplication)
  - Called the “intersection” of C and R
- Compute SVD of  $(c \times r)$
- “Umatrix” =  $U\Sigma V^T$  of intersection except the diagonal of  $\Sigma$  uses  $1/\sigma$  instead of  $\sigma$
- CUR’s U matrix is the pseudoinverse

©2018 Peter V. Henstock

# Recent Work

©2018 Peter V. Henstock



## Recommender for Everything

- What time I wake up
- What to eat for breakfast
- Which route to take to work
- Which emails should I read first
- Which courses I should take to maximize my career
- ...
- How to connect movie recommenders with music recommenders, etc.

©2018 Peter V. Henstock

## Recent work in Psychology

- How do people make decisions?
- How do people optimize over criteria?
- How do opinions change over time?
- What other factors do users pay attention to?
- How do users view recommendation systems? What do they want?
- Related areas:
  - UI Design with eye-tracking, talk-alouds, etc.
  - A/B Testing
  - Field work: surveys, etc.

©2018 Peter V. Henstock

## Explaining Recommendations

- Transparency: How system works
- Scrutability: User says wrong
- Trust: User confidence in sys
- Effectiveness: Helps user
- Persuasiveness: Convince user
- Efficiency: Faster decisions
- Satisfaction: Enjoyment/Ease
  
- Tintarev & Masthoff 2012

©2018 Peter V. Henstock

## Matrix Factorizations

- Tying in additional data on individual
  - Filling in gaps of sparse data
  - Big data era
- Linking social networks to recommendation systems in various ways
- Hybrid work

©2018 Peter V. Henstock

## Influence Limiting

- Prevent undue influence from someone trying to create/bias results by
  - perhaps creating accounts
  - stacking the results
- Influence may be promoting something
- Influence may be attacking competition

©2018 Peter V. Henstock

## Privacy Issues

- Users may be happy contribute but do not want their preferences known
  - Don't want to be advertising victim
  - Don't want others to know what they bought
- Encrypted/PGP methods
- Peer-to-Peer recommendations
- Shrinkage methods to compress and anonymize data
- Lots of research in medical data field

©2018 Peter V. Henstock

## Open Source Recommenders

- LensKit ([lenskit.org](http://lenskit.org))
- Apache Lucene ([lucene.apache.org](http://lucene.apache.org))
  - SOLR
  - PyLucene
- jCOLIBRI: Case Based Reasoning
  - [Gaia.fdi.ucm.es/research/colibri/jcolibri](http://Gaia.fdi.ucm.es/research/colibri/jcolibri)
- Crab (Python) [muricoca.github.org](http://muricoca.github.org)
- Recommenderlab for R

©2018 Peter V. Henstock