

钱龙OSC

QL_OSC

Var1:=REF(CLOSE,1);

Var2:=SUM(VOL,2)/((HHV(HIGH,2)-LLV(LOW,2))*100);

Var3:=(CLOSE-Var1)*Var2;

Var4:=SUM(Var3,0);

Var5:=SMA(Var4,5,1);

Var6:=SMA(Var4,8,1);

OSC: Var5-Var6;

OSCMa: MA(OSC,4);

OSC, COLORSTICK;

VD: SUM(IF(OSC>0,OSC*1.003,OSC*1.003>0),34)/34;

VE: SUM(IF(OSC<=0,OSC*0.97,OSC*0.97<0),34)/34;

0;

钱龙长线

QL_LONG

N(1,100,10);

乾龙长线:0;

Var1:=REF(CLOSE,1);

Var2:=SUM(VOL,2)/((HHV(HIGH,2)-LLV(LOW,2))*100);

Var3:=(CLOSE-Var1)*Var2;

Var4:=SUM(Var3,0);

Var5:=SMA(Var4,10,1);

Var6:=SMA(Var4,20,1);

LONMA: MA(Var5-Var6,n)COLORgreen;

Var5-Var6,COLORyellow;

Var5-Var6,COLORSTICK

钱龙变动速率

QL_BDSL

N(1,100, 13);

M(1,50, 6);

R:(C-REF(C,N))/REF(C,N)*100;

RMA:MA(R,M);

d:if(R<0,-R,R);

0,CIRCLEDOT;

钱龙布林

QL_BOLL

N(1, 100, 20);

D(1, 20, 2);

mb:ma(c,n);

r:=pow((c-mb),2);

x1:=ma(r,n);

x:=SQRT(x1);

upper:mb+d*x;

lower:mb-d*x;

STICKLINE(close>=open,open,close,5,1),colorred;

STICKLINE(open>close,close,open,5,0),colorgreen;

STICKLINE(close>=open,close,HIGH,0.5,1),colorred;

STICKLINE(close>=open,open,low,0.5,1),colorred;

STICKLINE(open>close,close,low,0.5,0),colorgreen;

STICKLINE(open>close,open,HIGH,0.5,0),colorgreen;

钱龙量布林

QL_VBOLL

mb:ma(v,13);

r:=pow((v-mb),2);

x1:=ma(r,13);

x:=SQRT(x1);

upper:mb+1*x;

lower:mb-1*x;

钱龙薛斯通道

QL_XSTD

N1(1,100,30);

N2(1,100,3);

P1(1,100,15);

P2(1,100,3);

UPPERL: MA(HIGH,n1)*(1+p1/100),colorwhite;

UPPERS: MA(HIGH,n2)*(1+p2/100),coloryellow;

LOWERS: MA(LOW,n2)*(1-p2/100),colorff00ff;

LOWERL: MA(LOW,n1)*(1-p1/100),color00ff00;

钱龙趋向指标

N(2,100,14);

M(1,100,6)

TR = SMA(MAX(MAX(HIGH-LOW,ABS(HIGH-REF(CLOSE,1))),ABS(LOW-REF(CLOSE,1))),N,1);

HD = HIGH-REF(HIGH,1);

LD = REF(LOW,1)-LOW;

DMP= SMA(IF(HD>0 && HD>LD,HD,0),N,1);

DMM= SMA(IF(LD>0 && LD>HD,LD,0),N,1);

PDI: DMP*100/TR;

MDI: DMM*100/TR;

ADX: SMA(ABS(MDI-PDI)/(MDI+PDI)*100,N,1);

ADXR:(ADX+REF(ADX,M))/2;