

Program 2 - Adventure

Due May 3, 2020 by 11:59pm **Points** 160 **Submitting** a file upload **File Types** zip
Available Apr 17, 2020 at 12:01am - May 6, 2020 at 11:59pm 20 days

This assignment was locked May 6, 2020 at 11:59pm.

Program 2 – CS 344

This assignment asks you to write a simple game akin to old text adventure games like Adventure:

http://en.wikipedia.org/wiki/Colossal_Cave_Adventure [_ \(http://en.wikipedia.org/wiki/Colossal_Cave_Adventure\)](http://en.wikipedia.org/wiki/Colossal_Cave_Adventure)

You'll write two programs that will introduce you to programming in C on UNIX based systems, and will get you familiar with reading and writing files.

Overview

This assignment is split up into two C programs (no other languages is allowed). The first program (hereafter called the "rooms program") will be contained in a file named "<STUDENT ONID USERNAME>.buildrooms.c", which when compiled with the same name (minus the extension) and run creates a series of files that hold descriptions of the in-game rooms and how the rooms are connected.

The second program (hereafter called the "game") will be called "<STUDENT ONID USERNAME>.adventure.c" and when compiled with the same name (minus the extension) and run provides an interface for playing the game using the most recently generated rooms.

In the game, the player will begin in the "starting room" and will win the game automatically upon entering the "ending room", which causes the game to exit, displaying the path taken by the player.

During the game, the player can also enter a command that returns the current time - this functionality utilizes mutexes and multithreading.

For this assignment, do not use the C99 standard: this should be done using raw C (which is C89). In the complete example and grading instructions below, note the absence of the -c99 compilation flag.

Specifications

Rooms Program

The first thing your rooms program must do is create a directory called "<YOUR STUDENT ONID USERNAME>.rooms.<PROCESS ID OF ROOMS PROGRAM>". Next, it must generate 7 different room files, which will contain one room per file, in the directory just created. You may use any filenames you want for these 7 room files, and these names should be hard-coded into your program. For example, if John Smith was writing the program, he might see this directory and filenames. Note that 19903 was the PID of the rooms program at the time it was executed, and was not hard-coded:

```
$ ls smithj.rooms.19903
Crowther_room Dungeon_room PLUGH_room PLOVER_room twisty_room XYZZY_room Zork_room
```

The elements that make up an actual room defined inside a room file are listed below, along with some additional specifications:

- **A Room Name**

- A room name cannot be assigned to more than one room.
- Each name can be at max 8 characters long, with only uppercase and lowercase letters allowed (thus, no numbers, special characters, or spaces). This restriction is not extended to the room file's filename.
- You must hard code a list of ten different Room Names into your rooms program and have your rooms program randomly assign one of these to each room generated. Thus, for a given run of your rooms program, 7 of the 10 hard-coded room names will be used.

- **A Room Type**

- The possible room type entries are: START_ROOM, END_ROOM, and MID_ROOM.
- The assignment of which room gets which type should be randomly generated each time the rooms program is run.
- Naturally, only one room should be assigned the START_ROOM type, and only one room should be assigned the END_ROOM type. The rest of the rooms will receive the MID_ROOM type.

- **Outbound connections** to other rooms

- There must be at least 3 outbound connections and at most 6 outbound connections from this room to other rooms.
- The outbound connections from one room to other rooms should be assigned randomly each time the rooms program is run.
- Outbound connections must have matching connections coming back: if room A connects to room B, then room B must have a connection back to room A. Because of all of these specs, there will always be at least one path through.
- A room cannot have an outbound connection that points to itself.
- A room cannot have more than one outbound connection to the same room.

Each file that stores a room must have exactly this format, where the ... is additional outbound room connections, as randomly generated:

```
ROOM NAME: <room name>
CONNECTION 1: <room name>
...
ROOM TYPE: <room type>
```

Here are the contents of files representing three *sample* rooms from a full set of room files (remember, you must use this same format). My list of room names includes the following, among others: XYZZY, PLUGH, PLOVER, twisty, Zork, Crowther, and Dungeon.

```
ROOM NAME: XYZZY
CONNECTION 1: PLOVER
CONNECTION 2: Dungeon
CONNECTION 3: twisty
ROOM TYPE: START_ROOM
```

```
ROOM NAME: twisty
CONNECTION 1: PLOVER
CONNECTION 2: XYZZY
CONNECTION 3: Dungeon
CONNECTION 4: PLUGH
ROOM TYPE: MID_ROOM

... (Other rooms) ...
```

```
ROOM NAME: Dungeon
CONNECTION 1: twisty
CONNECTION 2: PLOVER
CONNECTION 3: XYZZY
CONNECTION 4: PLUGH
CONNECTION 5: Crowther
CONNECTION 6: Zork
ROOM TYPE: END_ROOM
```

The ordering of the connections from a room to the other rooms, in the file, does not matter. Note that the randomization you do here to define the layout is not all that important: just make sure the connections between rooms, the room names themselves and which room is which type, is somewhat different each time the rooms program is run, however you want to do that. We're not evaluating your randomization procedure, though it's not acceptable to just randomize the room names yet use the same room structure every time.

I highly recommend building up the room graph in this manner: adding outbound connections two at a time (forwards and backwards), to randomly chosen room endpoints, until the map of all the rooms satisfies the requirements listed above. It's easy, requires no backtracking, and tends to generate sparser layouts. As a warning, the alternate method of choosing the number of connections *beforehand* that each room will have is *not recommended*, as it's hard to make those chosen numbers match the constraints of the map. To help do this correctly, please read the article [2.2 Program Outlining in Program 2](#) and consider using the room-generating pseudo-code listed there!

Here is an example of the rooms program being compiled and then run. Note that it returns NO OUTPUT, unless there is an error:

```
$ gcc -o smithj.buildrooms smithj.buildrooms.c
$ smithj.buildrooms
$
```

The Game

Now let's describe what should be presented to the player in the game. Once the rooms program has been run, which generates the room files, the game program can then be run. This program should present an interface to the player. Note that the room data must be read back into the program from the previously-generated room files, for use by the game. Since the rooms program may have been run multiple times before executing the game, your game should use the most recently created files: perform a `stat()` [function call](#) (<https://linux.die.net/man/2/stat>) on rooms directories in the same directory as the game, and open the one with most recent `st_mtime` component of the returned `stat` struct.

This player interface should list where the player current is, and list the possible connections that can be followed. It should also then have a prompt. Here is the form that must be used:

```
CURRENT LOCATION: XYZZY
POSSIBLE CONNECTIONS: PLOVER, Dungeon, twisty.
WHERE TO? >
```

The cursor should be placed just after the > sign. Note the punctuation used: colons on the first two lines, commas on the second line, and the period on the second line. All are required.

When the user types in the exact name of a connection to another room (Dungeon, for example), and then hits return, your program should write a new line, and then continue running as before. For example, if I typed twisty above, here is what the output should look like:

```
CURRENT LOCATION: XYZZY
POSSIBLE CONNECTIONS: PLOVER, Dungeon, twisty.
WHERE TO? >twisty

CURRENT LOCATION: twisty
POSSIBLE CONNECTIONS: PLOVER, XYZZY, Dungeon, PLUGH.
WHERE TO? >
```

If the user types anything but a valid room name from this location (case matters!), the game should return an error line that says “HUH? I DON’T UNDERSTAND THAT ROOM. TRY AGAIN.”, and repeat the current location and prompt, as follows:

```
CURRENT LOCATION: XYZZY
POSSIBLE CONNECTIONS: PLOVER, Dungeon, twisty.
WHERE TO? >Twisty

HUH? I DON’T UNDERSTAND THAT ROOM. TRY AGAIN.

CURRENT LOCATION: XYZZY
POSSIBLE CONNECTIONS: PLOVER, Dungeon, twisty.
WHERE TO? >
```

Trying to go to an incorrect location does not increment the path history or the step count. Once the user has reached the End Room, the game should indicate that it has been reached. It should also print out the path the user has taken to get there (this path should *not* include the start room), the number of steps taken (*not* the number of rooms visited, which would be one higher because of the start room), a congratulatory message, and then exit.

Note the punctuation used in the complete example below: we're looking for the same punctuation in your program.

When your program exits, set the exit status code to 0, and leave the rooms directory in place, so that it can be examined.

If you need to use temporary files (you probably won't), place them in the directory you create, above. Do not leave any behind once your program is finished. We will not test for early termination of your program, so you don’t need to watch for those signals.

Time Keeping

Your game program must also be able to return the current time of day by utilizing a second thread and mutex(es). I recommend you complete all other portions of this assignment first, then add this mutex-based timekeeping component last of all. Use the classic pthread library for this simple multithreading, which will require you to use the "-lpthread" compile option switch with gcc (see below for compilation example).

When the player types in the command "time" at the prompt, and hits enter, a second thread must write the current time in the format shown below (use `strftime()` [_\(https://linux.die.net/man/3/strftime\)_](https://linux.die.net/man/3/strftime) for the formatting) to a file called "currentTime.txt", which should be located in the same directory as the game (your adventure file). The main thread will then read this time value from the file and print it out to the user, with the next prompt on the next line. Additional writes to the "currentTime.txt" file should overwrite any existing contents. I recommend you keep the second thread running during the execution of the main program, and merely wake it up as needed via this "time" command. In any event, at least one mutex must be used to control execution between these two threads.

To help you know if you're using it right, remember these key points about mutexes:

- They're only useful if ...lock() is being called in multiple threads (i.e. having the only ...lock() and ...unlock() calls occur in one thread isn't using the mutex for control).
- Mutexes allow threads to jockey for contention by having multiple locks (attempt to be) established.
- A thread can be told to wait for another to complete with the ...join() function, resuming execution when the other thread finally terminates.

Using the time command does not increment the path history or the step count. Do not delete the currentTime.txt file after your program completes - it will be examined by the grading TA.

Here is an example of the "time" command being run in-game:

```
CURRENT LOCATION: XYZZY
POSSIBLE CONNECTIONS: PLOVER, Dungeon, twisty.
WHERE TO? >time

1:03pm, Tuesday, September 13, 2016

WHERE TO? >
```

Complete Example

Here is a complete example of the game being compiled and run, including the building of the rooms. Note the time command, incorrect spelling of a room name, the winning messages and formatting, and the return to the prompt with some examination commands following:

```
$ gcc -o smithj.buildrooms smithj.buildrooms.c
$ smithj.buildrooms
$ gcc -o smithj.adventure smithj.adventure.c -lpthread
$ smithj.adventure
CURRENT LOCATION: XYZZY
POSSIBLE CONNECTIONS: PLOVER, Dungeon, twisty.
WHERE TO? >Twisty

HUH? I DON'T UNDERSTAND THAT ROOM. TRY AGAIN.

CURRENT LOCATION: XYZZY
POSSIBLE CONNECTIONS: PLOVER, Dungeon, twisty.
```

WHERE TO? >time

1:03pm, Tuesday, September 13, 2016

WHERE TO? >twisty

CURRENT LOCATION: twisty

POSSIBLE CONNECTIONS: PLOVER, XYZZY, Dungeon, PLUGH.

WHERE TO? >Dungeon

YOU HAVE FOUND THE END ROOM. CONGRATULATIONS!

YOU TOOK 2 STEPS. YOUR PATH TO VICTORY WAS:

twisty

Dungeon

\$ echo \$?

0

\$ ls

currentTime.txt smithj.adventure smithj.adventure.c smithj.buildrooms

smithj.buildrooms.c smithj.rooms.19903

\$ ls smithj.rooms.19903

Crowther_room Dungeon_room PLUGH_room PLOVER_room

twisty_room XYZZY_room Zork_room

\$ cat smithj.rooms.19903/XYZZY_room

ROOM NAME: XYZZY

CONNECTION 1: PLOVER

CONNECTION 2: Dungeon

CONNECTION 3: twisty

ROOM TYPE: START_ROOM

Hints

- You'll need to figure out how to get C to read input from the keyboard, and pause until input is received. I recommend you use the `getline()` function as described in the lectures. You'll also get the chance to become proficient reading and writing files. You may use either the older `open()`, `close()`, `lseek()` method of manipulating files, or the `STDIO` standard input library methods that use `fopen()`, `fclose()`, and `fseek()`.
- Remember that you cannot copy a string with the assignment operator (`=`) in C! You'll need to copy strings around using a member of the `strcpy()` family. Don't confuse string pointers with the character data itself.
- For the timekeeping requirement, consider the following. Perhaps the *main* thread at its beginning locks a mutex, then spawns a *second* thread whose first action is to attempt to gain control of the mutex by calling `...lock()`, which blocks itself. How is the second thread started up again, when the user types "time"? By the first thread calling `...unlock()`. You can keep the first thread blocked while the second thread runs by calling `...join()` in the first thread. Remember to relock the mutex in the main thread when it starts running again and then re-create the second thread.
- I HIGHLY recommend that you develop this program directly on our class server (see our [home page](#)). Doing so will prevent you from having problems transferring the program back and forth, which can cause compatibility issues.

If you do see ^M characters all over your files, try this command:

```
$ dos2unix bustedFile
```

What to Turn In and When

What you'll submit is a .zip file that contains both of your correctly named programs, which compile according to the instructions given above. As our Syllabus says, please be aware that neither the Instructor nor the TA(s) are alerted to comments added to the text boxes in Canvas that are alongside your assignment submissions, and they may not be seen. No notifications (email or otherwise) are sent out when these comments are added, so we aren't aware that you have added content! If you need to make a meta-comment about this assignment, please include it in a README file in your .zip file, or email the person directly who will be grading it (see the [Home](#) page for grading responsibilities).

The due date given below is the last minute that this can be turned in for full credit. The "available until" date is NOT the due date, but instead closes off submissions for this assignment automatically once 48 hours past the due date has been reached, in accordance with our [Syllabus Grading policies](#).

Grading

Remember that if your programs don't compile or run on our class server, you may receive a zero for the grade.

144 points are available for meeting all of the listed specifications, while the final 16 points will be based on your style, readability, and commenting. Comment well, often, and verbosely, approximately every four or five lines or so, as appropriate: we want to see that you are telling us WHY you are doing things, in addition to telling us WHAT you are doing.

The TAs will use this set of instructions: [Program2 Grading.pdf](#)  to grade your submission.

Program 2 - Adventure Rubric

Criteria	Ratings			Pts
<p>Rooms Files</p> <p>3 points for each correct room/file.</p> <p>Room files should match this format:</p> <p>ROOM NAME: <room name></p> <p>CONNECTION 1: <room name></p> <p>...</p> <p>ROOM TYPE: <room type></p>	<p>21 to >0.0 pts</p> <p>Full Marks</p>		<p>0 pts</p> <p>No Marks</p>	21 pts
<p>Location Header</p> <p>The location header should match this format:</p> <p>CURRENT LOCATION: <current location></p>	<p>10 pts</p> <p>Formatting matches exactly</p>	<p>5 pts</p> <p>Formatting is close</p>	<p>0 pts</p> <p>No Marks</p>	10 pts
<p>Connection List</p> <p>The connection list should match this format exactly, including commas and period:</p> <p>POSSIBLE CONNECTIONS: <connection to room 1>, <connect 2>, ... , <connect n>.</p>	<p>12 pts</p> <p>Formatting matches exactly</p>	<p>6 pts</p> <p>Formatting is close</p>	<p>0 pts</p> <p>No Marks</p>	12 pts
<p>Prompt Line</p> <p>The prompt line should match this format exactly. The cursor should be immediately after the > symbol.</p>	<p>5 pts</p> <p>Formatting matches exactly</p>	<p>2.5 pts</p> <p>Formatting is close</p>	<p>0 pts</p> <p>No Marks</p>	5 pts
<p>New Prompt</p> <p>Traveling to a new room should produce a new prompt that matches that room, including connections. There is no partial credit on this criteria.</p>	<p>15 pts</p> <p>Full Marks</p>		<p>0 pts</p> <p>No Marks</p>	15 pts
<p>Room NOT in game</p> <p>Traveling to a room that is not in the game OR not connected to the current room should print some sort of message indicating that the room could not be reached or is invalid.</p>	<p>0 pts</p> <p>Error Message</p>	<p>-8 pts</p> <p>Crashes/No Message</p>		0 pts
<p>Adventure exit value - echo \$?</p> <p>When the adventure program exits normally (i.e. the game is won), it should have an exit value of 0.</p> <p>Typing the command `echo \$?` immediately after winning the game should print "0".</p>	<p>10 pts</p> <p>Full Marks</p>		<p>0 pts</p> <p>No Marks</p>	10 pts
<p># of Steps</p> <p>When the end room is reached, the game should print the number of steps taken. This value should be the final step.</p>	<p>10 pts</p> <p>Full Marks</p>	<p>5 pts</p> <p>Includes Start Room</p>	<p>0 pts</p> <p>No Marks</p>	10 pts

Criteria	Ratings			Pts
<p>List of Steps</p> <p>When the end room is reached the game should print the path taken. If a room was visited twice, then it should appear on this list twice. This list should NOT include the start room. It should include the end room.</p>	15 pts Full Marks	8 pts Includes Start Room	0 pts No Marks	15 pts
Crashes or No Win	0 pts Does not Crash		-15 pts Crashes	0 pts
<p>Different Path to Victory (run #2)</p> <p>The rooms generated by buildrooms should be random and the adventure program should be able to run multiple times.</p> <p>Running buildrooms and adventure again should result in a different path to victory.</p>	10 pts Full Marks	0 pts No Marks		10 pts
<p>Different PID (run #2)</p> <p>The buildrooms program should create a new directory each time it is ran. This directory should include the PID in its name.</p>	5 pts Full Marks	0 pts No Marks		5 pts
<p>Different Path to Victory (run #3)</p> <p>Again, each run of buildrooms should create a new directory and adventure should be using the newest created directory. Running both programs again should have a different path to victory.</p>	5 pts Full Marks	0 pts No Marks		5 pts
<p>Display Date and Time</p> <p>The adventure program should accept "time" as a command. This command should display the current date and time in this format: 1:03pm, Tuesday, September 13, 2016 Single digit hours are preceded by a blank.</p>	10 pts Formatting matches exactly.	5 pts Format Wrong	0 pts No Marks	10 pts
<p>Mutex and Timekeeping Thread</p> <p>The <username>.adventure.c code should properly utilize mutexes. This means there should be two sections that use the same mutex, one for the main thread and one for the time thread.</p>	10 pts Full Marks	0 pts No Marks		10 pts
<p>currentTime.txt</p> <p>When the user inputs the "time" command, a file containing the time should be created. This file should be named "currentTime.txt" and should be located in the game directory, not one of the directories that contain the room files.</p>	6 pts Full Marks	4 pts Format is wrong or file is in the wrong directory	0 pts No Marks	6 pts

Criteria	Ratings		Pts
<p>Commented Code</p> <p>We expect comments roughly every 3-4 lines that describe what you're doing as well as why you're doing it. Your code should also be presented in a readable style.</p> <p>Your script should also clean up any temp files should you choose to use them. -1 for each temp file left behind, to a maximum (minimum?) of -5.</p>	<p>16 to >0.0 pts</p> <p>Full Marks</p>	<p>0 pts</p> <p>No Marks</p>	16 pts
Resubmit	<p>0 pts</p> <p>No Penalty</p>	<p>-8 pts</p> <p>Penalty</p>	0 pts
Total Points: 160			