24/09/2026
Thursday

Name :- Trupti Vasant Gaikwad.

Page No.
Date

49/50

Test 1

section A

1) what is data ?
→ data is collection of raw facts, values or information that can be stored & processed. (1)

2) what is database ?
→ database is organize collection of data that can be stored, accessed, managed & update efficiently. (1)

3) what does DBMS stands for ?
→ DBMS stands for DataBase Management system. is a Software. (1)

4) what does RDBMS stands for ?
→ RDBMS stands for Relational Database Management System is type of DBMS (1)

5) what is MySQL ?
→ MySQL is open source relational database mgt system that uses SQL to create, manipulate & manage relational database. (1)

6) what is SQL ?
→ SQL is language is used to communicate with relational database. (1)

7) Name any two database models.
→ 1) Hierarchical Database Model.
2) Network Database Model. (1)

8) what is row in database table ?
→ row is record in database table. It contain information one particular information store. row is Horizontaly. (1)

9) What is the purpose of the DISTINCT keyword

→ It will return unique value. (1)

10) What does the % wildcard represent in MySQL LIKE?

→ % → Percentage symbol → zero, one, or multiple characters. (1)

Section B :- 11) difference between Database & DBMS

→ Database.	DBMS.
1) Database is organize collection of Data.	DBMS is software that can store, retrieve, update manage data.
2) eg: student database	2) eg: MySQL, oracle.
3) Stores data.	3) It is create, update, retrieve. (2)

12) difference between SQL & MySQL.

→	SQL	MySQL.
1)	SQL is query language	MySQL is DBMS.
2)	SQL not database software	MySQL is database s/w.
3)	SQL is used communicate with relational database	MySQL is open source relational database. (2)

13) write any four SQL command categories & give one command for each.

→ DDL → create
DML → insert
DQL → select
DCL → Grant. (2)

14). what is difference between In & Between

→ IN is used to multiple value matches any value on table.
Between: It is used to select value for specified range. (2)

15). explain Is Null & is NoT Null with suitable sql example.

→ Is Null: find record & colums has no value
Is NoT Null: find record & columns value is Present. (2)

eg: select * from student
where city is Null;

eg: select * from student
where city is Not Null;

Section c: 16). Explain DBMS & RDBMS write at leat three difference between them.

→

DBMS.	RDBMS.
1). DBMS is not stored data in related tables.	RDBMS data is stored in related tables
2) DBMS stands for Database Management system.	RDBMS stands for Relational Database Management System
3). DBMS is a software that can store, retrieve & update data.	RDBMS is type of DBMS that allows user applicatio

(4) (5)

17). Explain following database model with their basic structure. (1)

→ 1) Hierarchical Database → Tree like structu

college

Student Teacher

college

Student Teacher

2) Network database: Interconnected records graph-like structure (1)

3) relational database: tables format (row & column) (1)

4) object-oriented database: It is stores object. (1)

5) NoSQL database: It is stored key-value / Documen column family & Graph. (1)

~~18)~~

18) Explain the six MySQL constraints given in the notes. write Purpose of each.

1) Not Null: column can not null.
2) unique: values are different.
3) Default: automatically assign value.
4) check: data specified condition.
5) Foreign key: create relationship bet two tables.
6) Primary key: value is unique & not null & not duplicate value. (5)

19) a) display student whose age 20.

→ select * from student
where age = 20;

(1)

o/p:

id	name	age	gender	city
1	Rahul	20	Male	Delhi
6	Anjali	20	female	jaipur

b) display student whose age is between 20 & 23.

→ select * from student
where age between 20 and 23;

(1)

o/p:

id	name	age	gender	city
1	Rahul	20	Male	Delhi
2)	Priya	21	female	Mumba
3	Amit	22	Male	Patna

5	Rohit	23	Male	Pune
6.	Anjali	20	Female	jaipur
7.	Pooja	21	Female	kolkata.

c) display student from Delhi or Mumbai; using IN.

→
```
select * from student.
where city In ("Delhi", "Mumbai");
```

O/P:

id	name	age	gender	city
1	Rahul	20	Male	Delhi
2	Priya	21	Female	Mumbai
8	Manish	25	Male	Delhi

d) display only female Student:

→
```
Select * from student
where gender ==="female";
```

O/P:

id	name	age	gender	city
2.	Priya.	21	Female	Mumbai
4	Neha.	19	female	Gaya
6	Anjali	20	female	Jaipur
7	Pooja.	21	female	kolkata

e) display student whose name start with P.

→
```
select * from student.
where name like "p%";
```

O/P:

id	name	age	gender	city
2	Priya	21	female	Mumbai
7	Pooja	21	female	Kolkata

PAGE No.
DATE / /

Q.20 explain the mysql like operator & its wildcards % & _ write SQL queries.

a) Names starting with A.

→ select * from student
where name like "A%";

O/P:

id	name	age	gender	city
3	Amit	22	Male	Patna
6	Anjali	20	female	jaipur

b) Names ending with a.

→ select * from student
where name like "%a";

O/P:

id	name	age	gender	city
2	Priya	21	female	Mumbai
4	Neha	19	female	Gaya
7	Pooja	21	female	kolkata.

c) Names containing am.

→ select * from student
where name like "%am%";

O/P:

id	name	age	gender	city
3	Amit	22	Male	Patna

d) Names having a as the second characters

→ select * from student
where name like "_a%";

O/P:

id	Name	age	gender	city
1	Rahul	20	Male	Delhi
8	Manish	25	Male	Delhi

e) →

Q.21

e) Names having o as third character.

→ select * from student
where name like "__o%";

o/p:

id	name	age	gender	city
7	Pooja	21	female	kolkata

(1)

q.21) explain following MySql concepts with syntax & eg.

1) a) Distinct: It will return unique value

syntax: select column name, ~~column~~
from table name;

eg: select age
from student; (1)

b) LIMIT:

syntax:- select * from ~~Column name~~ table name.
Limit 5; ~~e~~ (X)

eg: select * from student
Limit 5; (1) (0.5)

d) Count(): ~~It~~ It will return the count the record

Syntax: ~~select~~ count (~~age~~ column name);

eg: count (age); (1)

e) ~~eg~~: SUM(): It will return the sum of ~~th~~ column name.

Syntax: sum (column-name); (1)

eg: sum (age);

DATE / /

c) Limit & offset ;

eg: ~~slect~~ select * from student
where age >= 20 and age <= 25
Limit 5 ;

0.5

syntax: select * from table-name
where condition.
Limit 5;

