

11/05/26
Thursday

Test assessment - I.

(Ans: 1) S = "Hello ^{world} string"print(reverse(s))S.reverse()Output: ~~dlrow~~

(Ans: 2) S = "A Quick Brown Fox Jump Over the Lazy Dog"

print(len(s))

Output: 9

(1)

(Ans: 3) S = "Carrot"

(Ans: 4) The following is the diff betⁿ list & sets.

List	Sets
1. List are <u>ordered</u>	Sets are <u>unordered</u>
2. <u>List uses []</u>	<u>Sets uses {}</u>
3. Indexing <u>possible</u>	In set indexing is <u>not possible</u> . (1)

(Ans: 5) No sets can't ~~can't~~ contains list cause - lists are mutable. while sets elements are immutable. (1)

unhashing.

↓ Keys are immutable

(Ans: 6) Sets use hashing (immutable method) which allows sets to work faster in every way such as searching, insertion, deleting etc.

(Ans: 7)

remove()

In removing method the element is temp remove from the required data

remove() → when use

remove method() if element is not found it throws an

error.

discard()

In discard the data is completely ~~cleared~~. It can't be replayed once deleted.

→ It can't throw any error if element not found in discard() method.

(Ans: 8) The following represent the total number of methods of list ~~and~~

- (a) append() ✓
(b) insert() ✓
(c) extend() ✓

①

This are the three methods to insert an element into the list

(Ans: 9) The following are methods to delete an ~~element~~ element from the list. There are 5 types:

(1) remove() —

(2) pop(n) —

(3) pop() ✓

(4) Clear() —

(5) del() —

①

8:00

Page No.

DOMS

Date

14
20

(Ans:10) The following are the Operators in python with their name in explain.

- (1) Arithmetic Operators (+, -, *, /, //, %)
- (2) Comparison operators (==, !=, >, <, >=, <=)
- (3) Assignment operator (=)
- (4) Logical operators (or, and, not)
- (5) membership (in, in not)
- (6) Identity

(Ans:11) The precedence rule of arithmetic in python are:

Highest - $() \rightarrow \neg \rightarrow \star \star, /, \star$

lowest - +, -

(Ans:12) list [5, 11, 14, 7, 8, 3, 2, 5, 9]
list.sort()
print(list)

output: [2, 3, 5, 5, 7, 8, 9, 11, 14]

(Ans:13) A Dictionary is a collection of key-values in a pair for example:
Student { "name": "Gayatri", "age": 20 }

1 pair

2 pair

(Ans:14) There are three types of ways/methods to create a dictionary

1. `{ }` : when we write a code inside it
2. `dict()` ✓
3. `{ }` : empty dictionary

(Ans: 15) There are

(1) By using a key.
for ex: `student = {"name": "gg"}`
Here the key is "name".

(2) `get()` : This is the safer method to access value of the dictionary if value not found or missing it doesn't give an error.

(Ans: 16) There are 4 types of methods to delete an element from a dictionary.

`x = { }`

1. `pop()` ✓
2. `popitem()` ✓
3. `clear()` ✓
4. `del()` ✓

(Ans: 17) So ~~to~~
`remove()`

(Ans: 18) Packing variables in tuple means storing multiple values into one tuple for example:

~~t =~~ t = (10, 20, 30)

①

(Ans: 19) Unpacking variables in tuple means assigning tuple values to a separate variable for example:

t = (10, 20, 30)

a b c = t
print (a)
print (b)
print (c)

①

10
20
30

(Ans: 20) The following represents the difference between a set and dictionary.