```
import pandas as pd
```

```
df=pd.read_csv('/content/covid_toy.csv')
df.head()
```

Show hidden output

Next steps: Generate code with df New interactive sheet

```
df.tail()
```

Show hidden output

```
df.shape
```

```
(100, 6)
```

```
df.sample(3)
```

Show hidden output

```
df.columns
```

```
Index(['age', 'gender', 'fever', 'cough', 'city', 'has_covid'],
dtype='object')
```

```
df.dtypes
```

Show hidden output

```
df.info()
```

Show hidden output

```
df.head(2)
```

Show hidden output

Next steps: Generate code with df New interactive sheet

```
categorical_df=df.select_dtypes(include=['category','object'])
categorical_df.columns.tolist()
```

```
['gender', 'cough', 'city', 'has_covid']
```

```
int_df=df.select_dtypes(include=['category','int'])
int_df.columns.tolist()
```

```
['age']
```

```
df_int=df.select_dtypes(include='int')
df_int.columns.tolist()
```

```
['age']
```

```
df.head(2)
```

```
   age  gender  fever  cough     city  has_covid
0   60    Male  103.0   Mild  Kolkata         No
1   27    Male  100.0   Mild    Delhi        Yes
```

Next steps: Generate code with df New interactive sheet

```
df.isnull().sum()
```

Show hidden output

```
df['fever']=df['fever'].fillna(df['fever'].mean)
```

```
df.isnull().sum()
```

```
           0
      age  0
   gender  0
    fever  0
    cough  0
     city  0
has_covid  0

dtype: int64
```

```
df['fever'].mean()
```

```
---------------------------------------------------------------------------
TypeError                                 Traceback (most recent call last)
/tmp/ipykernel_677/2399110436.py in <cell line: 0>()
----> 1 df['fever'].mean()
```

7 frames

```
/usr/local/lib/python3.13/dist-packages/numpy/_core/_methods.py in _sum(a,
axis, dtype, out, keepdims, initial, where)
     51 def _sum(a, axis=None, dtype=None, out=None, keepdims=False,
     52          initial=_NoValue, where=True):
---> 53     return umr_sum(a, axis, dtype, out, keepdims, initial, where)
     54 
     55 def _prod(a, axis=None, dtype=None, out=None, keepdims=False,

TypeError: unsupported operand type(s) for +: 'float' and 'method'
```

Next steps: Explain error

```
#uppar df['fever'] mai type error mtlab koi value num na hoke string mai thi
# to solution==> current or next cell mai

print(df['fever'].dtype)
print(df['fever'].head(10))
```

```
float64
0    103.0
1    100.0
2    101.0
3     98.0
4    101.0
5      NaN
6    101.0
7      NaN
8    100.0
9    101.0
Name: fever, dtype: float64
```

```
df['fever'] = pd.to_numeric(df['fever'], errors='coerce')
df['fever'].mean()
```

```
np.float64(100.84444444444445)
```

```
df.head(2)
```

Show hidden output

Next steps: Generate code with `df` New interactive sheet

```python
df['gender'].value_counts()
```

```
        count
gender
Female     59
  Male     41

dtype: int64
```

```python
df['cough'].value_counts()
```

```
        count
 cough
  Mild     62
Strong     38

dtype: int64
```

```
Start coding or generate with AI.
```

```
Start coding or generate with AI.
```