Practical No 05

a) Create Web Form to demonstrate use of Website Navigation controls.

GUI:

```
HOME

Home

Home

SiteMapDataSource - SiteMapDataSource1
```

Web.sitemap

```
<?xml version="1.0" encoding="utf-8" ?>
<siteMap xmlns="http://schemas.microsoft.com/AspNet/SiteMap-File-1.0" >
    <siteMapNode url="Home.aspx" title="Home" description="Home page of our web site">
        <siteMapNode url="Contactus.aspx" title="Contactus" description="Contactus" />
        <siteMapNode url="Search.aspx" title="Search" description="Search" />
        </siteMapNode>
</siteMap>
```

Program Code:

Home.aspx

SiteMapPath→ AutoFormat

Home (MENU) -> Choose Data Source and Select DataSource1

SiteMapDataSource->Refresh Schema

```
<%@ Page Language="C#" AutoEventWireup="true" CodeBehind="Home.aspx.cs"
Inherits="P5A.WebForm1" %>
<!DOCTYPE html>
<html xmlns="http://www.w3.org/1999/xhtml">
<head runat="server">
        <title></title>
</head>
<body>
```

```
<form id="form1" runat="server">
    <div>
      <br />
      <br />
      <asp:Label ID="Label1" runat="server" Text="HOME"></asp:Label>
      <br />
      <br />
      <br />
      <asp:SiteMapPath ID="SiteMapPath1" runat="server" Font-Names="Verdana" Font-
Size="0.8em" PathSeparator=":">
        <CurrentNodeStyle ForeColor="#333333" />
        <NodeStyle Font-Bold="True" ForeColor="#990000" />
        <PathSeparatorStyle Font-Bold="True" ForeColor="#990000" />
        <RootNodeStyle Font-Bold="True" ForeColor="#FF8000" />
      </asp:SiteMapPath>
      <br />
      <br />
      <asp:Menu ID="Menu1" runat="server" DataSourceID="SiteMapDataSource1">
      </asp:Menu>
      <br />
      <br />
      <asp:SiteMapDataSource ID="SiteMapDataSource1" runat="server" />
    </div>
  </form>
</body>
</html>
```

Create **Contactus.aspx and Search.aspx** and add **SiteMapPath** to both pages **Contactus.aspx**

GUI:



Search.aspx


GUI:

```
| body |
| SEARCH |
| Home : Search |
```

```
<%@ Page Language="C#" AutoEventWireup="true" CodeBehind="Search.aspx.cs"</pre>
Inherits="prac5 a.WebForm3" %>
<!DOCTYPE html>
<html xmlns="http://www.w3.org/1999/xhtml">
<head runat="server">
    <title></title>
</head>
<body>
    <form id="form1" runat="server">
            <asp:Label ID="Label1" runat="server" Text="SEARCH"></asp:Label>
            <br />
            <br />
            <asp:SiteMapPath ID="SiteMapPath1" runat="server" Font-Names="Verdana" Font-</pre>
Size="0.8em" PathSeparator=" : ">
                <CurrentNodeStyle ForeColor="#333333" />
                <NodeStyle Font-Bold="True" ForeColor="#7C6F57" />
                <PathSeparatorStyle Font-Bold="True" ForeColor="#5D7B9D" />
                <RootNodeStyle Font-Bold="True" ForeColor="#5D7B9D" />
            </asp:SiteMapPath>
        </div>
```

```
</form>
</body>
</html>
```

Output:



b) Create a web application to demonstrate use of Master Page and content page.

GUI:

\mathbf{W}	EIC	C()	N	1	ŀ	C	 	 	 	 	 	 	 ••••
to														
AWP														


Program Code:

Master page:

```
<%@ Master Language="C#" AutoEventWireup="true" CodeBehind="Site1.master.cs"</pre>
Inherits="prac5_b.Site1" %>
<!DOCTYPE html>
<html>
<head runat="server">
    <title></title>
    <asp:ContentPlaceHolder ID="head" runat="server">
    </asp:ContentPlaceHolder>
</head>
<body>
    <form id="form1" runat="server">
        <div>
              <h1>WElCOME</h1>
             <h2>to</h2>
             <asp:ContentPlaceHolder ID="ContentPlaceHolder1" runat="server">
             </asp:ContentPlaceHolder>
             \langle h4 \rangle AWP\langle /h4 \rangle
        </div>
    </form>
</body>
</html>
```

Content Page:

Output:



WEICOME

to

This is content page.

AWP

c) Create a web application to demonstrate various states of ASP.NET Pages.
GUI:
Program Code:
Output: