papergrid

Date: / /

Programming

It is a process of giving instruction to the computer to perform specific task

Three levels of Programming

i. Binary level - 0 & 1
ii. Mid / Assembly level
iii. high level programming - C, C++, python, java

Python

The developer of python programming is Guido Rossum.

It is high level programming, interpreted, object oriented, indent programming language

Features

* Easy to learn
* free & opensource
* platform independent
* huge community support
* vast collection of libraries
* It supports all kind of programming method

Application

* web application
* gaming application
* desktop application
* data analytic
* data science
* AI
* Automation
* IOT

papergrid
Date: / /

Version of python
* python 1 - 1991 year
* python 2 - 2000 year
* python 3 - 2008 year

Comment
They are part of programming but they never part of execution. They used to understand the flow of programming or some critical logics.

Types of comment
i single line comment
ii multiline comment

Keywords
They are predefined words to perform a specific task.
Ex:- If, for, else, break.
These keywords are not used as identifiers.

Variables.
They are place holders which the holds any kind of values and they represented by variables names.

Rules of variable
1. Variables can be upperCase or lowerCase
2. it can be single alphbet or string or alphnumeric
3. we can use dual words as single variable but they should separated by _ (underscore)
4. They cant be start numbers
5 they cant use any speval char apart from _
6. we cant separate them by space.

papergrid

Date: / /

	valid variable declaration Invalid variable declar
1.	A = 10 1. shu phonenum = 631
2	a = 5 2. emp@name = 'sagar'
3	place = "bangalore" 3 1 num = 100
4.	she-name = 'sharmila'
5	num1 = 20
6	_shu_id = 6364
	Datatypes
	It represent the kind of data
	Single value datatype
i	Int
ii	Float
iii	boolean
iv	complex
v	string
	Multivalued datatype (inbuilt data structure)
i	list
ii	tuple
iii	set
iv	dict
v	string
	Operators
	It's special symbol perform certain operation between opera
	example :- add = n1 + n2
	operandds : n1, n2, add
	operators : +, =