

Assignment 04 – JavaScript Alerts and Confirms

1. Module Name

Module 1 – Automation with Selenium

2. Experiment Title

JavaScript Alerts and Confirms

3. Problem Statement

Automate JavaScript Alert, Confirm and Prompt dialogs. Accept the Alert, dismiss the Confirm dialog, enter text into the Prompt using `send_keys()`, accept it, and verify the resulting page text.

4. Objective

To learn how to handle JavaScript browser dialogs in Selenium, including accepting, dismissing, entering Prompt data and verifying results.

5. Tools, Software and Concepts Used

- Python 3.x
- Selenium WebDriver
- Google Chrome
- Visual Studio Code
- JavaScript Alert
- JavaScript Confirm
- JavaScript Prompt
- `alert.accept()`
- `alert.dismiss()`
- `alert.send_keys()`
- `WebDriverWait`
- `alert_is_present()`
- `assert` statement

6. Source Code / Implementation Steps

1. Open the JavaScript Alerts page.
2. Trigger and accept the JavaScript Alert.
3. Trigger and dismiss the JavaScript Confirm.
4. Trigger the JavaScript Prompt.
5. Enter Selenium Automation using `send_keys()`.
6. Accept the Prompt.

7. Verify the resulting page text.
8. Print the successful execution result and close the browser.

Source Code

```
from selenium import webdriver
from selenium.webdriver.common.by import By
from selenium.webdriver.support.ui import WebDriverWait
from selenium.webdriver.support import expected_conditions as EC

driver = webdriver.Chrome()

try:
    driver.get("https://the-internet.herokuapp.com/javascript_alerts")
    driver.maximize_window()

    print("JavaScript Alerts page opened.")

    driver.find_element(By.XPATH, "//button[text()='Click for JS Alert']").click()
    alert = WebDriverWait(driver, 10).until(EC.alert_is_present())
    alert.accept()
    print("JavaScript Alert accepted successfully.")

    driver.find_element(By.XPATH, "//button[text()='Click for JS Confirm']").click()
    confirm = WebDriverWait(driver, 10).until(EC.alert_is_present())
    confirm.dismiss()
    print("JavaScript Confirm dismissed successfully.")

    driver.find_element(By.XPATH, "//button[text()='Click for JS Prompt']").click()
    prompt = WebDriverWait(driver, 10).until(EC.alert_is_present())
    prompt.send_keys("Selenium Automation")
    prompt.accept()
    print("JavaScript Prompt accepted successfully.")

    result = WebDriverWait(driver, 10).until(
        EC.visibility_of_element_located((By.ID, "result"))
    )

    print("Prompt result:", result.text)
    assert result.text == "You entered: Selenium Automation"

    print("Alert, Confirm and Prompt verification successful.")
    print("Assignment 04 completed successfully.")

    input("Press ENTER to close the browser...")

finally:
    driver.quit()
```

7. Output / Labelled Screenshots

- Screenshot 1 – JavaScript Alert dialog
- Screenshot 2 – JavaScript Confirm dialog
- Screenshot 3 – JavaScript Prompt with entered text
- Screenshot 4 – Final page showing the Prompt result
- Screenshot 5 – VS Code terminal showing successful execution

Screenshots are stored in the Screenshots folder for this assignment.

8. Result

The JavaScript Alert was accepted, the Confirm dialog was dismissed, and text was entered and submitted through the Prompt. The resulting page text was successfully verified.

9. Observation

JavaScript dialogs are handled through Selenium's alert interface rather than normal HTML element locators. WebDriverWait with `alert_is_present()` provides reliable synchronization.

10. Conclusion

The experiment successfully demonstrated handling of JavaScript Alert, Confirm and Prompt dialogs in Selenium, together with synchronization and result verification.