

SafeSend

A poison-aware payment router for EVM.
Makes the address-poisoning paste cancellable.

3rd Web Hack – unaudited testnet prototype – Solidity · Foundry · React

no owner · no fees · no upgradeability · on-chain enforcement

01

Anyone can make your history lie

- Many wallets abbreviate addresses as `0x7099...79c8`; people may check only those visible edges.
- Attackers vanity-generate a **lookalike** matching those same edges of a real payee.
- They inject it into your history: a **zero-value transferFrom** (succeeds on USDT-style tokens with **no allowance**) plus a dust transfer.
- If you copy the lookalike as your "last counterparty" and send directly, the transfer has no built-in cancellation path.

02

A visible-address fingerprint, enforced on-chain

SafeSend computes $fp = first4 \ll 16 \mid last4$ of every recipient and routes accordingly:

Recipient	Routing
Verified payee	Instant transfer — no escrow
Unknown payee	Sender-cancellable escrow · recipient claims after cooldown
Fingerprint collides with a verified payee	24h quarantine + LookalikeFlagged · cancellable · claim needs sender's on-chain approval

03

The contract — routing and escrow

send(to, token, amount)

Verified → instant. Lookalike → 24h lock + flag. Unknown → escrow for sender's cooldown (60s–7d).

cancel(id) sender only, while pending → full refund
claim(id) recipient only, after unlock → pays out **and**
verifies — flagged escrows also need sender's
approveLookalike(id)

reclaim(id) after unlock + 30d — dead-letter recovery

addPayee / removePayee / setCooldown — the sender's own book. No owner. No admin. No fees.

OpenZeppelin SafeERC20 + ReentrancyGuard • checks-effects-interactions • no external dependencies

04

Watch the attack, then watch it fail

- **Attacker console** (Anvil only): pick a payee → generated lookalike → **poison** (zero-value transferFrom) + **dust** (impersonation).
- **History** flags both injected rows — the lookalike now "looks like" the real payee.
- Paste it into **Send** → **LOOKALIKE badge** → contract quarantines + emits the flag.
- **Pending** → cancel → full refund. Even after 24h, the lookalike can't claim — claim also requires the sender's approval.
- Same flow to the real payee → **instant**. New contact → escrow → they claim → **verified for later sends**.

05

Engineering rigor

- **58 Foundry tests:** unit, negative (NotRecipient / NotSender / Locked / TooEarly ...), event assertions.
- **Fuzz** (512 runs): random amounts, recipients, timings across every transition.
- **Invariants** (128 × depth 32): router solvency for ERC-20 + ETH; nextId monotonic; verified recipients can never sit in escrow.
- **100% line coverage** on SafeSend.sol · `forge fmt` clean · gas snapshot.
- UI mirrors the contract's fingerprint exactly — parity-tested against Solidity output.

Honest limitations

- **Detection, not prevention** — only protects sends routed through SafeSend; raw transfer() is untouched.
- **4-hex fingerprint** — a different visible-address pattern, such as first-six matching without the last four, can slip by.
- **addPayee trusts the sender** — out-of-band verification is the human's job; claim-to-verify is the safer path.
- **Unaudited prototype.** Prior art: REVERSO / ERC-20R (arbitrated reversals — we use a deterministic rule, no judges), Argent trusted contacts (ours self-grows from deliveries), explorer tags (off-chain — ours enforces on-chain).

07

Sender approval gates flagged payments

Copy-from-history is a UI habit. SafeSend places a lookalike paste in a 24-hour escrow. The recipient needs sender approval to claim; after claim, that full address is verified for future instant sends.

- Runs today: `make anvil && make deploy-local && make seed && make web`
- Base Sepolia deploy path included; attack tooling confined to local Anvil, labeled for education.
- Next: EIP-712 permit UX, wallet-level fingerprint warnings, broader collision sets.