

Summary of cutting data for Hole on solid material

Material details

AISI/SAE, 1045, Hardness: 207 HB, Material group:P1.2.Z.AN


Task details



Hole on solid material	
Applicability for through hole	Yes
Diameter	22 mm
Tolerance class	
Depth	8 mm
System stability	Excellent stability


Recommended solution

Machining	Type of cooling	Description	Grade	Tmf [min:s]		
Pocket milling	Dry	Perform	WJ30ED	00:10.080		





Cutting data



Legend





Working engagement (ae)	11 mm
Depth of cut (a _p)	4 mm
Number of passes in AE direction (NOPae)	1
Number of passes in AP direction (NOPap)	2
Start diameter (Dms)	22 mm
Effective ramping angle (RMPangle)	12 °
Cutting speed (vc)	169 m/min
Spindle speed (n)	3370 1/min
Feed per tooth (fz)	0.0815 mm
Feed speed at the contour (vfe)	824 mm/min
Feed speed in the tool centre (v _f)	225 mm/min
Cutting power (Pc)	1.18 kW
Cutting torque (Mc)	3.35 Nm
Maximum chip thickness (hex)	0.0815 mm
Material removal rate (Q)	9.89 cm3/min
Total cutting time (Tc tot)	00:10.080 min:s
Tool life length (LifeLength)	50.31 m
Tool life time (LifeTime)	61 min

DECLARATION OF EXCLUSION
The program is used at the user's own risk. Walter AG accepts no guarantee or warranty whatsoever for the suitability of the program or for its efficiency, especially the correctness of the calculations. Walter AG accepts no liability for the trouble- and fault-free use of the program. The risk is borne by the user
Liability of any kind on the part of Walter AG and its employees for damage, detriment and expenditure of any kind, particularly including financial and data losses amongst others, such as may arise for the user or third parties as a result of, or in connection with the use or non-applicability of the program, is ruled out. This exclusion of liability does not apply if and in so far as such damage, detriment and expenditure is found to be due to intentional or grossly negligent behaviour on the part of Walter AG employees.