



MODEL	SR195HDMI
Panel Type	19.5" (16:9) LED Backlit Monitor
Case Type	Plastic
Maximum Resolution	1920 x 1080
Active Display Area	432 (H) x 243 (V) mm
Pixel Pitch	0.27 (H) x 0.27 (V) mm
Bezel Thickness	18mm
Contrast Ratio	1000 : 1 Ratio
Brightness	250 cd/ m ²
Response Time	5m.sec (G to G)
Viewing Angle	U/D: 80° / 80°, L /R: 75° / 75°
Display Colours	16.7 M
Video Synchronization	Yes
PC Compatible Frequency	30-80KHz(H) / 50-75Hz(V)
Adjustable Colour Temperature	9300K / 6500K / 5800K / User
Video Compatibility	Multi-Standard for NTSC / PAL
Aspect Ratio	16 : 9 Ratio
VGA Auto Frequency correction	Yes
Speakers	Right x 1 Left x 1, 2.5W
Number of Speakers	x 2
Sound Demodulation	Stereo, Audio
Mute	Yes
Work Humidity	20 % – 70 %
Work Temperature	-10 to +50 °C
Volume +/- Power On/Off	Yes

MODEL SR195HDMI	
IN/OUT INTERFACE	
Video Interface	HDMI x1, DVI x1, VGA x 1
Audio Interface	Audio In x 1, Audio Out x 1
Power Interface	DC In x 1
Termination	75 Ohms (Automatic termination)
Stand Type	Desktop
Safety & EMC Certification	Energy Star / CE / FCC / ROHS /WEEE
Vesa Standard Mount	100 x 100mm
Colour	Black
Button Position	Right Hand Side, Front
Packing Dimension	520 x 409 x 96mm
NET Weight	12.8 Kgs
GROSS Weight	11.5 Kgs
POWER	
Power Supply	12VDC, 3 amp
Voltage	AC100 – 240V 50 / 60Hz
Power Consumption	< 23W in "ON"
OSD CONTROLS	
Contrast, Brightness, Colour, Gamma, Colour Temperature, OSD position, OSD timeout, OSD transparency, Language, Mute, DCR, Screen size (16:9/4:3)	
OSD LANGUAGE	
English, French, German, Spanish, Italian, Russian and Portuguese	
ACCESSORIES	
Power Supply / Kettle Lead / HDMI Cable/Audio Cable / User Manual / Remote Control	

