| MODEL | SR215HDMI |
|---|---|
| Panel Type | 21.5" (16:9) LED Backlit Monitor |
| Case Type | Plastic |
| Maximum Resolution | 1920 x 1080 |
| Active Display Area | 476.64 (H) x 268.11 (V) mm |
| Pixel Pitch | 0.248 (H) x 0.248 (V) mm |
| Bezel Thickness | 18mm |
| Contrast Ratio | 1000 : 1 Ratio |
| Brightness | 250 cd/ m$^2$ |
| Response Time | 5m.sec |
| Viewing Angle | U/D: 80° / 80°, L /R: 75° / 75° |
| Display Colours | 16.7 M |
| Video Synchronization | Yes |
| PC Compatible Frequency | 30-80KHz(H) / 50-75Hz(V) |
| Adjustable Colour Temperature | 9300K / 6500K / 5800K / User |
| Video Compatiblity | Multi-Standard for NTSC / PAL |
| Aspect Ratio | 16 : 9 Ratio |
| VGA Auto Frequency correction | Yes |
| Speakers | Right x 1 Left x 1, 2.5W |
| Number of Speakers | x 2 |
| Sound Demodulation | Stereo, Audio |
| Mute | Yes |
| Work Humidity | 20 % – 70 % |
| Work Temperature | -10 to +50 °C |
| Volume +/- Power On/Off | Yes |

| MODEL | SR215HDMI |
|---|---|
| **IN/OUT INTERFACE** | |
| Video Interface | HDMI x1, DVI x1, VGA x 1 |
| Audio Interface | Audio In x 1, Audio Out x 1 |
| Power Interface | DC In x 1 |
| Termination | 75 Ohms (Automatic termination) |
| Stand Type | Desktop |
| Safety & EMC Certification | Energy Star / CE / FCC / ROHS /WEEE |
| Vesa Standard Mount | 100 x 100mm |
| Colour | Black |
| Button Position | Right Hand Side, Front Rear |
| Packing Dimension | 520 x 419 x 96mm |
| NET Weight | 3.5 Kgs |
| GROSS Weight | 4.2 Kgs |
| **POWER** | |
| Power Supply | 12VDC, 3 amp |
| Voltage | AC100 – 240V 50 / 60Hz |
| Power Consumption | < 25W in "ON" |
| **OSD CONTROLS** | |
| Contrast, Brightness, Colour, Gamma, Colour Temperature,OSD position, OSD timeout, OSD tranparency, Language, Mute, DCR, Screen size (16:9/4:3) | |
| **OSD LANGUAGE** | |
| English, French, German, Spanish, Italian, Russian and Portuguese | |
| **ACCESSORIES** | |
| Power Supply / Kettle Lead / HDMI Cable/Audio Cable / User Manual / Remote Control | |

* Specifications subject to change without further notice