MODEL	SR32/4K
Panel Type	32" (16:9) 4k LED Backlit Monitor
Case Type	Metal
Maximum Resolution	3840 x 2160 @60Hz
Active Display Area	698.4 (H) x 392.85 (V)
Pixel Pitch	0.181875 (H) x 0.181875 (V)
Bezel Thickness	L/R/U: 15.5mm, D: 23.1mm
Contrast Ratio	3000 : 1 Ratio
Brightness	300 cd/ m^2
Response Time	5m.sec (G to G)
Viewing Angle	178/178
Display Colours	1.07B
Display Mode	Quad, Pip, Pop
Video Synchronization	Yes
PC Compatibility	Yes
Aspect Ratio	16:9 / 4:3
VGA Auto Frequency correction	Yes
Speakers	2
Number of Speakers	5W x 2
Sound Demodulation	ACC
Mute	Yes
Work Humidity	5 % – 90 %
Work Temperature	-10 to +50 °C
Volume +/- Power On/Off	Yes

SERAGE

MODEL	SR32/4K
IN/OUT INTERFACE	
Video Interface	2 x HDMI v 2.0 input, 2 x DP v1.2 input
Audio Interface	PC Audio out
Power Interface	AC in
Termination	75 Ohms
Stand Type	Desk
Safety & EMC Certification	CE / FCC / ROHS
Vesa Standard Mount	200 x 200mm
Colour	Black
Button Position	Buttom Right
NET Weight	12.8 Kgs
GROSS Weight	11.5 Kgs
POWER	
Power Supply	N/A
Voltage	110 / 230v AC
Power Consumption	60 watt (typical)
OSD CONTROLS	
Brightness, Contrast, Eco, DCR, H.Position, V.Position, Clock, Phase, Aspect, Colour Temp, OSD setting, OSD language, OSD H. Pos, OSD V. Pos, OSD timer, OSD Transparency, Factory Reset. Singal Source, Volume	
OSD LANGUAGE	
English, French, German, Chinese, Italian, Spanish, Portuguese, Turkish, Polish and Dutch.	
ACCESSORIES	
Remote, power cable, HDMI cable, User's manual	

* Specifications subject to change without further notice