

### MAIN FEATURES



**5MP**



2592 (H) × 1944 (V)



2.8 mm Fixed Lens



**Color 0.01lux @ F1.2(AGC ON)**  
; **B/W 0 lux @ IR ON**



**30m** IR Distance



True WDR



IP66



DC 12V/POE

MODEL	SRDNFACE
Image Sensor	Sensor: IMX335, 1/2.8" Progressive CMOS
Resolution	5MP 2592(H)×1944(V)
Min. Illumination	Color 0.01lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON
Shutter	1/5 ~ 1/20000s
Slow shutter	Support
Lens	2.8mm H.FOV: 92°
F No.	F No. 2.0±5%
Day & Night	IR cut filter with auto switch (Day/Night/Auto/Schedule)
Digital noise reduction:	3D DNR
WDR	120 dB
Video Compression	H.265/H.264
Video bit rate	8Kbps ~ 8Mbps
Triple Stream	YES
Resolution	Mainstream 1~30fps default 30fps 5MP (2592x1944),4MP(2592x1520), 3MP(2304x1296)(2048x1535) 1080P(1920x1080), 720P(1280x720), Substream 1~30fps default 10fps ) 720P(1280x720), VGA(640x480),QVGA(320x240) Mobilestream 1~30fps default 10fps VGA(640x480), QVGA 320x240
Image Settings	Flip, Rotation, Corridor mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
BLC	Support
ROI	Support
Privacy Mask	Support
Video Analytics	Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Pedestrian Detection,Face Detection(DEEP LEARNING),Cross Counting.
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPoE, SMTP,NTP,UPnP,SNMP,HTTPS,FTP,
System Compatibility	ONVIF( Profile S, Profile G)
Interface	RJ45 10M / 100M Ethernet interface x1
Led	18pcs(SMD)
IR Range	Up to 30m
SD storage	No
Alarm Trigger	No
Audio	No
Video Output	No
Reset Button	No
PoE	YES
Water Proof	IP 66
Power Supply	DC 12V/POE
Consumption	≤ 6W
Dimension	Ø100 X 90mm
Weight	appr. 370g
Storage Temperature	-30~+60°C
Operating Temperature	-30~+55°C

