



MODEL	SR10HDB
Panel Type	10.1" (16:9) LED Monitor Glass Fronted
Case Type	Metal
Maximum Resolution	1280 (H) x 800 (V)
Active Display Area	216.96 (H) x 135.60 (V) mm
Pixel Pitch	0.169 (V) x 0.169 (H) mm
Bezel Thickness	L/R: 14.9 mm, T: 14.6mm, B: 26.2mm
Contrast Ratio	800 : 1 Ratio
Brightness	300 cd/ m ²
Response Time	12 m.sec (G to G)
Viewing Angle	80/80/80/80 °
Display Colours	16.7 M
Video Synchronization	Yes
PC Compatibility	Yes
Aspect Ratio	16 : 9 Ratio
VGA Auto Frequency correction	Yes
Speakers	Yes
Number of Speakers	2
Sound Demodulation	Stereo
Mute	Yes
Work Humidity	0 % – 90 %
Work Temperature	0 to +50 °C
Volume +/- Power On/Off	Yes
MTBF	50,000 hrs

MODEL SR10HDB	
IN/OUT INTERFACE	
Video Interface	VGA, HDMI, 1 x BNC in, 1 x BNC out, Audio
Audio Interface	3.5mm Jackplug
Power Interface	DC In x 1
Termination	75 Ohms
Safety & EMC Certification	FCC, CE, ROHS-2, Reach, Weee
Vesa Standard Mount	75 x 75 mm
Stand Type	Picture Frame
Colour	Black
Button Position	Front
Packing Dimension	360mm x 320 mm x 90mm
NET Weight	1.3 Kgs
GROSS Weight	1.75 Kgs
POWER	
Power Supply	12v 1AMP
Voltage	AC100-240V 50/60HZ
Power Consumption	<10 Watt
OSD CONTROLS	
VIDEO-Picture, Brightness, Contrast, Colour, Sharpness, Tint, Colour Temp, Advance Control, Focus. AUDIO-Sound Mode, Balance, Bass, Treble, Virtual Surround, AVL. SETTING-Menu Language, Picture Format, Menu Timeout, Menu Transparency, Power On Status, Blue Screen, Colour System, Time Set-up, System Reset	
OSD LANGUAGE	
English, French, German, Spanish, Italian, Russian, Portuguese, Polish, Arabic & Korean	
ACCESSORIES	
Power supply, Stand, Remote Control, User Guide, HDMI Cable	

