

# Night Light

## MAIN FEATURES



5MP



2592 (H) × 1944 (V)



30m IR Distance



2.8 mm Fixed Lens



0.05lux@F1.2(AGC ON), 0Lux with IR ON



Digital WDR






IP66



12v DC/PoE

MODEL	SRDN5FW
Image Sensor	Sensor SC5235, 1/2.7" Progressive CMOS
Resolution	5MP 2592(H)×1944(V)
Shutter	1/5 ~ 1/20000s
Lens	2.8 mm H.FOV: 92°
F No.	F No. 1.6±10%
Day & Night	IR cut filter with auto switch
Minimum Illumination	Color 0.05lux @ F1.2(AGC ON); B/W 0 lux @ IR ON
WDR	Digital WDR
Video Compression	H.265/H.264
Video bit rate	8Kbps ~ 8Mbps
Triple Stream	yes
Frame Rate	Mainstream (1~15fps): 5MP (2160×2160), 1520×1520, 1080×1080, 720×720 Substream (1~15fps) : 720×720, 480×480, 240×240
Image Settings:	Rotate mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
BLC	Support
ROI	Support
Privacy Mask	Support
Video Analytics	N/A
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMT-P, NTP, UPnP, SNMP, HTTPS, FTP,
System Compatibility	ONVIF( Ver 2.6)
Interface	RJ45 10M / 100M Ethernet interface x1
Led	18pcs(SMD)
IR Range	Up to 30m
SD storage	No
Alarm Trigger	No
Audio	No
Video Output:	No
Reset Button	No
PoE	Yes
Water Proof	IP66
Power Supply	DC 12V/POE
Consumption	≤ 7W
Dimension	Ø90 X 85mm
Weight	appr 378g
Storage Temperature	-30~+60°C
Operating Temperature	-30~+55°C



## ACCESSORIES



SRJ1/W



SRWI/W