SERAGE

SR5032D

32 CH, 4 IN 1 HYBRID ANALOGUE DVR
TVI/AHD/CVI/Analogue

HD-TVI 5MP

MAIN FEATURES

32CH H.265/H.264

Support TVI/AHD/CVI/Analogue Up to 36CH (Analog video + IP video)

8 Audio Input, 1 Output

Recording Quality up to 5MP

Synchronous Playback 16 CH

VGA and HDMI BNC output

USB 2.0 x 2

x 4HDD up to 32TB

MODEL	SR5032D	
Video Compression	H.265/H.264	
Video System	NTSC/PAL	
Operation System	Linux (Embedded)	
Analog Video-Input /Output	32CH inputs / VGA and HDMI BNC output	
IP Video Input	4CH	
Composite Video Input	up to 36ch (Analog video + IP video)	
Audio Input /Output	8CH inputs/1CH output(RCA)	
Display	Resolution	Analog:5MP Lite:20fps 4MP Lite:30fps/3MP:18fps/1080P/720P/960H:30fps IP:5MP/4MP/3MP/1080P/720P
	Feature	single/Quad/Nine/Sixteen/S.E.Q.
Record	Resolution	Analog: 5MP Lite/4MP Lite/3MP/1080P/720P/960H IP:5MP/4MP/3MP/1080P/720P
	Speed	Analog:5MP Lite:12fps(each ch); 4MP Lite:15fps(each ch); 3MP:10fps(each ch); 1080P:15fps(each ch); 720P PAL:25fps(each ch)/NTSC:30fps(each ch); IP:PAL:25fps(each ch)/NTSC:30fps(each ch)
IP-Recording Bandwidth (Maximum Input Bandwidth)	32Mbps	
Maximum Output Brandwidth	128Mbps	
Maximum Decode Performance	1080P:480fps	
Recording Mode	Continuous/Manual/Motion detect	
Synchronous Playback	16CH	
Network Type	Lan, DHCP, and DDNS	
HDD Interface	4SATA HDDs, up to 32 TB	
Multiplex Operation	Live display, record, playback, backup and network	
USB	2xUSB (For mouse and backup/upgrade)	
Sensor & Alarm I/O	16 inputs/1 output	
PTZ Control	Yes (RS485)	
Mobile Surveillance	Support Mobile Phones based on iPhone and Android operation system	
VGA/HDMI	1024*768,1280*1024,1440*900,1920*1080,2560*1440(2K), 3840*2160(4K)	
Power Supply	DC 12V/5A	
Dimension (WxDxH)	378X326X66mm	
Working Temperature	-10°C~+55°C	
Working Humidity	10%~90%	

* Specifications subject to change without further notice