


MAIN FEATURES

- 5 MP
- 2560(H) x 1920(V) Resolution
- 2.8-8mm Motorized Iris Lens
- 20m IR
- x3 Optical Zoom
- AGC, AWB, BLC, DNR
- 12v DC
- IP66



MODEL	SRSPM5
IMAGE SENSOR	1/2.8" SONY 2.0 Megapixel CMOS Sensor
EFFECTIVE PIXEL	2560(H) x 1920(V) Resolution
SCANNING SYSTEM	Progressive Scan
SYNCHRONIZATION	Internal
ELECTRONIC SHUTTER	1/25s~1/50,000s , 1/30s~1/60,000s
TV SYSTEM	PAL/NTSC
VIDEO FRAME RATE	25fps/30fps@1080P
MIN. ILLUMINATION	0.01Lux@F1.2(AGC ON), 0Lux IR on
VIDEO OUTPUT	1 CH BNC AHD /TVI /CVI High Definition Video Output/CVBS Standard Definition Video Output
IR LED	Nano-tech IR LED: 42μ x 2pcs, IR Range: 20M
PAN RANGE	0°~350°, Horizontal
PAN SPEED	120°/s
TILT RANGE	0°~90°, Vertical
TILT SPEED	45°/s
QUANTITIES OF PRESETS	255
SCANNING MODE	Auto Pan/Pattern/Auto Tour
PTZ PROTOCOL	PELCO-D/PELCO-P
BAUD RATE	2400/4800/9600/19200/38400
PIXEL	5.0 MP
IMAGE FORMAT	1/2.8"
FOCAL LENGTH	2.8-8mm
APERTURE	F1.4
MOUNT	M12
IRIS	Fixed
FOCUS	AUTO
ZOOM	Motorized 3X optincal zoom
SENSE-UP	OFF/ON
DWDR	OFF/ON
DEFOG	OFF/ON
BACKLIGHT COMPENSATION	OFF/BLC/HSLBC
WHITE BALANCE	ATW/AWC-SET/INDOOR/OUTDOOR/MANUAL/AWB
DAY&NIGHT	EXT/AUTO/COLOR/B/W
NOISE REDUCTION	2D NR/3D NR
CAMERA TITLE	OFF/ON
MOTION DETECTION	OFF/ON
PRIVACY MASK	OFF/ON
OSD LANGUAGE	EN/CN/DE/FR/IT/ES/PL/RU/PT/NL/TR
INGRESS PROTECTION	IP66
POWER SUPPLY	DC12V±10%
POWER CONSUMPTION	Max 5W
WORKING ENVIRONMENT	-10°C~+50°C / Less than 95%RH (no condensation)
DIMENSION	105mm x 69mm(H)
WEIGHT	450g

