

MAIN FEATURES



5MP



2592 (H) × 1944 (V) Resolution



3.6 mm Fixed Lens



60m IR Distance



WDR 90dB



IP66



12v DC



Night Light

MODEL	SRBN5FW
Image Sensor	Sensor OV4689, 1/3" Progressive CMOS
Resolution	5MP 2592 (H) × 1944 (V)
Min. Illumination	Color 0.1lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON
Shutter	1/5 ~ 1/20000s
Slow shutter	Support
Lens	3.6 mm H.FOV: 73°
F No.	F 2.0 ±5%
Day & Night	IR cut filter with auto switch
WDR	90dB
Video Compression	H.265/H.264
Video Bit Rate	8Kbps ~ 8Mbps
Triple Stream	YES
Frame Rate	Mainstream (1-20fps optional): 5MP(2592×1944),4MP (2592×1520), 3MP (2048×1536) (2304×1296), 1080P(1920×1080), 960P (1280×960), 720P (1280×720) Substream: 720P (1280×720), VGA (640×480), QVGA (320×240) Mobilestream: VGA (640×480), QVGA (320×240)
Image Settings	Rotate mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
BLC	Support
ROI	Support
Privacy Mask	Support
Video Analytics	Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection.
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
System Compatibility	ONVIF (Ver 2.6)
Interface	RJ45 10M / 100M Ethernet interface x1
Led	2pcs (Array)
IR Range	Up to 60m
SD storage	NO
Alarm Trigger	NO
Audio	NO
Video Output:	NO
Reset Button	NO
PoE	Yes
Water Proof	IP 66
Power Supply	DC 12V/POE
Consumption	≤ 7W
Dimension	Ø84 X 239mm
Weight	appr. 607g
Storage Temperature	-30~+60°C
Operating Temperature	-30~+60°C
Storage Temperature	-30~+60°C

* Specifications subject to change without further notice