SERAGE

SR8004N

HD-IP 4K

4 CHANNEL NVR (POE)

MAIN FEATURES

4 CH Build-in PoE

Recording Quality up to 4K

2 Way Audio

40Mbps Incoming Bandwidth

Simultaneous VGA & HDMI outputs

4 Alarm in / 1 Alarm out
4 Alarm input / 1 Alarm output

Video Compression
H.265 / H.264

USB 2.0 x 3

x 1HDD up to 8TB

MODEL	SR8004N
PoE	4 PoE
Video System	50Hz/60Hz
IP Video Input	4 Inputs
Video Output	1 VGA (up to 1080P) and 1 HDMI (up to 4K) output
Two-way Audio Line-in	1 Input, RCA (2.0 Vp-p, 1kΩ)
Audio Output	1 Output, RCA (2.0 Vp-p, 1kΩ)
Video Format	H.265/H.264
Max. Input Bandwidth	40Mbps
Display Resolution	1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080, 2560*1440, 3840*2160 (4K)
Recording Resolution	8MP / 5MP / 4MP / 3MP / 2MP(1080P) / 1.3MP(960P) / 1MP(720P)
Peak Decode Performance	1 Channel real-time @ 4K 2 Channels real-time @5/4MP 3 Channels real-time @ 3MP 4 Channels real-time @ 2MP 4K mainstream 1ch, substream 4ch
Recording Mode	Continuous / Manual / Schedule / Motion detection / Sensor Triggered
HDD Supported	1 SATA HDD, up to 8TB
Network Interface	RJ-45 10/100Mbps self-adaptive Ethernet interfaces
Network Type	Static IP, DHCP, PPPoE
Onvif Support	Yes, Ver2.6.1
P2P Support	Yes, scan QR code to connect to NVR via mobile app
DDNS Support	Yes
UPnP Support	Yes, support to forward network port automatically
Cloud Storage Support	Yes, support to save pictures to Dropbox storage
CMS Support	Yes, No limitation on adding devices, max. 128 channels live view
Mobile App Support	iOS & Android APP: RxCamView, support to live view max. 80 channels simultaneously
Local Playback	Max. 4 Channels
Network Remote Playback	Max. 4 Channels Simultaneously via CMS, IE/Mac Safari or Mobile App
Playback Search	Date & Time / Event List / Smart Search
Playback Mode	Play, Fast Forward (max. 16x), Fast Rewind (max. 16x), Zoom
Backup Method	USB, Network
USB	USB 2.0 x3
e-SATA	Optional
PTZ Control	N/A
Sensor & Alarm Port	4 inputs / 1 output
Keyboard Port	N/A
Power Supply	DC 48V, PoE Swith: 48V
Dimension(WxDxH)	300x227x53mm
Working Environment	-10°C~+55°C / 10%~90%RH
Working Environment	-10°C~+55°C / 10%~90%RH

* Specifications subject to change without further notice