



MODEL	SR215HDA
Panel Type	19.5" (16:9) LED Backlit Monitor
Case Type	Plastic Case
Maximum Resolution	1920 x 1080
Active Display Area	476.64 (H) x268.11(V) mm
Pixel Pitch	0.24825 (H) x 0.24825 (V) mm
Bezel Thickness	L/R/U: 14.6mm, D:22.7mm
Contrast Ratio	1000 : 1 Ratio
Brightness	250 cd/ m <sup>2</sup>
Response Time	5m.sec (G2G)
Viewing Angle	170 /160
Display Colours	16.7 M
PC Compatible Frequency	30-60 KHz (H) / 56-75Hz (V)
Aspect Ratio	16 : 9 Ratio
VGA Auto Frequency correction	No
Speakers	2 x 3W
Number of Speakers	x 2
Sound Demodulation	Stereo, Audio
Mute	Yes
Work Humidity	5 % – 90 %
Work Temperature	-10 to +50 °C
Volume +/- Power On/Off	On/Off

MODEL SR215HDA	
IN/OUT INTERFACE	
Video Interface	HD-TVI (Supports 4Mp), HD-CVI (Supports 3Mp), AHD 2.0 (Supports 5Mp) x 1 BNC in /out , CVBS x 1 BNC in / out, HDMI x 1
Audio Interface	PC Audio in / BNC Audio in Power Interface
Power Interface	DC In x 1
Termination	75 Ohms
Stand Type	Desktop
Safety & EMC Certification	CE, FCC, ROHS
Vesa Standard Mount	100 x 100mm
Colour	Black
Button Position	Bottom, front of case
Packing Dimension	575 x 120 x 425mm
NET Weight	3.25 Kgs
GROSS Weight	4.55 Kgs
POWER	
Power Supply	12VDC, 3 amp
Voltage	110 / 240v AC
Power Consumption	20 watt(typical)
OSD CONTROLS	
Contrast, Brightness, Colour Temperature, Sharpness, Anti-Picture-Burn-In, Sound volume, OSD position, OSD transperance, Background color, Factory reset	
OSD LANGUAGE	
English and Chinese	
ACCESSORIES	
HDMI Cable, User Manual, Power Adapter, Power Lead, Remote control	

