

MAIN FEATURES



5MP



2592 (H) × 1944 (V) Resolution



3.6 mm Fixed Lens



60m IR Distance



WDR 90dB



IP66



12v DC



Night Light

MODEL	SRBN5FG
Image Sensor	Sensor OV4689, 1/3" Progressive CMOS
Resolution	5MP 2592 (H) × 1944 (V)
Min. Illumination	Color 0.1lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON
Shutter	1/5 ~ 1/20000s
Slow shutter	Support
Lens	3.6 mm H.FOV: 73°
F No.	F 2.0 ±5%
Day & Night	IR cut filter with auto switch
WDR	90dB
Video Compression	H.265/H.264
Video Bit Rate	8Kbps ~ 8Mbps
Triple Stream	YES
Frame Rate	Mainstream (1-20fps optional): 5MP 2592 (H) × 1944 (V), 4MP (2592x1520), 3MP (2048x1536) (2304x1296), 1080P(1920x1080), 960P (1280x960), 720P (1280x720) Substream: 720P (1280x720), VGA (640x480), QVGA (320x240) Mobilestream: VGA (640x480), QVGA (320x240)
Image Settings	Rotate mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
BLC	Support
ROI	Support
Privacy Mask	Support
Video Analytics	Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection.
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
System Compatibility	ONVIF (Ver 2.6)
Interface	RJ45 10M / 100M Ethernet interface x1
Led	2pcs (Array)
IR Range	Up to 60m
SD storage	NO
Alarm Trigger	NO
Audio	NO
Video Output:	NO
Reset Button	NO
PoE	Yes
Water Proof	IP 66
Power Supply	DC 12V/POE
Consumption	≤ 7W
Dimension	Ø84 X 239mm
Weight	appr. 607g
Storage Temperature	-30~+60°C
Operating Temperature	-30~+60°C
Storage Temperature	-30~+60°C