SERAGE

SR2004D

HYBRID 1080p

4 CH, 5 IN 1 HYBRID ANALOGUE DVR
TVI - CVI - AHD - Analogue - IP

MAIN FEATURES

4 CH H.264

Support TVI/AHD/CVI/Analogue + 2 IP – **Total of 6 Cameras**

4 Audio Input, 1 Output

HD 1080P 2MP 1080p

Synchronous Playback 4CH

VIDEO output HDMI, VGA & BNC CVBS output

USB 2.0 x 2

x 1HDD up to 8TB

MODEL	SR2004D
Video Compression	H.264
Video System	NTSC/PAL
Operation System	Linux (Embedded)
Analog Video-Input /Output	4CH Inputs / VGA and HDMI Output
IP Video Input	2CH (Only IP up to 6CH)
Composite Video Input	Up to 6ch (Analog video + IP video)
Audio Input /Output	4CH Inputs /1CH Output (RCA)

Display	Reslution	Analog: 3MP (15fps), 1080p/720p, 960H IP: 4MP/3MP, 1080p/720p, 960H
	Feature	1/4/6/S.E.Q.

Record	Resolution	Analog: 3MP, 1080p/720p, 960H IP: 4MP/3MP, 1080p/720p, 960H
	Speed	Analog: 3MP: 5fps (Each CH) 1080p: PAL: 14fps (Each CH) 720p: PAL: 25fps (Each CH)/NTSC: 30fps (Each CH) 960H: PAL: 25fps (Each CH)/NTSC: 30ps (Each CH) IP: PAL: 25fps (Each CH)/NTSC: 30fps (Each CH)

IP-Recording Bandwidth (Maximum Input Bandwidth)	8Mbps ~24Mbps (Default is 8Mbps, decrease one analog channel can increase 4Mbps)
Maximum Output Brandwidth	32Mbps
Maximum Decode Performance	1080p: 2CH realtime
Recording Mode	Continuous/Manual/Motion detect
Synchronous Playback	4CH
Network Type	LAN, DHCP and DDNS
HDD Interface	1SATA HDD, up to 8TB
Multiplex Operation	Live display, record, playback, backup and network
USB	2xUSB (For mouse and backup/upgrade)
Sensor & Alarm I/O	4 CH Inputs /1CH Output
PTZ Control	Yes (RS485)
Mobile Surveillance	Support mobile phones based on iPhone and Android operation system
VGA/HDMI	1024x768, 1280x1024, 1440x900, 1920x1080
CVBS Spot	Yes
Power Supply	DC 12V/2A
Dimension (WxDxH)	300x227x53mm
Working Temperature	-10°C~+55°C
Working Humidity	10%~90%

* Specifications subject to change without further notice