

## MAIN FEATURES



2MP



Full HD 1080P



60m IR Distance



3.6 mm Fixed Lens



IP66



12v DC



# Night Light



| MODEL                 | SRBN2FW   |
|-----------------------|---|
| Image Sensor          | Sensor IMX323, 1/2.9" Progressive CMOS  |
| Resolution            | 2MP 1920(H)×1080(V)   |
| Min. Illumination     | Color 0.1lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON   |
| Shutter               | 1/5 ~ 1/20000s  |
| Slow shutter          | Support   |
| Lens                  | 3.6 mm H.FOV: 73°   |
| F No.                 | F 2.0 ±5%   |
| Day & Night           | IR cut filter with auto switch  |
| WDR                   | Digital WDR   |
| Video Compression     | H.265/H.264   |
| Video Bit Rate        | 8Kbps ~ 8Mbps   |
| Triple Stream         | YES   |
| Frame Rate            | <b>Mainstream (1-30fps optional):</b> 1920x1080, 1280x960, 1280x720<br><b>Substeam:</b> 1280x720, 640x480, 320x240<br><b>Mobilestream:</b> 640x480, 320x240 |
| Image Settings        | Rotate mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable  |
| BLC                   | Support   |
| ROI                   | Support   |
| Privacy Mask          | Support   |
| Video Analytics       | Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection.  |
| Protocols             | TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP   |
| System Compatibility  | ONVIF ( Ver 2.6)  |
| Interface             | RJ45 10M / 100M Ethernet interface x1   |
| Led                   | 2pcs (Array)  |
| IR Range              | Up to 60m   |
| PoE                   | Yes   |
| Water Proof           | IP 66   |
| Power Supply          | DC 12V/POE  |
| Consumption           | ≤ 7W  |
| Dimension             | Ø84 X 239mm   |
| Weight                | appr. 607g  |
| Storage Temperature   | -30~+60°C   |
| Operating Temperature | -30~+60°C   |
| Storage Temperature   | -30~+60°C   |

\* Specifications subject to change without further notice

## ACCESSORIES



SRJ1/W