

MAIN FEATURES



5MP 2592 (H) × 1944 (V)



5.0-50 mm Motorised Lens



80m IR Distance



0.05lux@F1.2(AGC ON),0Lux with IR ON



IP66



12v DC

MODEL	SRBT5VF/550
Image Sensor	Sensor: SC5235 1/2.7" Progressive CMOS
Resolution	5MP 2592(H)×1944(V)
Signal System	PAL/NTSC
Min.illumination	0.05lux@F1.2(AGC ON),0Lux with IR ON
Frame Rate	5AHD/5TVI: 5MP@20fps 4AHD/4CVI/4TVI: 4MP/P@25fps 4MP/N@30fps CVBS: 960H
Shutter Time	1/15 s to 1/50,000 s
Lens	5.0-50 mm Motorised lens
Horizontal Field of View	H.FOV:45°(W)—7°(T)(2.8-12)
Day & Night	IR cut filter
IR Cut Filter	YES,850nm
Synchronization	Internal synchronization
DWDR	Support
AGC	yes
Day/Night Mode	EXT/Auto/Color/BW (Black and White)
white balance	Auto/Manual
BLC	Support
S/N Ratio	35dB
OSD	Support
Video Output Termination	1-channel BNC video output
Swatch button	TVI/AHD/CVI/CVBS
IP Rating	IP66
Power Supply	12V
Power Consumption	MAX 8W
Led	8pcs Array Led
IR Range	up to 80M
Communication	Up the coax, Protocol

ACCESSORIES



SRJ1/W