

MAIN FEATURES

- 2.0 MP
- Full HD 1080P
- 6-50mm Motorized Auto Iris Lens
- 120m IR
- True WDR
- AGC, AWB, BLC, DNR
- 12v DC/24v AC
- IP68
- Anti-Reflection
- rue D&N (ICR), Defog, DNR
- **Built-in Base**
- **Analogue Output as a Second Cable**
- **For best result use with 24v power supply**



MODEL	SRTVI-BVF/120
RESOLUTION	1080P, 720P, 720P CROP
SENSOR	1/2.9 inch SONY CMOS
LENS	6-50mm Varifocal Auto Iris Lens
TOTAL PIXELS	2000(H) x 1241(V) = 2,482,000
EFFECTIVE PIXELS	1944(H) X 1092(V) = 2,122,648
SCANNING SYSTEM	PROGRESSIVE
S/N (Y SIGNAL)	More than 52 dB (AGC Off)
VIDEO OUTPUT	TVI / (CVBS: 1.0Vp-p (75ohm) : Option)
MIN ILLUMINATION	0 Lux at IR On
WHITE BALANCE	AUTO / AUTO EXT / PRESET / MANUAL
SHUTTER	AUTO / MANUAL (1/30sec ~ 1/60,000sec)
BRIGHTNESS	ADJUSTABLE (0 ~ 20 STEP)
SENSE UP	OFF / X2 / X3 / X4 / X5 / X6 / X7 / X8
DNR	OFF / LOW / MIDDLE / HIGH
BACKLIGHT	OFF / WDR / BLC / HLM
ACE	OFF / LOW / MIDDLE / HIGH
DAY & NIGHT	AUTO (Day <--> Night TIME Change) , COLOR , B/W, EXTERN, MDIR (SEARCH Option)
PRIVACY	OFF / ON (16 Zone)
MOTION	OFF / SET
D.ZOOM	0 ~ 127
FLIP	OFF / ON
FREEZE	OFF / ON
LANGUAGE	ENG, CHN, CHN(S), JPN, KOR
SHARPNESS	ADJUSTABLE (0 ~ 10 STEP)
DEFOG	OFF / SET
COMM	RS-485 (PELCO-D)
SMART IR	ADJUSTABLE (0 ~ 20 STEP) - Up to 120m IR
OPERATING TEMPERATURE / HUMIDITY	-10'C~+50'C / 30%~80% RH
STORAGE TEMPERATURE / HUMIDITY	-20'C~+60'C / 20%~90% RH
POWER	DC 12V / AC 24C
SIGNAL TRANSMISSION	The distant difference is occurred according to cable option and other circumstances. (coaxial cable 300M)



Built-in Base