MODEL	SR28/4K
Panel Type	LED
Case Type	Plastic
Maximum Resolution	3840 H x 2160 V
MTBF	50,000 hrs
Active Display Area	620 (H) X 341 (V)
Pixel Pitch	0.158 (H) x 0.158 (V) mm
Bezel Thickness	Left/Right/Top: 17mm, bottom: 31mm
Contrast Ratio	1000 : 1 Ratio
Brightness	300 cd/ m^2
Response Time	5m.sec (G to G)
Viewing Angle	178/178 H/V
Display Colours	1.07B (10-bit)
Display Mode	16:9/4:3
Video Synchronization	Yes
PC Compatibility	Yes
Aspect Ratio	16:9 / 4:3 Ratio
VGA Auto Frequency Correction	N/A
Speakers	0
Sound Demodulation	No
Mute	Yes
Work Humidity	5 % – 90 %
Work Temperature	0-40 °C
Volume +/- Power On/Off	Yes

MODEL	SR28/4K
IN/OUT INTERFACE	
Video Interface	1x HDMI v2.0 input, 2x HDMI v1.4 input, 1 x DP v1.2 input
Audio	1x Output
Termination	N/A
Certification	CE / FCC / ROHS
VESA	100 x 100
Stand Type	Desk
Colour	Black
Button Position	Back Bottom Right
Packing Dimensions	756mm x 240mm x 533mm
Monitor Packing Dimensions	744mm x 118mm x 515mm
GROSS Weight	8.5 Kgs
POWER	
Power Supply	220/240 AC
Voltage	12 v DC
Power Consumption	35 Watt
Power Interface	DC 12V in x1

OSD CONTROLS

Contrast, Brightness, DCR, Saturation, OSD position, Gamma, Color temp, Hue, Low blue light, Sharpness, Noise reduction, Aspect Ratio, Mute, Volume, Multi-Window, OSD position

OSD LANGUAGE

English, French, Russian, Spanish, German, Italian, Portuguese, Turkish, Danish, Polish and Dutch

ACCESSORIES

Power cable, Adaptor, Stand, HDMI cable, User's Guide, Remote Control

* Specifications subject to change without further notice

460.3

62.5

397.7

255.0

660.4

28"

50.0

162.0

44.5

A-M4

100.0

100.0