

Night Light

 Audio with Built-in Microphone

MAIN FEATURES



5MP



2592 (H) × 1944 (V)



2.8 mm Fixed Lens



10m IR Distance



Color 0.05lux @ F1.2(AGC ON);
B/W 0 lux @



Digital WDR



IP66



12v DC

MODEL	SRDN5FSM
Image Sensor	Sensor SC5235, 1/2.7" Progressive CMOS
Resolution	5MP 2592(H)×1944(V)
Min. Illumination	Color 0.05lux @ F1.2(AGC ON); B/W 0 lux @ IR ON
Lens	2.8 mm H.FOV: 92°
F No.	F No. 1.6±10%
Day & Night	IR cut filter with auto switch
WDR	Digital WDR
Video Compression	H.265/H.264
Video bit rate	8Kbps ~ 8Mbps
Triple Stream	YES
Frame Rate	Mainstream (1~15fps) 5MP(2592×1944),4MP(2592×1520) 3MP(2048×1520),1080P(1920×1080) 960P(1280×960), 720P(1280×720) Substream (1~15fps) 720P(1280×720)VGA(640×480),QVGA(320×240)
Image Settings	Rotate mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
BLC	Support
ROI	Support
Privacy Mask	N/A
Video Analytics	N/A
Protocols	TCP/IP, HTTP, DHCP,DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
System Compatibility	ONVIF (Ver 2.6)
Interface	RJ45 10M / 100M Ethernet interface x1
Led	12pcs(SMD)
IR Range	Up to 10m
SD storage	YES
Alarm Trigger	No
Audio	No
Video Output	No
Reset Button	No
PoE	YES
Water Proof	IP 66
Power Supply	DC 12V/POE
Consumption	≤ 7W
Dimension	Ø119.5 X 63.8mm
Weight	appr. 300g
Storage Temperature	-30~+60°C
Operating Temperature	-30~+55°C