```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Testing & Quality Assurance</title>
  <link rel="stylesheet" href="style.css">
</head>
<body>

  <header>
    <h1>Testing & Quality Assurance</h1>
    <p>Software Testing and Quality Monitoring System</p>
  </header>

  <nav>
    <a href="#home">Home</a>
    <a href="#tests">Testing</a>
    <a href="#report">Reports</a>
  </nav>

  <section id="home" class="container">
    <h2>Testing Dashboard</h2>
    <p>Monitor application quality and testing results.</p>

    <div class="cards">
      <div class="card">
        <h3>Total Tests</h3>
        <p id="total">0</p>
      </div>

      <div class="card">
        <h3>Passed</h3>
        <p id="passed">0</p>
      </div>
```

```
      <div class="card">
        <h3>Failed</h3>
        <p id="failed">0</p>
      </div>
    </div>
</section>

<section id="tests" class="container">
    <h2>Testing Module</h2>

    <label>Enter Test Name:</label>
    <input type="text" id="testName"
        placeholder="Example: Login Testing">

    <label>Testing Status:</label>
    <select id="status">
      <option value="Passed">Passed</option>
      <option value="Failed">Failed</option>
    </select>

    <button onclick="addTest()">Add Test Result</button>
</section>

<section id="report" class="container">
    <h2>Testing Reports</h2>
    <table>
      <thead>
        <tr>
          <th>Test Name</th>
          <th>Status</th>
        </tr>
      </thead>
      <tbody id="reportList"></tbody>
    </table>
</section>
```

```
    <footer>
        <p>Testing & Quality Assurance Project</p>
    </footer>

    <script src="script.js"></script>
</body>
</html>
```