Experiment No. 7
Implement a program using super and final keyword.
Date of Performance:
Date of Submission:

Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Aim: To implement the concept of super and final keyword.

Objective: To understand the usage of superclass and final method, variables and class

Theory:

super and final keywords are two popular and useful keywords in Java. They also play a significant role

in dealing with Java programs and their classes. In this chapter, you will learn about how to use super

and final within a Java program.

Syntax: super.<method-name>();

Super variables refer to the variable of a variable of the parent class.

Super() invokes the constructor of immediate parent class.

Super refers to the method of the parent class

Instance refers an instance variable of the current class by default, but when you have to refer parent

class instance variable, you have to use super keyword to distinguish between parent class (here

employee) instance variable and current class (here, clerk) instance variable.

What is final in Java?

Final is a keyword in Java that is used to restrict the user and can be used in many respects. Final can be

used with:

Class

Methods

Variables

A method declared as final cannot be overridden; this means even when a child class can call the

final method of parent class without any issues, but the overriding will not be possible.

Once a variable is assigned with the keyword final, it always contains the same exact value. Again

things may happen like this; if a final variable holds a reference to an object then the state of the



Vidyavardhini's College of Engineering and Technology Department of Artificial Intelligence & Data Science

object can be altered if programmers perform certain operations on those objects, but the variable will always refer to the same object. A final variable that is not initialized at the time of declaration is known as a blank final variable. If you are declaring a final variable in a constructor, then you must initialize the blank final variable within the constructor of the class. Otherwise, the program might show a compilation error.

Code:

```
1.SUPER
code:
class Animal {
  String name = "Generic Animal";
  Animal() {
     System.out.println("Animal Constructor");
  void sound() {
     System.out.println("Animal makes a sound");
}
class Dog extends Animal {
  String name = "Dog";
  Dog() {
    super();
     System.out.println("Dog Constructor");
  void sound() {
     super.sound();
     System.out.println("Dog barks");
     System.out.println("Animal name using super: " + super.name);
     System.out.println("Dog name: " + name);
}
public class Man {
  public static void main(String[] args) {
    Dog dog = new Dog();
     dog.sound();
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

}

OUTPUT:

```
C:\Users\Sharvari A Bhondekar\OneDrive\Desktop\JAVA PROGRAMS\Exp 7>javac Man.java
C:\Users\Sharvari A Bhondekar\OneDrive\Desktop\JAVA PROGRAMS\Exp 7>java Man.java
Animal Constructor
Dog Constructor
Animal makes a sound
Dog barks
Animal name using super: Generic Animal
Dog name: Dog
```

2.FINAL

code:

```
public class Main {
    final int x = 10;

public static void main(String[] args) {
        Main myObj = new Main();
        System.out.println(myObj.x);
    }
}
```

OUTPUT:

C:\Users\Sharvari A Bhondekar\OneDrive\Desktop\JAVA PROGRAMS\Exp 7>javac Main.java
C:\Users\Sharvari A Bhondekar\OneDrive\Desktop\JAVA PROGRAMS\Exp 7>java Main.java
10
C:\Users\Sharvari A Bhondekar\OneDrive\Desktop\JAVA PROGRAMS\Exp 7>



Vidyavardhini's College of Engineering and Technology Department of Artificial Intelligence & Data Science

Conclusion:

Comment on how you have used super and final keyword.

Use of super:

• In my Dog class, I used the **super** keyword to refer to the **parent class (Animal)**. This includes calling the parent class constructor <code>super()</code> within the Dog constructor, which ensures that the <code>Animal</code> constructor is executed before the Dog constructor. Additionally, I used <code>super.sound()</code> to call the parent class's <code>sound()</code> method, demonstrating how to invoke a method from the superclass. I also accessed the parent class's <code>name</code> variable with <code>super.name</code> to differentiate it from the <code>name</code> variable in the Dog class.

Use of final:

• In the second program, I used the **final** keyword to declare the variable x as a constant, ensuring that its value cannot be changed after initialization. This demonstrates the use of final to create immutable data within the class, enforcing that x will always hold the value 10.