

1. DDL commands –

- Create –

```
mysql> create database student;  
Query OK, 1 row affected (0.01 sec)
```

```
mysql> show databases;  
+-----+  
| Database |  
+-----+  
| information_schema |  
| mysql |  
| performance_schema |  
| student |  
| sys |  
+-----+  
5 rows in set (0.00 sec)  
  
mysql>
```

```
mysql> use student;  
Database changed  
mysql> create table students(id int,name char(50),age int,address varchar(50));  
Query OK, 0 rows affected (0.03 sec)
```

```
mysql> desc students;  
+-----+-----+-----+-----+-----+-----+  
| Field | Type | Null | Key | Default | Extra |  
+-----+-----+-----+-----+-----+-----+  
| id | int | YES | | NULL | |  
| name | char(50) | YES | | NULL | |  
| age | int | YES | | NULL | |  
| address | varchar(50) | YES | | NULL | |  
+-----+-----+-----+-----+-----+-----+  
4 rows in set (0.00 sec)  
  
mysql>
```

- **Alter –**

```
mysql> alter table students add(contactNo int);
Query OK, 0 rows affected (0.02 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> desc students;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| id         | int       | YES  |     | NULL    |       |
| name       | char(50)  | YES  |     | NULL    |       |
| age        | int       | YES  |     | NULL    |       |
| address    | varchar(50)| YES  |     | NULL    |       |
| contactNo  | int       | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)

mysql> _
```

- **Drop –**

```
mysql> drop table students;
Query OK, 0 rows affected (0.02 sec)

mysql> desc students;
ERROR 1146 (42S02): Table 'student.students' doesn't exist
mysql> _
```