

3. DML Commands –

- Insert –

```
mysql> insert into student values(1,"Sharveshwar","Chennai");
Query OK, 1 row affected (0.00 sec)

mysql> select*from student;
+-----+-----+-----+
| ID    | Name          | City    |
+-----+-----+-----+
| 1     | Sharveshwar   | Chennai |
+-----+-----+-----+
1 row in set (0.00 sec)

mysql>
```

- Select –

```
mysql> select*from student;
+-----+-----+-----+
| ID    | Name          | City    |
+-----+-----+-----+
| 1     | Sharveshwar   | Chennai |
+-----+-----+-----+
1 row in set (0.00 sec)

mysql>
```

- Update –

```
mysql> update student set Name = "Gayathri" where ID = 1;
Query OK, 1 row affected (0.01 sec)
Rows matched: 1  Changed: 1  Warnings: 0

mysql> select*from student;
+-----+-----+-----+
| ID    | Name          | City    |
+-----+-----+-----+
| 1     | Gayathri      | Chennai |
+-----+-----+-----+
1 row in set (0.00 sec)

mysql>
```

- Delete –

```
mysql> delete from student where ID = 1;  
Query OK, 1 row affected (0.01 sec)  
  
mysql> select*from student;  
Empty set (0.00 sec)  
  
mysql>
```