

Chapter 2: Relational Model


Chapter 2: Relational Model

- ❑ Structure of Relational Databases
- ❑ Fundamental Relational-Algebra-Operations
- ❑ Additional Relational-Algebra-Operations
- ❑ Extended Relational-Algebra-Operations
- ❑ Null Values
- ❑ Modification of the Database

Basic Structure

- ❑ **Relational database:** a set of relations
- ❑ **Relation:** a named data table consisting of two parts:
 - **Schema:** specifies name of relation, consists of a list of attributes and type of each attribute (domains).
 - ▶ E.g., Students(*sid*: string, *name*: string, *login*: string, *age*: integer, *gpa*: real).
 - **Instance:** a table of tuples (or called *records*, *rows*) and attributes (or called *fields*, *columns*).

Example of a Relation



The diagram shows a table representing a relation. The header row is shaded gray and contains three columns: *account_number*, *branch_name*, and *balance*. Below the header are seven data rows. Arrows from the text 'attributes (or columns)' point to each of the three header cells. Arrows from the text 'tuples (or rows)' point to each of the seven data rows.

<i>account_number</i>	<i>branch_name</i>	<i>balance</i>
A-101	Downtown	500
A-102	Perryridge	400
A-201	Brighton	900
A-215	Mianus	700
A-217	Brighton	750
A-222	Redwood	700
A-305	Round Hill	350

Attribute Types

- ❑ Each attribute of a relation has a name
- ❑ **Domain** of the attribute: The set of allowed values for each attribute
- ❑ Attribute values are (normally) required to be **atomic**; that is, indivisible
 - E.g. the value of an attribute can be an account number, but cannot be a set of account numbers
- ❑ Domain is said to be atomic if all its members are atomic
- ❑ The special value *null* :
 - Signifies that the value is **unknown** or **does not exist**
 - A member of every domain
- ❑ The null value causes complications in the definition of many operations
 - We shall ignore the effect of null values in our main presentation and consider their effect later

Relation Schema

- ❑ A_1, A_2, \dots, A_n are *attributes*
- ❑ $R = (A_1, A_2, \dots, A_n)$ is a *relation schema*

Example:

$Customer_schema = (customer_name, customer_street, customer_city)$

- ❑ $r(R)$ denotes a *relation* r on the *relation schema* R

Example:

$customer (Customer_schema)$

Relation Instance

- ❑ The current values (*relation instance*) of a relation are specified by a **table**
- ❑ An element t of r is a *tuple*, represented by a *row* in a table

The diagram shows a table representing a relation instance. The table has three columns and four rows. The columns are labeled *customer_name*, *customer_street*, and *customer_city*. The rows contain the following data: Jones, Smith, Curry, Lindsay; Main, North, North, Park; Harrison, Rye, Rye, Pittsfield. Annotations include arrows pointing from the text 'attributes (or columns)' to the column headers, and arrows pointing from the text 'tuples (or rows)' to the data rows. The table is labeled 'customer' at the bottom.

<i>customer_name</i>	<i>customer_street</i>	<i>customer_city</i>
<i>Jones</i>	<i>Main</i>	<i>Harrison</i>
<i>Smith</i>	<i>North</i>	<i>Rye</i>
<i>Curry</i>	<i>North</i>	<i>Rye</i>
<i>Lindsay</i>	<i>Park</i>	<i>Pittsfield</i>

customer

Relations are Unordered

- Order of tuples is irrelevant (tuples may be stored in an arbitrary order)
- Example: *account* relation with unordered tuples

<i>account_number</i>	<i>branch_name</i>	<i>balance</i>
A-101	Downtown	500
A-215	Mianus	700
A-102	Perryridge	400
A-305	Round Hill	350
A-201	Brighton	900
A-222	Redwood	700
A-217	Brighton	750

Database

- ❑ A database consists of multiple relations
- ❑ Information about an enterprise is broken up into parts, with each relation storing one part of the information
 - account* : stores information about accounts
 - depositor* : stores information about which customer owns which account
 - customer* : stores information about customers
- ❑ Storing all information as a single relation such as
bank(account_number, balance, customer_name, ..)
results in
 - repetition of information
 - ▶ e.g., if two customers own an account (What gets repeated?)
 - the need for null values
 - ▶ e.g., to represent a customer without an account
- ❑ Normalization theory (Chapter 7) deals with how to design relational schemas

The *customer* Relation

<i>customer_name</i>	<i>customer_street</i>	<i>customer_city</i>
Adams	Spring	Pittsfield
Brooks	Senator	Brooklyn
Curry	North	Rye
Glenn	Sand Hill	Woodside
Green	Walnut	Stamford
Hayes	Main	Harrison
Johnson	Alma	Palo Alto
Jones	Main	Harrison
Lindsay	Park	Pittsfield
Smith	North	Rye
Turner	Putnam	Stamford
Williams	Nassau	Princeton

The *depositor* Relation

<i>customer_name</i>	<i>account_number</i>
Hayes	A-102
Johnson	A-101
Johnson	A-201
Jones	A-217
Lindsay	A-222
Smith	A-215
Turner	A-305

Keys

- ❑ A set of attribute K is a **superkey** of R if:
 - No two tuples can have same values in all these attributes
- ❑ Example: Customer(*customer_name*, *customer_street*, *customer_city*)
 - {*customer_name*, *customer_street*} and {*customer_name*} are both superkeys
 - What about *name*?
 - PS: In real life, an attribute such as *customer_id* would be used instead of *customer_name* to uniquely identify customers, but we omit it to keep our examples small, and instead assume customer names are unique.

Keys (Cont.)


- ❑ K is a **candidate key** if K is minimal

Example: $\{customer_name\}$ is a candidate key for *Customer*, since it is a superkey and no subset of it is a superkey.

- ❑ **Primary key:** If there's more than one candidate keys, one is chosen as the primary key
 - Should choose an attribute whose value never, or very rarely, changes.
 - E.g., email address is unique, but may change

Foreign Keys

- ❑ **Foreign key:** A relation schema may have an attribute that corresponds to the primary key of another relation.
 - E.g. *customer_name* and *account_number* attributes of *depositor* are foreign keys to *customer* and *account* respectively.
 - Can refer to itself
 - Only values occurring in the primary key attribute of the **referenced relation** may occur in the foreign key attribute of the **referencing relation**.
- ❑ **Schema diagram**



Review of last lecture

❑ Concepts:

- Schema
- Table
- Relation
- Attribute
- Domain
- Super key
- Candidate key
- Primary key

Class Exercise

- ❑ 1. Given a relation r defined over the schema R , which of the following can always uniquely identify the tuples in r ?
 - A. any non-null attributes of R
 - B. super key of R
 - C. the first attribute in R
 - D. R itself
- 2. Given the following relation, list all candidate keys and superkeys.

A	B	C	D
A1	B1	C1	D1
A1	B2	C2	D1
A2	B1	C2	D1

Query Languages

- ❑ Language in which user requests information from the database.
- ❑ Categories of languages
 - Procedural
 - Non-procedural, or declarative
- ❑ “Pure” languages:
 - Relational algebra
 - Tuple relational calculus
 - Domain relational calculus
- ❑ Pure languages form underlying basis of query languages that people use.

Chapter 2: Relational Model

- ❑ Structure of Relational Databases
- ❑ Fundamental Relational-Algebra-Operations
- ❑ Additional Relational-Algebra-Operations
- ❑ Extended Relational-Algebra-Operations
- ❑ Null Values
- ❑ Modification of the Database

Role of Relational Algebra

- ❑ How does a relational DBMS work?
 - Queries are expressed by users in a language, e.g. SQL;
 - The DBMS translates an SQL query into relational algebra, and meanwhile looks for other algebra expressions that produce the same answers but saving the computational costs.
 - Based on the relational algebra, DBMS calculates the query results.

Relational Algebra

- ❑ Procedural language
- ❑ Six basic operators
 - select: σ
 - project: Π
 - union: \cup
 - set difference: $-$
 - Cartesian product: \times
 - rename: ρ
- ❑ The operators take one or two relations as inputs and produce a new relation as a result.

Instance Example

ID	name	dept_name	salary
100	Kart	CS	65000
101	Crick	History	90000
102	Kim	Finance	60000
103	Wu	Physics	72000
104	John	CS	80000

instructor

Select Operation

- ❑ Notation: $\sigma_p(r)$
- ❑ p is called the **selection predicate**
- ❑ Defined as:

$$\sigma_p(\mathbf{r}) = \{t | t \in r \text{ and } p(t)\}$$

Where p is a formula in propositional calculus consisting of **terms** connected by : \wedge (**and**), \vee (**or**), \neg (**not**)

Each **term** is one of:

$\langle \text{attribute} \rangle \quad op \quad \langle \text{attribute} \rangle$ or $\langle \text{constant} \rangle$

where op is one of: $=, \neq, >, \geq, <, \leq$

- ❑ Example of selection:

$$\sigma_{dept_name = "Physics"}(instructor)$$

Select Operation

ID	name	dept_name	salary
101	Crick	History	90000

instructor

Salary greater than 80,000

$\sigma_{\text{salary} > 80000}(\text{instructor})$

Select Operation

ID	name	dept_name	salary
100	Kart	CS	65000
101	Crick	History	90000
102	Kim	Finance	60000
103	Wu	Physics	72000
104	John	CS	80000

instructor

In department CS with salary greater than 70000

$\sigma_{dept_name="CS" \wedge salary > 70000}(\text{instructor})$

Select Operation

ID	name	dept_name	salary
100	Kart	CS	65000
101	Crick	History	90000
102	Kim	Finance	60000
103	Wu	Physics	72000
104	John	CS	80000

instructor

salary greater than 85,000 or less than 70,000

$\sigma_{salary > 85000 \vee salary < 70000}(\text{instructor})$

Project Operation

- Notation:


$$\Pi_{A_1, A_2, \dots, A_k}(r)$$

where A_1, A_2 are attribute names and r is a relation name.

- The result is defined as the relation of k columns obtained by erasing the columns that are not listed
- Duplicate rows removed from result, since relations are sets
- Example: To eliminate the *dept_name* attribute of *account*

$$\Pi_{ID, name, salary}(instructor)$$

Project Operation



ID	name	dept_name	salary
100	Kart	CS	65000
101	Crick	History	90000
102	Kim	Finance	60000
103	Wu	Physics	72000
104	John	CS	80000

instructor

Remove the department attribute

$\pi_{ID, name, salary}(\text{instructor})$

Project Operation

ID	name	salary
100	Kart	65000
101	Crick	90000
102	Kim	60000
103	Wu	72000
104	John	80000

instructor

Remove the department attribute

$\pi_{ID, name, salary}(\text{instructor})$

Project Operation


ID	name	dept_name	salary
100	Kart	CS	60000
101	Crick	History	90000
102	Kim	Finance	60000
103	Wu	Physics	72000
104	John	CS	80000

instructor

Only remain the dept_name attribute

$\pi_{dept_name}(\text{instructor})$

Project Operation



ID		name	dept_name	salary
100		Kart	CS	65000
101		Crick	History	90000
102		Kim	Finance	60000
103		Wu	Physics	72000
104		John	CS	80000

instructor

Only remain the dept_name attribute

$\pi_{dept_name}(\text{instructor})$

Project Operation

dept_name
CS
History
Finance
Physics

instructor

Only remain the dept_name attribute
(duplicate rows are removed)

$\pi_{dept_name}(instructor)$

Operator composition

ID		name	dept_name	salary
100		Kart	CS	60000
101		Crick	History	90000
102		Kim	Finance	60000
103		Wu	Physics	72000
104		John	CS	80000

instructor

List the name of instructor in CS

$$\pi_{name}(\sigma_{dept_name=cs}(instructor))$$

Operator composition

s2

<u>sid</u>	sname	rating	age
28	yuppy	9	35.0
31	lubber	8	55.5
44	guppy	5	35.0
58	rusty	10	35.0

$\pi_{sname, rating}(\sigma_{rating > 8}(S2))$

sname	rating
yuppy	9
rusty	10