# **SIGEVO Summer School 2017 Challenge**

Challenge posed by Dr Mike Preuss

Shashank Srikant July 19, 2017

shash@mit.edu

#### Question


How does a "Cumulated Gradient Paths" heatmap help me selecting a suitable algorithm/good parameters for a multi-objective optimization problem?

### Response

- The context to this concept is provided in Kerschke et al. 2017, An Expedition to Multimodal Multi-objective Optimization Landscapes
- The work identifies a Combined Gradient as:  $\overrightarrow{v} = \frac{\overrightarrow{v_1}}{\left\|\overrightarrow{v_2}\right\|} + \frac{\overrightarrow{v_2}}{\left\|\overrightarrow{v_2}\right\|}$
- A gradient field is then defined when the search-space is divided in a number of grids, and for each grid we calculate the combined gradient.
- A path connecting each cell's gradient vector is calculated to find out the shape of search-space

continued..

## Response (contd..)



• While creating the path, a neighboring cell is selected based on the direction of the gradient vector.

## Response (contd..)

- Visualizing this path as heat-maps helps show up basins and ridges of local and global efficient sets in the search space.
- An area of a local/global efficient set is marked by decreasing gradients in the region
- This method even allows to visualize and detect disjoint local optimal sets