

Lab Session 1

MA-423 : Matrix Computations

July-November 2021

S. Bora

1. This is an exercise on handling matrices in MATLAB.

- (a). Generate the following square matrix which is known as the Wilkinson matrix without using any *for loops*.

$$W_{ij} = \begin{cases} -1 & \text{if } i > j \\ 1 & \text{if } i = j \text{ or } j = n \\ 0 & \text{otherwise} \end{cases}$$

Here n is the size of the matrix. You may write a function program `W = Wilkinson(n)` which takes the size n of the matrix as input for this.

Hint: Use the MATLAB commands `eyes`, `ones` and `tril`.

- (b). A real $2n \times 2n$ matrix $H = \begin{bmatrix} H_{11} & H_{12} \\ H_{21} & -H_{11}^T \end{bmatrix}$ is said to be Hamiltonian if H_{12} and H_{21} are $n \times n$ matrices such that $H_{12}^T = H_{12}$ and $H_{21}^T = H_{21}$. Here T denotes the transpose of a matrix. Use concatenation and the `randn` command to generate a random real Hamiltonian matrix.
2. The following exercise illustrates that addition is not necessarily associative in finite precision environments.

Given $n \in \mathbb{N}$, the built in function `chop` or `round` (depending upon your MATLAB version) may be used to round $1/n$ to k significant digits and to simulate the summing of a finite number of terms of the sequence $\{\frac{1}{n}\}$, say the first m , in k -digit arithmetic. (Type `help chop` or `help round` for details)

Use the `chop` or `round` function to write a function program `[s, scf, scb] = sumreciprocal(m, k)` to return the sum of the first m terms of the sequence $\frac{1}{n}, n \in \mathbb{N}$, as `s`, the sum of the first m terms in ' k ' digit arithmetic as `scf` and finally the same sum in reverse order, that is, from $\frac{1}{m}$ to 1 in ' k ' digit arithmetic as `scb`.

Now calculate the following:

- (a) Sum up $1/n$ for $n = 1, 2, \dots, 10^3$.
- (b) Round each number $1/n$ to 5 digits and simulate the summing of the resulting sequence for $n = 1, 2, \dots, 10^3$ in 5-digit arithmetic.
- (c) Sum up the same chopped (or rounded) numbers in (b) again in 5-digit arithmetic but in reverse order, that is, for $n = 10^3, \dots, 2, 1$.

Compare the three computed results. Which among (b) and (c) is closer to (a)?

3. The solution of a system of equations $Ax = b$ can be obtained in MATLAB by setting `x = A\b`. MATLAB uses GEPP (Gaussian Elimination with Partial Pivoting) to find x for this command. [Wait for a few more classes to know the details!]

The same may also be found by setting $\mathbf{x} = \text{inv}(\mathbf{A}) * \mathbf{b}$. Write an M-file which finds the time taken by both these commands for 20 matrices with sizes increasing from 200 to 1150 in steps of 50 and plots them on a semilog scale on the same graph. Use legends to distinguish between your curves.

4. Write the following function programs to solve triangular systems of equations.
 - (a). $\mathbf{x} = \text{colbackward}(\mathbf{U}, \mathbf{b})$ to solve an upper triangular system $Ux = b$ by column oriented back substitution.
 - (b). $\mathbf{x} = \text{rowforward}(\mathbf{L}, \mathbf{b})$ to solve a lower triangular system $Lx = b$ by row oriented forward substitution.
5. Write a MATLAB function program $[\mathbf{L}, \mathbf{U}] = \text{genp}(\mathbf{A})$ which finds an LU factorization $A = LU$ of an n -by- n matrix A by performing Gaussian Elimination with no pivoting (GENP).