arXiv:2402.03664v5 [cs.LG] 27 Mar 2025

Partial Gromov-Wasserstein Metric

Yikun Bai[1], Rocio Diaz Martin[*2], Abihith Kothapalli[*1],
Hengrong Du[3], Xinran Liu[1], and Soheil Kolouri[1]

[1]Department of Computer Science, Vanderbilt University
[2]Department of Mathematics, Tufts University
[3]Department of Mathematics, University of California, Irvine
[1]yikun.bai, abi.kothapalli, xinran.liu, soheil.kolouri@vanderbilt.edu
[2]rocio.diaz_martin@tufts.edu
[3]hengrond@uci.edu

Abstract

The Gromov-Wasserstein (GW) distance has gained increasing interest in the machine learning community in recent years, as it allows for the comparison of measures in different metric spaces. To overcome the limitations imposed by the equal mass requirements of the classical GW problem, researchers have begun exploring its application in unbalanced settings. However, Unbalanced GW (UGW) can only be regarded as a discrepancy rather than a rigorous metric/distance between two metric measure spaces (mm-spaces). In this paper, we propose a particular case of the UGW problem, termed Partial Gromov-Wasserstein (PGW). We establish that PGW is a well-defined metric between mm-spaces and discuss its theoretical properties, including the existence of a minimizer for the PGW problem and the relationship between PGW and GW, among others. We then propose two variants of the Frank-Wolfe algorithm for solving the PGW problem and show that they are mathematically and computationally equivalent. Moreover, based on our PGW metric, we introduce the analogous concept of barycenters for mm-spaces. Finally, we validate the effectiveness of our PGW metric and related solvers in applications such as shape matching, shape retrieval, and shape interpolation, comparing them against existing baselines. Our code is available at https://github.com/mint-vu/PGW_Metric.

1 Introduction

The classical optimal transport (OT) problem [1] seeks to match two probability measures while minimizing the expected transportation cost. At the heart of classical OT theory lies the principle of mass conservation, which aims to optimize the transfer between two probability measures, assuming they have the same total mass and strictly preserving it. Statistical distances that arise from OT, such as Wasserstein distances, have been widely applied across various machine learning domains, ranging from generative modeling [2, 3] to domain adaptation [4] and representation learning [5]. Recent advancements have extended the OT problem to address certain limitations within machine learning applications. These advancements include: 1) facilitating the comparison of non-negative measures that possess different total masses via unbalanced [6] and partial OT [7], and 2) enabling the comparison of probability measures across distinct metric spaces through Gromov-Wasserstein distances [8], with applications spanning from quantum chemistry [9] to natural language processing [10].

Regarding the first aspect, many applications in machine learning involve comparing non-negative measures (often empirical measures) with varying total amounts of mass, e.g., domain adaptation [11]. Moreover, OT distances (or dissimilarity measures) are often not robust against outliers and noise, resulting in potentially high transportation costs for outliers. Many recent publications have focused on variants of the OT problem that allow for comparing non-negative measures with unequal mass. For instance, the optimal partial transport problem [7, 12, 13, 14, 15, 16], Kantorovich–Rubinstein norm [17, 18, 19], and the Hellinger–Kantorovich distance [20, 21]. Recent works formulating the metric properties of partial OT with total variation constraints include [22, 23]. These methods fall under the broad category of "unbalanced optimal transport." In this regard, we also highlight [24, 25, 26], which enhance OT's robustness in the presence of outliers.

[*]These authors contributed equally to this work.

Regarding the second aspect, comparing probability measures across different metric spaces is essential in many machine learning applications, ranging from computer graphics, where shapes and surfaces are compared [27, 28], to graph partitioning and matching problems [29]. Source and target distributions often arise from varied conditions, such as different times, contexts, or measurement techniques, creating substantial differences in intrinsic distances among data points. The conventional OT framework necessitates a meaningful distance across diverse domains, a requirement that is not always achievable. To circumvent this issue, the Gromov-Wasserstein (GW) distances were proposed in [8, 28] as an adaptation of the Gromov-Hausdorff distance, which measures the discrepancy between two metric spaces [30, 31, 32, 33]. The GW distance [8, 34] extends OT-based distances to metric measure spaces (mm-spaces) up to isometries. Its invariance across isomorphic mm-spaces makes the GW distance particularly valuable for applications like shape comparison and matching, where invariance to rigid motion transformations is crucial.

The main computational challenge of the GW metric is the non-convexity of its formulation [8]. The conventional computational approach relies on the Frank-Wolfe (FW) algorithm [35, 36]. Optimal transport (OT) computational methods [17, 37, 38, 39, 40, 41, 42, 43, 44], such as the Sinkhorn algorithm, can be incorporated into FW iterations, which yields the classical GW solvers [45, 46, 47].

Given that the GW distance is limited to the comparison of probability mm-spaces, recent works have introduced unbalanced and partial variations [48, 49, 50]. These variations have been applied in diverse contexts, including partial graph matching for social network analysis [51] and the alignment of brain images [52]. Although solving these unbalanced variants of the GW problem yields notions of *discrepancies* between mm-spaces, their *metric* properties remain unclear in the literature.

Motivated by the emerging applications of the GW problem in unbalanced settings, this paper focuses on developing a metric between general (not necessarily probability) mm-spaces and providing efficient solvers for its computation. Our proposed metric arises from formulating a variant of the GW problem for unbalanced contexts, rooted in the framework provided by [48], which we named the *Partial Gromov-Wasserstein* (PGW) problem. In contrast to [48], which introduces a KL-divergence penalty and a Sinkhorn solver, we employ a total variation penalty, demonstrate the resulting metric properties, and provide novel, efficient solvers for this problem. To the best of our knowledge, this paper presents the first metric for non-probability mm-spaces based on the GW distance.

Contributions. Our specific contributions to this paper are:

- **GW metric in unbalanced settings.** We propose the Partial Gromov-Wasserstein (PGW) problem and prove that it gives rise to a metric between arbitrary mm-spaces.
- **PGW solver.** [1] Analogous to the technique presented in [12], we show that the PGW problem can be turned into a variant of the GW problem. Based on this relation, we propose two mathematically equivalent, but distinct in numerical implementation, Frank-Wolfe solvers for the discrete PGW problem. Inspired by the results of [36], we prove that similar to the Frank-Wolfe solver presented in [49], our proposed solvers for the PGW problem converge linearly to a stationary point.
- **Numerical experiments.** We demonstrate the performance of our proposed algorithms in terms of computation time and efficacy on a series of tasks: shape-matching with outliers between 2D and 3D objects, shape retrieval between 2D shapes, and shape interpolation using the concept of PGW barycenters. We compare the performance of our proposed algorithms against existing baselines for each task.

2 Background

In this section, we review the basics of OT theory, one of its variants in unbalanced contexts called Partial OT (POT), and their connection as established in [12]. We then introduce the GW distance.

2.1 Optimal Transport and Partial Optimal Transport

Let $\Omega \subseteq \mathbb{R}^d$ be, for simplicity, a compact subset of $\mathbb{R}^d$, and $\mathcal{P}(\Omega)$ be the space of probability measures defined on the Borel σ-algebra of Ω.

[1] Rigorously speaking, due to the non-convexity of the GW problem and its variants, current methods achieve only local minima rather than global minima. We use the term "solver" following the convention of previous related works [48, 49]. However, it should be emphasized that the proposed methods aim to find local minima rather than global minima, similar to related and classical computational GW works.

The Optimal Transport (OT) problem for $\mu, \nu \in \mathcal{P}(\Omega)$, with transportation cost $c(x, y) : \Omega \times \Omega \to \mathbb{R}_+$ being a lower-semi continuous function is defined as:

$$OT(\mu, \nu) := \min_{\gamma \in \Gamma(\mu,\nu)} \gamma(c), \qquad \text{where} \quad \gamma(c) := \int_{\Omega^2} c(x, y)\, d\gamma(x, y) \tag{1}$$

and where $\Gamma(\mu, \nu)$ denotes the set of all joint probability measures on $\Omega^2 := \Omega \times \Omega$ with marginals μ, ν, i.e., $\gamma_1 := \pi_{1\#}\gamma = \mu, \gamma_2 := \pi_{2\#}\gamma = \nu$, where $\pi_1, \pi_2 : \Omega^2 \to \Omega$ are the canonical projections $\pi_1(x, y) := x, \pi_2(x, y) := y$. A minimizer for (1) always exists [1, 53] and when $c(x, y) = \|x - y\|^p$, for $p \geq 1$, it defines a metric on $\mathcal{P}(\Omega)$, which is referred to as the "p-Wasserstein distance":

$$W_p^p(\mu, \nu) := \min_{\gamma \in \Gamma(\mu,\nu)} \int_{\Omega^2} \|x - y\|^p d\gamma(x, y). \tag{2}$$

The Partial Optimal Transport (POT) problem [6, 13, 16] extends the OT problem to the set of Radon measures $\mathcal{M}_+(\Omega)$, i.e., non-negative and finite measures. For $\lambda > 0$ and $\mu, \nu \in \mathcal{M}_+(\Omega)$, the POT problem is defined as:

$$POT(\mu, \nu; \lambda) := \inf_{\gamma \in \mathcal{M}_+(\Omega^2)} \gamma(c) + \lambda(|\mu - \gamma_1| + |\nu - \gamma_2|), \tag{3}$$

where, in general, $|\sigma|$ denotes the total variation norm of a measure σ, i.e., $|\sigma| := \sigma(\Omega)$. The constraint $\gamma \in \mathcal{M}_+(\Omega^2)$ in (3) can be further restricted to $\gamma \in \Gamma_{\leq}(\mu, \nu)$:

$$\Gamma_{\leq}(\mu, \nu) := \{\gamma \in \mathcal{M}_+(\Omega^2) : \gamma_1 \leq \mu, \gamma_2 \leq \nu\},$$

denoting $\gamma_1 \leq \mu$ if for any Borel set $B \subseteq \Omega$, $\gamma_1(B) \leq \mu(B)$ (respectively, for $\gamma_2 \leq \nu$) [7]. Roughly speaking, the linear penalization indicates that if the classical transportation cost exceeds 2λ, it is better to create/destroy' mass (see [44] for further details).

The relationship between POT and OT. By using the techniques in [12], the POT problem can be transferred into an OT problem, and thus, OT solvers (e.g., network simplex) can be employed to solve the POT problem.

Proposition 2.1. *[12, 44] Given $\mu, \nu \in \mathcal{M}_+(\Omega)$, construct the following measures on $\hat{\Omega} := \Omega \cup \{\hat{\infty}\}$, for an auxiliary point $\hat{\infty}$:*

$$\hat{\mu} = \mu + |\nu|\delta_{\hat{\infty}} \qquad \text{and} \qquad \hat{\nu} = \nu + |\mu|\delta_{\hat{\infty}}. \tag{4}$$

Consider the following OT problem

$$OT(\hat{\mu}, \hat{\nu}) = \min_{\hat{\gamma} \in \Gamma(\hat{\mu},\hat{\nu})} \hat{\gamma}(\hat{c}), \qquad \text{where} \quad \hat{c}(x, y) := \begin{cases} c(x, y) - 2\lambda & \text{if } x, y \in \Omega, \\ 0 & \text{elsewhere.} \end{cases} \tag{5}$$

Then, there exists a bijection $F : \Gamma_{\leq}(\mu, \nu) \to \Gamma(\hat{\mu}, \hat{\nu})$ given by

$$F(\gamma) := \gamma + (\mu - \gamma_1) \otimes \delta_{\hat{\infty}} + \delta_{\hat{\infty}} \otimes (\nu - \gamma_2) + |\gamma|\delta_{\hat{\infty},\hat{\infty}}. \tag{6}$$

such that γ is optimal for the POT problem (3) if and only if $F(\gamma)$ is optimal for the OT problem (5).

It is worth noting that instead of considering the same underlying space Ω for both measures μ and ν, the OT and POT problems can be formulated in the scenario where μ and ν are defined on different metric spaces X and Y, respectively. In this setting, one needs a cost function $c : X \times Y \to \mathbb{R}_+$ to formulate the OT and POT problems. However, in practice, it is usually difficult to define reasonable 'distance' or *ground cost* $c(\cdot, \cdot)$ between the two spaces X and Y. In particular, the p-Wasserstein distance cannot be adopted if μ, ν are defined on different spaces. To relax this requirement, in the next section, we will review the fundamentals of the *Gromov-Wasserstein* problem [8].

2.2 The Gromov-Wasserstein (GW) Problem

A metric measure space (mm-space) consists of a set X endowed with a metric structure, that is, a notion of distance d_X between its elements, and equipped with a Borel measure μ. As in [8, Ch. 5], we will assume that X is compact and that $\text{supp}(\mu) = X$. Given two probability mm-spaces $\mathbb{X} = (X, d_X, \mu)$, $\mathbb{Y} = (Y, d_Y, \nu)$, with $\mu \in \mathcal{P}(X)$ and $\nu \in \mathcal{P}(Y)$, and a non-negative lower semi-continuous cost function $L : \mathbb{R}^2 \to \mathbb{R}_+$ (e.g., the Euclidean distance or the KL-loss), the Gromov-Wasserstein (GW) matching problem is defined as:

$$GW^L(\mathbb{X}, \mathbb{Y}) := \inf_{\gamma \in \Gamma(\mu,\nu)} \gamma^{\otimes 2}(L(d_X(\cdot, \cdot), d_Y(\cdot, \cdot))), \tag{7}$$

Acknowledgments

This research was partially supported by the NSF CAREER Award No. 2339898.

References

[1] Cedric Villani. *Optimal transport: old and new*. Springer, 2009.

[2] Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein generative adversarial networks. In *International conference on machine learning*, pages 214–223. PMLR, 2017.

[3] Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron C Courville. Improved training of wasserstein gans. *Advances in neural information processing systems*, 30, 2017.

[4] Nicolas Courty, Rémi Flamary, Amaury Habrard, and Alain Rakotomamonjy. Joint distribution optimal transportation for domain adaptation. *Advances in neural information processing systems*, 30, 2017.

[5] Soheil Kolouri, Navid Naderializadeh, Gustavo K Rohde, and Heiko Hoffmann. Wasserstein embedding for graph learning. In *International Conference on Learning Representations*, 2020.

[6] Lenaic Chizat, Gabriel Peyré, Bernhard Schmitzer, and François-Xavier Vialard. Unbalanced optimal transport: Dynamic and Kantorovich formulations. *Journal of Functional Analysis*, 274(11):3090–3123, 2018.

[7] Alessio Figalli. The optimal partial transport problem. *Archive for rational mechanics and analysis*, 195(2):533–560, 2010.

[8] Facundo Mémoli. Gromov–wasserstein distances and the metric approach to object matching. *Foundations of computational mathematics*, 11:417–487, 2011.

[9] Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural message passing for quantum chemistry. In *International conference on machine learning*, pages 1263–1272. PMLR, 2017.

[10] David Alvarez-Melis and Tommi Jaakkola. Gromov-wasserstein alignment of word embedding spaces. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 1881–1890, 2018.

[11] Kilian Fatras, Thibault Séjourné, Rémi Flamary, and Nicolas Courty. Unbalanced minibatch optimal transport; applications to domain adaptation. In *International Conference on Machine Learning*, pages 3186–3197. PMLR, 2021.

[12] Luis A Caffarelli and Robert J McCann. Free boundaries in optimal transport and monge-ampere obstacle problems. *Annals of mathematics*, pages 673–730, 2010.

[13] Alessio Figalli and Nicola Gigli. A new transportation distance between non-negative measures, with applications to gradients flows with dirichlet boundary conditions. *Journal de mathématiques pures et appliquées*, 94(2):107–130, 2010.

[14] Anh Duc Nguyen, Tuan Dung Nguyen, Quang Nguyen, Hoang Nguyen, Lam M. Nguyen, and Kim-Chuan Toh. On partial optimal transport: Revised sinkhorn and efficient gradient methods. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, 2024.

[15] Tryphon T Georgiou, Johan Karlsson, and Mir Shahrouz Takyar. Metrics for power spectra: an axiomatic approach. *IEEE Transactions on Signal Processing*, 57(3):859–867, 2008.

[16] Benedetto Piccoli and Francesco Rossi. Generalized wasserstein distance and its application to transport equations with source. *Archive for Rational Mechanics and Analysis*, 211:335–358, 2014.

[17] Kevin Guittet. *Extended Kantorovich norms: a tool for optimization*. PhD thesis, INRIA, 2002.

[18] Florian Heinemann, Marcel Klatt, and Axel Munk. Kantorovich–rubinstein distance and barycenter for finitely supported measures: Foundations and algorithms. *Applied Mathematics & Optimization*, 87(1):4, 2023.

[19] Jan Lellmann, Dirk A Lorenz, Carola Schonlieb, and Tuomo Valkonen. Imaging with kantorovich–rubinstein discrepancy. *SIAM Journal on Imaging Sciences*, 7(4):2833–2859, 2014.

[20] Lenaic Chizat, Gabriel Peyré, Bernhard Schmitzer, and François-Xavier Vialard. An interpolating distance between optimal transport and Fisher–Rao metrics. *Foundations of Computational Mathematics*, 18(1):1–44, 2018.

[21] Matthias Liero, Alexander Mielke, and Giuseppe Savare. Optimal entropy-transport problems and a new Hellinger–Kantorovich distance between positive measures. *Inventiones mathematicae*, 211(3):969–1117, 2018.

[22] Sharath Raghvendra, Pouyan Shirzadian, and Kaiyi Zhang. A new robust partial p-wasserstein-based metric for comparing distributions. *arXiv preprint arXiv:2405.03664*, 2024.

[23] Sloan Nietert, Rachel Cummings, and Ziv Goldfeld. Robust estimation under the wasserstein distance. *arXiv preprint arXiv:2302.01237*, 2023.

[24] Yogesh Balaji, Rama Chellappa, and Soheil Feizi. Robust optimal transport with applications in generative modeling and domain adaptation. *Advances in Neural Information Processing Systems*, 33:12934–12944, 2020.

[25] Quang Minh Nguyen, Hoang H Nguyen, Yi Zhou, and Lam M Nguyen. On unbalanced optimal transport: Gradient methods, sparsity and approximation error. *The Journal of Machine Learning Research*, 2023.

[26] Khang Le, Huy Nguyen, Quang M Nguyen, Tung Pham, Hung Bui, and Nhat Ho. On robust optimal transport: Computational complexity and barycenter computation. *Advances in Neural Information Processing Systems*, 34:21947–21959, 2021.

[27] Alexander M Bronstein, Michael M Bronstein, and Ron Kimmel. Generalized multidimensional scaling: a framework for isometry-invariant partial surface matching. *Proceedings of the National Academy of Sciences*, 103(5):1168–1172, 2006.

[28] Facundo Mémoli. Spectral gromov-wasserstein distances for shape matching. In *2009 IEEE 12th International Conference on Computer Vision Workshops, ICCV Workshops*, pages 256–263. IEEE, 2009.

[29] Hongteng Xu, Dixin Luo, and Lawrence Carin. Scalable gromov-wasserstein learning for graph partitioning and matching. *Advances in neural information processing systems*, 32, 2019.

[30] David A Edwards. The structure of superspace. In *Studies in topology*, pages 121–133. Elsevier, 1975.

[31] Mikhael Gromov. Structures métriques pour les variétés riemanniennes. *Textes Math.*, 1, 1981.

[32] Michael Gromov. Groups of polynomial growth and expanding maps (with an appendix by jacques tits). *Publications Mathématiques de l'IHÉS*, 53:53–78, 1981.

[33] Dmitri Burago, Yuri Burago, Sergei Ivanov, et al. *A course in metric geometry*, volume 33. American Mathematical Society Providence, 2001.

[34] Karl-Theodor Sturm. *The space of spaces: curvature bounds and gradient flows on the space of metric measure spaces*, volume 290. American Mathematical Society, 2023.

[35] Marguerite Frank, Philip Wolfe, et al. An algorithm for quadratic programming. *Naval research logistics quarterly*, 3(1-2):95–110, 1956.

[36] Simon Lacoste-Julien. Convergence rate of frank-wolfe for non-convex objectives. *arXiv preprint arXiv:1607.00345*, 2016.

[37] Marco Cuturi. Sinkhorn distances: Lightspeed computation of optimal transport. *Advances in neural information processing systems*, 26, 2013.

[38] Nicolas Papadakis, Gabriel Peyré, and Edouard Oudet. Optimal transport with proximal splitting. *SIAM Journal on Imaging Sciences*, 7(1):212–238, 2014.

[39] Jean-David Benamou, Brittany D Froese, and Adam M Oberman. Numerical solution of the optimal transportation problem using the monge–ampère equation. *Journal of Computational Physics*, 260:107–126, 2014.

[40] Jean-David Benamou, Guillaume Carlier, Marco Cuturi, Luca Nenna, and Gabriel Peyré. Iterative bregman projections for regularized transportation problems. *SIAM Journal on Scientific Computing*, 37(2):A1111–A1138, 2015.

[41] Gabriel Peyré, Marco Cuturi, et al. Computational optimal transport: With applications to data science. *Foundations and Trends® in Machine Learning*, 11(5-6):355–607, 2019.

[42] Lenaic Chizat, Gabriel Peyré, Bernhard Schmitzer, and François-Xavier Vialard. Scaling algorithms for unbalanced optimal transport problems. *Mathematics of Computation*, 87(314):2563–2609, 2018.

[43] Nicolas Bonneel and David Coeurjolly. SPOT: sliced partial optimal transport. *ACM Transactions on Graphics*, 38(4):1–13, 2019.

[44] Yikun Bai, Bernhard Schmitzer, Matthew Thorpe, and Soheil Kolouri. Sliced optimal partial transport. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 13681–13690, 2023.

[45] Gabriel Peyré, Marco Cuturi, and Justin Solomon. Gromov-wasserstein averaging of kernel and distance matrices. In *International conference on machine learning*, pages 2664–2672. PMLR, 2016.

[46] Hongteng Xu, Dixin Luo, Hongyuan Zha, and Lawrence Carin Duke. Gromov-wasserstein learning for graph matching and node embedding. In *International conference on machine learning*, pages 6932–6941. PMLR, 2019.

[47] Vayer Titouan, Nicolas Courty, Romain Tavenard, and Rémi Flamary. Optimal transport for structured data with application on graphs. In *International Conference on Machine Learning*, pages 6275–6284. PMLR, 2019.

[48] Thibault Séjourné, François-Xavier Vialard, and Gabriel Peyré. The unbalanced gromov wasserstein distance: Conic formulation and relaxation. *Advances in Neural Information Processing Systems*, 34:8766–8779, 2021.

[49] Laetitia Chapel, Mokhtar Z Alaya, and Gilles Gasso. Partial optimal tranport with applications on positive-unlabeled learning. *Advances in Neural Information Processing Systems*, 33:2903–2913, 2020.

[50] Nicolò De Ponti and Andrea Mondino. Entropy-transport distances between unbalanced metric measure spaces. *Probability Theory and Related Fields*, 184(1-2):159–208, 2022.

[51] Weijie Liu, Chao Zhang, Jiahao Xie, Zebang Shen, Hui Qian, and Nenggan Zheng. Partial gromov-wasserstein learning for partial graph matching. *arXiv preprint arXiv:2012.01252*, 2020.

[52] Alexis Thual, Quang Huy Tran, Tatiana Zemskova, Nicolas Courty, Rémi Flamary, Stanislas Dehaene, and Bertrand Thirion. Aligning individual brains with fused unbalanced gromov wasserstein. *Advances in Neural Information Processing Systems*, 35:21792–21804, 2022.

[53] Cédric Villani. *Topics in optimal transportation*, volume 58. American Mathematical Soc., 2021.

[54] Lemin Kong, Jiajin Li, Jianheng Tang, and Anthony Man-Cho So. Outlier-robust gromov-wasserstein for graph data. *Advances in Neural Information Processing Systems*, 36, 2024.

[55] Florian Beier, Robert Beinert, and Gabriele Steidl. On a linear gromov–wasserstein distance. *IEEE Transactions on Image Processing*, 31:7292–7305, 2022.

[56] Vayer Titouan, Nicolas Courty, Romain Tavenard, Chapel Laetitia, and Rémi Flamary. Optimal transport for structured data with application on graphs. In Kamalika Chaudhuri and Ruslan Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pages 6275–6284, Long Beach, California, USA, 09–15 Jun 2019. PMLR.

[57] Xinran Liu, Yikun Bai, Huy Tran, Zhanqi Zhu, Matthew Thorpe, and Soheil Kolouri. Ptlp: Partial transport l^p distances. In *NeurIPS 2023 Workshop Optimal Transport and Machine Learning*, 2023.

[58] Filippo Santambrogio. Optimal transport for applied mathematicians. *Birkäuser, NY*, 55(58-63):94, 2015.

[59] Cedric Cagniart, Edmond Boyer, and Slobodan Ilic. Free-form mesh tracking: a patch-based approach. In *2010 IEEE Computer Society Conference on Computer Vision and Pattern Recognition*, pages 1339–1346. IEEE, 2010.

[60] Zixuan Cang, Yaqi Wu, and Yanxiang Zhao. Supervised gromov-wasserstein optimal transport. *arXiv preprint arXiv:2401.06266*, 2024.

[61] Marco Cuturi and Arnaud Doucet. Fast computation of wasserstein barycenters. In *International conference on machine learning*, pages 685–693. PMLR, 2014.

[62] Cedric Villani. *Topics in Optimal Transportation*. American Mathematical Society, 2003.

[63] M Gromov. Metric structures for riemannian and non-riemannian spaces. *Bulletin of the American Mathematical Society*, 38:353–363, 2001.

[64] Rémi Flamary, Nicolas Courty, Alexandre Gramfort, Mokhtar Z. Alaya, Aurélie Boisbunon, Stanislas Chambon, Laetitia Chapel, Adrien Corenflos, Kilian Fatras, Nemo Fournier, Léo Gautheron, Nathalie T.H. Gayraud, Hicham Janati, Alain Rakotomamonjy, Ievgen Redko, Antoine Rolet, Antony Schutz, Vivien Seguy, Danica J. Sutherland, Romain Tavenard, Alexander Tong, and Titouan Vayer. Pot: Python optimal transport. *Journal of Machine Learning Research*, 22(78):1–8, 2021.

[65] Jessa Bekker and Jesse Davis. Learning from positive and unlabeled data: A survey. *Machine Learning*, 109:719–760, 2020.

[66] Charles Elkan and Keith Noto. Learning classifiers from only positive and unlabeled data. In *Proceedings of the 14th ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 213–220, 2008.

[67] Masahiro Kato, Takeshi Teshima, and Junya Honda. Learning from positive and unlabeled data with a selection bias. In *International conference on learning representations*, 2018.

[68] Yu-Guan Hsieh, Gang Niu, and Masashi Sugiyama. Classification from positive, unlabeled and biased negative data. In *International Conference on Machine Learning*, pages 2820–2829. PMLR, 2019.

[69] Kate Saenko, Brian Kulis, Mario Fritz, and Trevor Darrell. Adapting visual category models to new domains. In *Computer Vision–ECCV 2010: 11th European Conference on Computer Vision, Heraklion, Crete, Greece, September 5-11, 2010, Proceedings, Part IV 11*, pages 213–226. Springer, 2010.

[70] Jeff Donahue, Yangqing Jia, Oriol Vinyals, Judy Hoffman, Ning Zhang, Eric Tzeng, and Trevor Darrell. Decaf: A deep convolutional activation feature for generic visual recognition. In *International conference on machine learning*, pages 647–655. PMLR, 2014.

[71] Thibault Séjourné, Clément Bonet, Kilian Fatras, Kimia Nadjahi, and Nicolas Courty. Unbalanced optimal transport meets sliced-wasserstein. *arXiv preprint arXiv:2306.07176*, 2023.

A Notation and Abbreviations

- OT: Optimal Transport.
- POT: Partial Optimal Transport.
- GW: Gromov-Wasserstein.
- PGW: Partial Gromov-Wasserstein.
- FW: Frank-Wolfe.
- MPGW: Mass-Constrained Partial Gromov-Wasserstein.
- $\|\cdot\|$: Euclidean norm.
- $X^2 = X \times X$.
- $\mathcal{M}_+(X)$: set of all positive (non-negative) Randon (finite) measures defined on X.
- $\mathcal{P}_2(X)$: set of all probability measures defined on X, whose second moment is finite.
- $\mathbb{R}_+$: set of all non-negative real numbers.
- $\mathbb{R}^{n\times m}$: set of all $n \times m$ matrices with real coefficients.
- $\mathbb{R}_+^{n\times m}$ (resp. $\mathbb{R}_+^n$): set of all $n \times m$ matrices (resp., n-vectors) with non-negative coefficients.
- $\mathbb{R}^{n\times m\times n\times m}$: set of all $n \times m \times n \times m$ tensors with real coefficients.
- $1_n, 1_{n\times m}, 1_{n\times m\times n\times m}$: vector, matrix, and tensor of all ones.
- $\mathbb{1}_E$: characteristic function of a measurable set E

$$\mathbb{1}_E(z) = \begin{cases} 1 & \text{if } z \in E, \\ 0 & \text{otherwise.} \end{cases}$$

- $\mathbb{X}, \mathbb{Y}$: metric measure spaces (mm-spaces): $\mathbb{X} = (X, d_X, \mu)$, $\mathbb{Y} = (Y, d_Y, \nu)$.
- C^X: given a discrete mm-space $\mathbb{X} = (X, d_X, \mu)$, where $X = \{x_1, \ldots, x_n\}$, the symmetric matrix $C^X \in \mathbb{R}^{n\times n}$ is defined as $C^X_{i,i'} = d_X^q(x_i, x_i')$.
- $\mu^{\otimes 2}$: product measure $\mu \otimes \mu$.
- $T_\#\sigma$: $T : X \to Y$ is a measurable function and σ is a measure on X. $T_\#\sigma$ is the push-forward measure of σ, i.e., its is the measure on Y such that for all Borel set $A \subset Y$, $T_\#\sigma(A) = \sigma(T^{-1}(A))$.
- $\gamma, \gamma_1, \gamma_2$: γ is a joint measure defined in a product space having γ_1, γ_2 as its first and second marginals, respectively. In the discrete setting, they are viewed as matrices and vectors, i.e., $\gamma \in \mathbb{R}_+^{n\times m}$, and $\gamma_1 = \gamma 1_m \in \mathbb{R}_+^n$, $\gamma_2 = \gamma^\top 1_n \in \mathbb{R}_+^m$.
- $\pi_1 : X \times Y \to X$, canonical projection mapping, with $(x, y) \mapsto x$. Similarly, $\pi_2 : X \times Y \to Y$ is canonical projection mapping, with $(x, y) \mapsto y$.
- $\pi_{1,2} : S \times X \times Y \to X \times Y$, canonical projection mapping, with $(s, x, y) \to (x, y)$. Similarly, $\pi_{0,1}$ maps (s, x, y) to (s, x); $\pi_{0,2}$ maps (s, x, y) to (s, y).
- $\Gamma(\mu, \nu)$, where $\mu \in \mathcal{P}_2(X), \nu \in \mathcal{P}_2(Y)$ (where X, Y may not necessarily be the same set): it is the set of all the couplings (transportation plans) between μ and ν, i.e., $\Gamma(\mu, \nu) := \{\gamma \in \mathcal{P}_2(X \times Y) : \gamma_1 = \mu, \gamma_2 = \nu\}$.
- $\Gamma(\mathrm{p}, \mathrm{q})$: set of all the couplings between the discrete probability measures $\mu = \sum_{i=1}^n p_i^X \delta_{x_i}$ and $\nu = \sum_{j=1}^m q_j^Y \delta_{y_j}$ with weight vectors

$$\mathrm{p} = [p_1^X, \ldots, p_n^X]^\top \qquad \text{and} \qquad \mathrm{q} = [q_1^Y, \ldots, q_m^Y]^\top. \tag{20}$$

  That is, $\Gamma(\mathrm{p}, \mathrm{q})$ coincides with $\Gamma(\mu, \nu)$, but it is viewed as a subset of $n \times m$ matrices defined in (12).